

Data sheet

3VA2612-7HM37-0AA0



circuit breaker 3VA2 IEC Frame 1250 breaking capacity class C $I_{cu}=110\text{ kA}$ @ 415 V 3-pole line protection ETU330 LIG $I_{n}=1250\text{ A}$ overload protection $I_{r}=500\text{ A}$...1250 A short-circuit protection $I_{i}=15\ldots10 \times I_n$ ground-fault protection $I_{g}=02\ldots1 \times I_n$ $t_g=01/03\text{s}$ circuit breaker with straight bus connectors extended


Model	
product brand name	SENTRON
product designation	Molded case circuit breaker
design of the product	Line protection
design of the overcurrent release	ETU330
protection function of the overcurrent release	LIG
number of poles	3
General technical data	
insulation voltage / rated value	800 V
operating voltage / at AC / rated value	690 V
power loss [W] / maximum	516 W
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	172 W
mechanical service life (operating cycles) / typical	10 000
electrical endurance (operating cycles) / at AC-1 / at 380/415 V	4 600
electrical endurance (operating cycles) / at AC-1 / at 690 V	3 200
product feature / for neutral conductors / upgradable/retrofittable / short-circuit and overload proof	No
ground-fault monitoring version	Summation current formation L-conductor
product function	
• communication function	No
• other measurement function	No
Net Weight	22.6 kg
Current	
operational current	
• at 40 °C	1 250 A
• at 45 °C	1 250 A
• at 50 °C	1 250 A
• at 55 °C	1 187 A
• at 60 °C	1 125 A
• at 65 °C	1 000 A
• at 70 °C	875 A
Switching capacity according to IEC 60947	
switching capacity class of the circuit breaker	C
maximum short-circuit current breaking capacity (I_{cu})	
• at 240 V	200 kA
• at 415 V	110 kA
• at 440 V	110 kA
• at 500 V	85 kA
• at 690 V	35 kA
operating short-circuit current breaking capacity (I_{cs})	

• at 240 V	150 kA
• at 415 V	85 kA
• at 440 V	70 kA
• at 500 V	65 kA
• at 690 V	19 kA
short-circuit current making capacity (Icm)	
• at 240 V	440 kA
• at 415 V	242 kA
• at 440 V	242 kA
• at 500 V	187 kA
• at 690 V	73.5 kA
Adjustable parameters	
product feature / for L-tripping / can be switched on/off	No
adjustable response value setting current (Ir) / of the L-trip / with I _{2t} characteristic	
• minimum	500 A
• maximum	1 250 A
adjustable response value delay time (tr) / for L-tripping / with I _{2t} characteristic	
• minimum	0.5 s
• maximum	17 s
adjustable response value setting current (li) / for I-tripping	
• minimum	1 875 A
• maximum	12 500 A
adjustable current response value current / for G-tripping / with standard characteristic	
• initial value	250 A
• full-scale value	1 250 A
adjustable response value delay time (tg) / for G-tripping / with I _{0t} characteristic	
• minimum	0.1 s
• maximum	0.3 s
adjustable setting current (InN) / for N-tripping	
• minimum	0 A
• maximum	0 A
product function / grounding protection	Yes
Mechanical Design	
product component	
• undervoltage release	No
• voltage trigger	No
• trip indicator	No
height [in]	12.6 in
height	320 mm
width [in]	8.27 in
width	210 mm
depth [in]	4.72 in
depth	120 mm
Connections	
arrangement of electrical connectors / for main current circuit	Front terminal
type of electrical connection / for main current circuit	busbar connection pieces extended on two sides
design of the surface / of the connections / on the top of the switch (N, 1, 3, 5)	silver
design of the surface / of the connections / on the bottom of the switch (N, 2, 4, 6)	silver
Auxiliary circuit	
number of CO contacts / for auxiliary contacts	0
Accessories	
product extension / optional / motor drive	No
Environmental conditions	
protection class IP / on the front	IP40
ambient temperature	
• during operation / minimum	-25 °C

• during operation / maximum	70 °C
• during storage / minimum	-40 °C
• during storage / maximum	80 °C
reference code / according to IEC 81346-2	Q

Approvals / Certificates	EMV	Test Certificates	Maritime application
General Product Approval			

[Miscellaneous](#)   [Miscellaneous](#) [Type Test Certificates/Test Report](#) 

other	Dangerous goods	Environment			
Confirmation	 产品合格 QC PASS	Miscellaneous	Transport Information	Environmental Confirmations	Environmental Confirmations

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

<http://support.industry.siliconvalley.com/www/en/view/10001000>

Information- and Downloadcenter (Cat. No. 6EP0000-0000)

<http://www.siemens.com/novvoltage/catalog>

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA2612-7HM37-0AA0>

Service&Support (Manuals Certificates Characteristics FAQs)


<https://support.industry.siemens.com/cs/ww/en/ns/3VA2612-ZHM37-0AA0>


<https://support.industry.siemens.com>

Image database (product in)

<http://www.automation.com>

CAx-Online-Generator
<http://www.siemens.com/cax>





last modified:

4/3/2025

