



Main

Range of product	Canalis
Range compatibility	KS busbar trunking KT busbar trunking
Offer type	Standard
Product or component type	Tap-off unit
Busbar trunking compatibility	Canalis KS busbar trunkingplug-in Canalis KT busbar trunking with KS type plug-in
[Ie] rated operational current	400 A at 35 °C
Protection type	Circuit breaker: NSX400
Provided equipment	circuit breaker to be ordered separately
Mounting mode	Plug-in with fixed polarity
Tap-off unit polarity	3L+N+PE
Colour	White (RAL 9001)

Complementary

Device application	Medium power distribution
[Ue] rated operational voltage	230...690 V depending on protective device
[Uimp] rated impulse withstand voltage	6.8 kV
[Ui] rated insulation voltage	400 V depending on protective device 500 V depending on protective device 690 V depending on protective device
Network frequency	50/60 Hz
Control type	Rotary handle
Electrical connection	Crimp lug - ISO50 240 mm² flexible Crimp lug - ISO50 240 mm² rigid
Door/Cover opening side	Right
Tap-off unit disconnection mode	By rotary operating handle
Number of openings	2 openings for FL21 gland plate
Standards	IEC 61439-6

Body material	Metal
Width	732 mm
Depth	350 mm
Depth (door open)	976.5 mm
Height	438 mm
Net weight	18 kg

Environment

Earthing system	TT TN-S IT
IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------

