2057743-2 ACTIVE

IMPACT

TE Internal #: 2057743-2

96 Position High Speed Backplane Connector, 6 Row, 16 Column, PCB Mount Header, Vertical, Fully Shrouded, 1.9 mm [.075 in]

Centerline, IMPACT

View on TE.com >



Connectors > PCB Connectors > Backplane Connectors > High Speed Backplane Connectors



Number of Positions: 96

Row-to-Row Spacing: 1.35 mm [.053 in]

Mating Alignment: With

Mating Alignment Type: Guide Pin

Number of Rows: 6

Features

Product Type Features

Signal Arrangement	Differential
Connector & Contact Terminates To	Printed Circuit Board
Connector System	Board-to-Board
PCB Connector Type	PCB Mount Header
Shroud Style	Fully Shrouded
Configuration Features	
Number of Pairs	32
Number of Ground Positions	32
Number of Signal Positions	64
Stackable	No
Number of Positions	96
Number of Rows	6
Number of Columns	16
PCB Mount Orientation	Vertical
Guide Location	Right
Electrical Characteristics	
Operating Voltage	30 VDC

Signal Characteristics



Data Rate	25 Gb/s
Number of Differential Pairs per Column	2
Body Features	
Primary Product Color	Black
Contact Features	
Contact Underplating Material	Nickel
Contact Underplating Material Thickness	1.27 μm[50 μin]
PCB Contact Termination Area Plating Material Finish	Matte
Contact Mating Area Plating Material Thickness	.76 μm[29.92 μin]
Contact Shape & Form	Dual Beam
PCB Contact Termination Area Plating Material Thickness	1.27 μm[50 μin]
Contact Layout	Inline
Contact Mating Area Plating Material	Gold (Au)
Contact Mating Area Length	4.9 mm[.193 in]
Contact Base Material	Copper Alloy
PCB Contact Termination Area Plating Material	Tin
Contact Type	Pin
Contact Current Rating (Max)	.75 A
Termination Features	
Termination Method to PCB	Through Hole - Press-Fit
Termination Post & Tail Length	1.4 mm[.055 in]
Mechanical Attachment	
Guide Hardware	With
Guide Hardware PCB Mount Retention	With
PCB Mount Retention	With
PCB Mount Retention Mating Retention	Without
PCB Mount Retention Mating Retention PCB Mount Retention Type	With Without Action/Compliant Tail & Screw
PCB Mount Retention Mating Retention PCB Mount Retention Type PCB Mount Alignment Type	With Without Action/Compliant Tail & Screw Locating Posts
PCB Mount Retention Mating Retention PCB Mount Retention Type PCB Mount Alignment Type Mating Alignment	With Without Action/Compliant Tail & Screw Locating Posts With
PCB Mount Retention Mating Retention PCB Mount Retention Type PCB Mount Alignment Type Mating Alignment Mating Alignment Type	With Without Action/Compliant Tail & Screw Locating Posts With Guide Pin
PCB Mount Retention Mating Retention PCB Mount Retention Type PCB Mount Alignment Type Mating Alignment Mating Alignment Type Connector Mounting Type	With Without Action/Compliant Tail & Screw Locating Posts With Guide Pin



End Wall Location	Left
Housing Material	LCP (Liquid Crystal Polymer)
Centerline (Pitch)	1.9 mm[.075 in]
Dimensions	
Connector Width	12.7 mm[.5 in]
	.039 in
PCB Hole Diameter	.39 mm[.015 in]
Connector Height	11.95 mm[.47 in]
Connector Length	38.3 mm[1.508 in]
Row-to-Row Spacing	1.35 mm[.053 in]
Usage Conditions	
Operating Temperature Range	-55 – 85 °C[-67 – 185 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Compatible With Approved Standards Products	UL E28476
Packaging Features	
Packaging Method	Box & Tube

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability




Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | IMPACT



Customers Also Bought













TE Part #2007836-2 IMP100S,H,V4P16C,UG,OEW39,4.9



TE Part #2007820-1 IMP100S,H,V4P10C,UG,OEW39,4.5



TE Part #100751-1 Z-PACK/N M-HSG 3P.







Documents

Product Drawings

IMP100S,H,V2P16C,RG,LEW39,4.9

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2057743-2_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2057743-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2057743-2_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Agency Approvals

Agency Approval Document

English