TE Internal #: 350436-2

Closed Ring Tongue Terminal, 18 – 14 AWG, #10 Stud, 5.18 mm [.

204 in] Stud Diameter, Open Barrel, Straight, Tin Plating,

Uninsulated

View on TE.com >



Terminals & Splices > Ring Terminals











Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: 1624 – 4106 CMA

Stud Size: #10

Features

Product Type Features

Shape Description	Anti-Rotational/Grounding
Terminal Features	Sheared
Ring Terminal Product Type	Closed Ring Tongue Terminal
Stud Size	#10
Sealable	No
Compatible With Discrete Wire Type	Stranded
Wire Insulation Support Retention Type	Insulation Support
Configuration Features	
Number of Holes	1
Body Features	
Product Weight	.572 g
Contact Features	
Contact Base Material	Steel
Barrel Type	Open
Terminal Orientation	Straight

Tin

Terminal Plating Material



Contact Underplating Material	Nickel
Mechanical Attachment	
Wire Insulation Support	With
Dimensions	
	.105 in
Wire Size	1624 – 4106 CMA
Stud Diameter	5.18 mm[.204 in]
Tongue Thickness	.76 mm[.03 in]
Product Length	18.29 mm[.72 in]
Barrel Inside Diameter	1.62 mm, 3.17 mm[.064 in][.125 in]
Compatible Insulation Diameter (Max)	3.68 mm[.145 in]
Compatible Insulation Diameter Range	2.67 – 3.68 mm[.105 – .145 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-40 - 110 °C[-40 - 230 °F]
Operation/Application	
Compatible With Wire Base Material	Copper
Industry Standards	
Government Qualified Terminal	No
Packaging Features	
Packaging Quantity	10000
Packaging Method	Strip/Reel
Product Compliance	
For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold

Current ECHA Candidate List: JAN 2025

Does not contain REACH SVHC

Candidate List Declared Against: JAN 2025

(247)

(247)

EU REACH Regulation (EC) No. 1907/2006



Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per
	homogenous material. Also BFR/CFR/PVC
	Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 2150008-1
OCEAN_2.0_Applicator-E-130F180FREM



TE Part # 7-2150008-7

OCEAN_2.0_SPARE_PART_KIT130F180F



TE Part # 61359-1 RING GR ANTI ROTATIONAL 18-14 AWG PTPST



TE Part # 2150008-2

OCEAN_2.0_Applicator-E-130F180FREA






Customers Also Bought























Documents

Product Drawings

RING TERMINAL 18-14 AWG TPST

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_350436-2_AA.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_350436-2_AA.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_350436-2_AA.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English