

ENGLISH

Datasheet

Stock No: 282-0626

RS Pro Black Nylon Rod, 1000mm x 10mm Diameter



Product Details

Nylon 6

Black extruded Nylon 6 containing MoS₂

Good sliding and dry running properties

Resistant to oils, grease, petrol etc.

Easily welded, bonded, machined and polished

UV and weather resistant

Suitable for friction bearings/strips, gears, castors, pulleys, chains, wheels and machine parts etc

Black in colour

Tolerance thickness sheets: +0.2 mm → +0.9 mm

| Max. Service Temp. (Long Term) | +100°C |
|--------------------------------|--------------------|
| Elongation | 40% |
| Tensile Strength | 60-85 MPa |
| Hardness (Rockwell-Shore D) | M88 (Rockwell) |
| Flammability Rating | UL 94 HB |
| Water Absorption | 8-9% at saturation |

Note

This material is not electrically insulating

Natural & Cast Nylon

These materials have good chemical, abrasion and UV resistance, are easy to machine and possess good selflubricating qualities. They are resistant to hot water and can be welded.





Specifications

| Colour | Black |
|-------------------------------|-----------|
| Length | 1000mm |
| Material | Nylon |
| Form | Rod |
| Rod Diameter | 10mm |
| Density | 1.14g/cm³ |
| Tensile Strength | 75 MPa |
| Flammability Rating | UL 94 HB |
| Water Absorption | 8 to 9% |
| Elongation | 25% |
| Maximum Operating Temperature | +160°C |