

MGQM, Compact Guide Cylinder, Slide Bearing configurator MGQM16-75

Datasheet

The solution for a linear-actuator subject to high loads. Ideal for material handling applications. Two basic models include a self-lubricating slide bushing and a linear ball bearing style. The 100mm slide bushing model can stop a load of 1300 Kg. traveling at 280 mm(sg, or smoothly lift a centered load of 450 Kg. with a 40% safety factor. The overall package is very compact, and pre-tapped mounting holes ensure easy attachment of fixtures. Mounts on side or bottom. The MGQ offers bore sizes from 12 to 100mm and is switch capable.



Double-acting, single-rod cylinder

Standard specifications


Bore Size	16mm
Thread Type	Metric (Bore ø12 to ø16) & Rc(PT)
Stroke	75
Auto Switch	No Switch
Lead Wire or Prewired Connector	0.5m (Or None in the Case of No Switch)
Number	2 pcs. (Or None in the Case of No Switch)
Rod End Options	None
Temperature Resistance	None
Low Speed	None
Fluororubber Seal	None
Pressure medium	Air
Maximum temperature of pressure medium	60 °C
Minimum temperature of pressure medium	-10 °C (No freezing)
Maximum operating pressure	1.0 MPa
Minimum operating pressure	0.12 MPa
Proof pressure	1.5 MPa
Maximum ambient temperature	60 °C
Minimum ambient temperature	-10 °C (No freezing)
Conform to the European RoHS Directive	Conform


26/05/2020 Page 1


	2
	2
	ac
,	15
	2
	13
	Ε
	9
1	8
,	ó
	۲
	Dal
	_
	ре
	•
	00
	40
	S
	ga
	3
	0
	2
	ā
	DC
	B
	ce
	00
	S
	0
	2
	Ħ
	Q
:	8
	\leq
	g
	20
	ig
•	ક
	ō
	7
	90
	0
	ns
	d)
	3.LE
	50
	0
	9


Numbero of pneumatic connections	2 pcs.
Pneumatic input connection	M5 x 0.8
Mode of operation of drive	Double acting
Theoretical cylinder force, advance stroke (at 0.5 MPa)	101 N
Theoretical cylinder force, return stroke (at 0.5 MPa)	76 N
Maximum piston speed	500 mm/s
Type of cushioning	Rubber bumper on both ends
Minimum piston speed	50 mm/s
Non-rotating accuracy of plate	± 0.08 °
Lubrication	Non-lube
Weight	0.646 Kg

Dimensions











Additional information

Catalogue

MGQ_EU.pdf

Specifications are subject to change without prior notice and any obligation on the part of the manufacturer.