

1311013

https://www.phoenixcontact.com/in/products/1311013

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Empty enclosure, DIN rail mounting, light gray (7035), transparent hinged cover, for Raspberry Pi computer (suitable for Raspberry Pi A+, B+, B2, B3, B4), width: 107.6 mm, height: 89.7 mm, depth: 60.7 mm

Your advantages

- · Tool-free mounting
- · Plenty of space for additional circuits on matrix or additional boards
- · GPIO strip can be used with PTSM series connection technology
- · Easy module-to-module connection, thanks to bus connection via DIN rails

Commercial data

Item number	1311013
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	****
Product key	ACHBAE
GTIN	4063151602956
Weight per piece (including packing)	122.7 g
Weight per piece (excluding packing)	119.4 g
Customs tariff number	85369010
Country of origin	DE



https://www.phoenixcontact.com/in/products/1311013



Technical data

Product properties

Product type	Stackable housing set
Housing type	DIN rail housing for use in distribution boards in accordance with DIN 43880
Housing series	BC
Туре	Housing set
Ventilation openings present	yes

Dimensions

Dimensional drawing	h
Width	107.6 mm
Height	89.7 mm
Depth	60.7 mm
Depth from top edge of DIN rail	54.7 mm

Material specifications

Color (Upper housing part)	light gray (RAL 7035)
Color (Lower housing part)	light gray (RAL 7035)
Flammability rating according to UL 94	V0
Insulating material	Polycarbonat
Housing material	PC

Environmental and real-life conditions

Power dissipation single housing for 20 °C

Ambient temperature	20 °C
Reduction factor	1
Power dissipation single housing for 30 °C	
Ambient temperature	30 °C
Reduction factor	0.84
Power dissipation single housing for 40 °C	
Ambient temperature	40 °C

0.72

Power dissipation single housing for 50 °C

Reduction factor



1311013

https://www.phoenixcontact.com/in/products/1311013


Ambient temperature	50 °C
Reduction factor	0.6
Power dissipation single housing for 60 °C	
Ambient temperature	60 °C
Reduction factor	0.48
Power dissipation single housing for 70 °C	
Ambient temperature	70 °C
Reduction factor	0.38
Ambient conditions	
Max. IP code to attain	IP20
Ambient temperature (operation)	-40 °C 105 °C (depending on power dissipation)
Ambient temperature (storage/transport)	-40 °C 70 °C
Ambient temperature (assembly)	-5 °C 100 °C
Relative humidity (storage/transport)	95 %
B data	
Type of PCB mount	Latching
punting	
Mounting type	DIN rail mounting/panel mounting
ckaging specifications	
Type of packaging	packed in cardboard


1311013

https://www.phoenixcontact.com/in/products/1311013



Drawings





Schematic figure for illustrating the item dimensions. The figure is not of the desired product. For further details, refer to the product drawings in the "Downloads" tab.



1311013

https://www.phoenixcontact.com/in/products/1311013

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/in/products/1311013



UL RecognizedApproval ID: E240868



1311013

https://www.phoenixcontact.com/in/products/1311013

Classifications

ECLASS

	ECLASS-11.0	27182702
	ECLASS-13.0	27190301
ETIM		
	ETIM 9.0	EC001031
	JORGO	
UNSPSC		
	UNSPSC 21.0	31261500

Feb 4, 2025, 6:09 PM Page 6 (7)



1311013

https://www.phoenixcontact.com/in/products/1311013

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in