



## Safety Data Sheet

Copyright, 2018, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 28-7782-7 **Version number:** 6.03  
**Revision date:** 22/03/2018 **Supersedes date:** 13/11/2017  
**Transportation version number:** 1.00 (10/01/2012)

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

3M(TM) Adhesive Sealant 760 UV, White, Gray, and Black

#### Product Identification Numbers

DE-2729-2846-1 DE-2729-2850-3 DE-2729-2854-5 UU-0030-8338-1 UU-0030-8339-9  
UU-0030-8340-7

7000061766 7000061767 7000061768 7100062075 7100062076  
7100062077

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Sealant.

#### 1.3. Details of the supplier of the safety data sheet

**Address:** 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.  
**Telephone:** +44 (0)1344 858 000  
**E Mail:** tox.uk@mmm.com  
**Website:** www.3M.com/uk

#### 1.4. Emergency telephone number

+44 (0)1344 858 000

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

##### CLASSIFICATION:

Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

#### 2.2. Label elements

**3M(TM) Adhesive Sealant 760 UV, White, Gray, and Black****CLP REGULATION (EC) No 1272/2008****HAZARD STATEMENTS:**

H412 Harmful to aquatic life with long lasting effects.

**PRECAUTIONARY STATEMENTS****Disposal:**

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**SUPPLEMENTAL INFORMATION****Supplemental Hazard Statements:**

EUH208 Contains Tin, dioctylbis(2,4-pentanedionato-κO2,κO4)- | N-(3-(Trimethoxysilyl)propyl)ethylenediamine. May produce an allergic reaction.

**Notes on labelling**

Not classified for eye irritation per test data.

Specific concentration limits for calcium oxide (CASRN 1305-78-8): &gt;=50% Skin Corr. 1C; &gt;=10-&lt;50% Skin Irrit. 2.

**2.3. Other hazards**

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

**SECTION 3: Composition/information on ingredients**

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
Calcium Carbonate	471-34-1	207-439-9		25 - 45	Substance with a Community level exposure limit in the workplace
Polyether (NJTS Reg. No. 04499600-6711)	Trade Secret			20 - 35	Substance not classified as hazardous
Diisodecyl Phthalate	26761-40-0	247-977-1		1 - 15	Substance with a Community level exposure limit in the workplace
Limestone	1317-65-3	215-279-6		1 - 15	Substance with a Community level exposure limit in the workplace
Titanium dioxide	13463-67-7	236-675-5		0 - 15	Substance with a Community level exposure limit in the workplace
Calcium Oxide	1305-78-8	215-138-9		1 - 5	EUH071; Skin Corr. 1C, H314
Triiron tetraoxide	1317-61-9	215-277-5		0 - 3	Substance not classified as hazardous
Tin, dioctylbis(2,4-pentanedionato-κO2,κO4)-	54068-28-9			< 1	Skin Sens. 1B, H317; Repr. 2, H361d; Aquatic Chronic 2, H411
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	1760-24-3	217-164-6		< 1	Acute Tox. 4, H332; Acute Tox. 4, H302; Eye Dam. 1,

### 3M(TM) Adhesive Sealant 760 UV, White, Gray, and Black

					H318; Skin Sens. 1, H317; STOT SE 3, H335
Carbon black	1333-86-4	215-609-9		0 - 1	Substance with a Community level exposure limit in the workplace
Hindered Amine	63843-89-0	264-513-3		< 0.2	Aquatic Chronic 1, H410,M=10 Acute Tox. 4, H302

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

#### Substance

Carbon monoxide.  
Carbon dioxide.  
Irritant vapours or gases.  
Oxides of nitrogen.

#### Condition

During combustion.  
During combustion.  
During combustion.  
During combustion.

### 5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus,

## 3M(TM) Adhesive Sealant 760 UV, White, Gray, and Black

bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial or professional use only. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (eg. gloves, respirators...) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from amines.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Calcium Oxide	1305-78-8	UK HSC	TWA:2 mg/m <sup>3</sup>	
Limestone	1317-65-3	UK HSC	TWA(as inhalable dust):10 mg/m <sup>3</sup> ;TWA(as respirable dust):4 mg/m <sup>3</sup> ;TWA(Inhalable):10 mg/m <sup>3</sup> ;TWA(respirable):4 mg/m <sup>3</sup>	
Carbon black	1333-86-4	UK HSC	TWA: 3.5 mg/m <sup>3</sup> ; STEL: 7 mg/m <sup>3</sup>	
Titanium dioxide	13463-67-7	UK HSC	TWA(Inhalable):10 mg/m <sup>3</sup> ;TWA(respirable):4	

## 3M(TM) Adhesive Sealant 760 UV, White, Gray, and Black

Diisodecyl Phthalate	26761-40-0	UK HSC	mg/m <sup>3</sup> TWA:5 mg/m <sup>3</sup>
Limestone	471-34-1	UK HSC	TWA(as inhalable dust):10 mg/m <sup>3</sup> ;TWA(as respirable dust):4 mg/m <sup>3</sup> ;TWA(Inhalable):10 mg/m <sup>3</sup> ;TWA(respirable):4 mg/m <sup>3</sup>

UK HSC : UK Health and Safety Commission  
TWA: Time-Weighted-Average  
STEL: Short Term Exposure Limit  
CEIL: Ceiling

### Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

None required.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

#### Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

#### Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state	Solid.
Specific Physical Form:	Paste
Appearance/Odour	Slight odour
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Boiling point/boiling range	> 120 °C
Melting point	<i>No data available.</i>
Flammability (solid, gas)	Not classified
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	No flash point
Autoignition temperature	> 200 °C
Flammable Limits(LEL)	<i>Not applicable.</i>
Flammable Limits(UEL)	<i>Not applicable.</i>
Relative density	1.6 [Ref Std: WATER=1]
Water solubility	Negligible
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Vapour density	5 [Test Method: Estimated] [Ref Std: AIR=1]
Decomposition temperature	<i>No data available.</i>
Viscosity	<i>No data available.</i>
Density	1.61 g/m <sup>3</sup>

**9.2. Other information**

EU Volatile Organic Compounds	<i>No data available.</i>
Percent volatile	0.8 % weight

**SECTION 10: Stability and reactivity****10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

**10.2 Chemical stability**

Stable.

**10.3 Possibility of hazardous reactions**

Hazardous polymerisation will not occur.

**10.4 Conditions to avoid**

Heat.

**10.5 Incompatible materials**

Alcohols.

Water

Amines.

**10.6 Hazardous decomposition products**

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

#### Additional Health Effects:

#### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

#### Additional information:

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Calcium Carbonate	Dermal	Rat	LD50 > 2,000 mg/kg
Calcium Carbonate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Calcium Carbonate	Ingestion	Rat	LD50 6,450 mg/kg
Limestone	Dermal	Rat	LD50 > 2,000 mg/kg
Limestone	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3 mg/l

**3M(TM) Adhesive Sealant 760 UV, White, Gray, and Black**

Limestone	Ingestion	Rat	LD50 6,450 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Diisodecyl Phthalate	Dermal	Rabbit	LD50 > 3,160 mg/kg
Diisodecyl Phthalate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 12.5 mg/l
Diisodecyl Phthalate	Ingestion	Rat	LD50 > 9,700 mg/kg
Calcium Oxide	Ingestion	Rat	LD50 > 2,500 mg/kg
Triiron tetraoxide	Dermal	Not available	LD50 3,100 mg/kg
Triiron tetraoxide	Ingestion	Not available	LD50 3,700 mg/kg
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	Dermal	Rabbit	LD50 > 2,000 mg/kg
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	Inhalation-Dust/Mist (4 hours)	Rat	LC50 >1.49, <2.44 mg/l
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	Ingestion	Rat	LD50 1,897 mg/kg
Carbon black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon black	Ingestion	Rat	LD50 > 8,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Calcium Carbonate	Rabbit	No significant irritation
Limestone	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
Diisodecyl Phthalate	Rabbit	Minimal irritation
Calcium Oxide	Human	Corrosive
Triiron tetraoxide	Rabbit	No significant irritation
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	Rabbit	Mild irritant
Carbon black	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Overall product	In vitro data	No significant irritation
Calcium Carbonate	Rabbit	No significant irritation
Limestone	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
Diisodecyl Phthalate	Rabbit	Mild irritant
Calcium Oxide	Rabbit	Corrosive
Triiron tetraoxide	Rabbit	No significant irritation
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	Rabbit	Corrosive
Carbon black	Rabbit	No significant irritation

**Skin Sensitisation**

Name	Species	Value
Titanium dioxide	Human and animal	Not classified
Diisodecyl Phthalate	Guinea pig	Not classified
Triiron tetraoxide	Human	Not classified
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	Multiple animal species	Sensitising
Tin, dioctylbis(2,4-pentanedionato-κO2,κO4)-	Mouse	Sensitising



**3M(TM) Adhesive Sealant 760 UV, White, Gray, and Black**

**Respiratory Sensitisation**

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic
Diisodecyl Phthalate	In Vitro	Not mutagenic
Diisodecyl Phthalate	In vivo	Not mutagenic
Calcium Oxide	In Vitro	Not mutagenic
Triiron tetraoxide	In Vitro	Not mutagenic
Carbon black	In Vitro	Not mutagenic
Carbon black	In vivo	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.
Triiron tetraoxide	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Carbon black	Dermal	Mouse	Not carcinogenic
Carbon black	Ingestion	Mouse	Not carcinogenic
Carbon black	Inhalation	Rat	Carcinogenic.

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Calcium Carbonate	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	pre mating & during gestation
Limestone	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	pre mating & during gestation
Diisodecyl Phthalate	Ingestion	Not classified for female reproduction	Rat	NOAEL 927 mg/kg/day	2 generation
Diisodecyl Phthalate	Ingestion	Not classified for male reproduction	Rat	NOAEL 929 mg/kg/day	2 generation
Diisodecyl Phthalate	Ingestion	Toxic to development	Rat	NOAEL 38 mg/kg/day	2 generation
Tin, dioctylbis(2,4-pentanedionato-κO2,κO4)-	Ingestion	Toxic to development	Rat	NOAEL 1.8 mg/kg/day	pre mating into lactation

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Calcium Carbonate	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes
Limestone	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes
Calcium Oxide	Inhalation	respiratory irritation	May cause respiratory irritation	Not available	NOAEL Not available	occupational exposure
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	

**3M(TM) Adhesive Sealant 760 UV, White, Gray, and Black****Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Calcium Carbonate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Limestone	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Diisodecyl Phthalate	Inhalation	respiratory system   hematopoietic system   liver   kidney and/or bladder	Not classified	Rat	NOAEL 0.5 mg/l	2 weeks
Diisodecyl Phthalate	Ingestion	endocrine system	Not classified	Rat	NOAEL 686 mg/kg/day	90 days
Diisodecyl Phthalate	Ingestion	liver   kidney and/or bladder   heart	Not classified	Rat	NOAEL 500 mg/kg/day	90 days
Diisodecyl Phthalate	Ingestion	hematopoietic system	Not classified	Dog	NOAEL 320 mg/kg/day	90 days
Triiron tetraoxide	Inhalation	pulmonary fibrosis   pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Carbon black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure

**Aspiration Hazard**

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

**SECTION 12: Ecological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

**12.1. Toxicity**

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Calcium Carbonate	471-34-1	Water flea	Experimental	48 hours	EC50	>100 mg/l
Calcium Carbonate	471-34-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Calcium Carbonate	471-34-1	Rainbow trout	Experimental	96 hours	LC50	>100 mg/l
Calcium Carbonate	471-34-1	Green algae	Experimental	72 hours	Effect Concentration 10%	>100 mg/l
Polyether (NJTS Reg. No. 04499600-6711)	Trade Secret		Data not available or insufficient for classification			
Diisodecyl Phthalate	26761-40-0	Water flea	Estimated	48 hours	EC50	>100 mg/l
Diisodecyl Phthalate	26761-40-0	Rainbow trout	Estimated	96 hours	LC50	>100 mg/l

**3M(TM) Adhesive Sealant 760 UV, White, Gray, and Black**

Diisodecyl Phthalate	26761-40-0	Green algae	Estimated	96 hours	EC50	>100 mg/l
Diisodecyl Phthalate	26761-40-0	Green algae	Estimated	96 hours	NOEC	>100 mg/l
Diisodecyl Phthalate	26761-40-0	Water flea	Estimated	21 days	NOEC	>100 mg/l
Limestone	1317-65-3	Western Mosquitofish	Experimental	96 hours	LC50	>100 mg/l
Limestone	1317-65-3	Rainbow trout	Experimental	42 days	NOEC	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
Calcium Oxide	1305-78-8	Common Carp	Experimental	96 hours	LC50	1,070 mg/l
Triiron tetraoxide	1317-61-9	Green Algae	Experimental	72 hours	EC50	>50,000 mg/l
Triiron tetraoxide	1317-61-9	Water flea	Experimental	48 hours	EC50	>50,000 mg/l
Triiron tetraoxide	1317-61-9	Green Algae	Experimental	72 hours	Effect Concentraion 0%	>50,000 mg/l
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	1760-24-3	Green Algae	Experimental	72 hours	EC50	8.8 mg/l
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	1760-24-3	Water flea	Experimental	48 hours	EC50	81 mg/l
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	1760-24-3	Fathead minnow	Experimental	96 hours	LC50	168 mg/l
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	1760-24-3	Green Algae	Experimental	72 hours	NOEC	3.1 mg/l
Carbon black	1333-86-4		Data not available or insufficient for classification			
Tin, dioctylbis(2,4-pentanedionato-κO2,κO4)-	54068-28-9	Water flea	Estimated	24 hours	EC50	1.3 mg/l
Tin, dioctylbis(2,4-pentanedionato-κO2,κO4)-	54068-28-9	Water flea	Estimated	21 days	NOEC	0.52 mg/l
Hindered Amine	63843-89-0	Water flea	Experimental	21 days	NOEC	0.002 mg/l

**12.2. Persistence and degradability**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Calcium Carbonate	471-34-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polyether (NJTS Reg. No. 04499600-6711)	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Diisodecyl Phthalate	26761-40-0	Estimated Biodegradation	28 days	BOD	74 % BOD/ThBOD	OECD 301F - Manometric respirometry
Limestone	1317-65-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

### 3M(TM) Adhesive Sealant 760 UV, White, Gray, and Black

Calcium Oxide	1305-78-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Triiron tetraoxide	1317-61-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	1760-24-3	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	39 % weight	Other methods
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	1760-24-3	Experimental Hydrolysis		Hydrolytic half-life	1.5 minutes (t 1/2)	Other methods
Carbon black	1333-86-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Tin, dioctylbis(2,4-pentanedionato-κO2,κO4)-	54068-28-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hindered Amine	63843-89-0	Experimental Biodegradation	28 days	CO2 evolution	2 % weight	OECD 301B - Modified sturm or CO2

### 12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Calcium Carbonate	471-34-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polyether (NJTS Reg. No. 04499600-6711)	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Diisodecyl Phthalate	26761-40-0	Experimental BCF-Carp	56 days	Bioaccumulation factor	<14.4	OECD 305E - Bioaccumulation flow-through fish test
Limestone	1317-65-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF-Carp	42 days	Bioaccumulation factor	9.6	Other methods
Calcium Oxide	1305-78-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Triiron tetraoxide	1317-61-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	1760-24-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Carbon black	1333-86-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Tin, dioctylbis(2,4-pentanedionato-κO2,κO4)-	54068-28-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hindered Amine	63843-89-0	Experimental BCF-Carp	60 days	Bioaccumulation factor	≤437.1	OECD 305C-Bioaccum degree fish

### 12.4. Mobility in soil

Please contact manufacturer for more details

### 12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

### 12.6. Other adverse effects

## 3M(TM) Adhesive Sealant 760 UV, White, Gray, and Black

No information available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

See Section 11.1 Information on toxicological effects

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

### EU waste code (product as sold)

08 04 09\* Waste adhesives and sealants containing organic solvents or other dangerous substances  
20 01 27\* Paint, inks, adhesives and resins containing dangerous substances

## SECTION 14: Transportation information

DE-2729-2846-1, DE-2729-2850-3, DE-2729-2854-5, UU-0030-8338-1,  
UU-0030-8339-9, UU-0030-8340-7

Not hazardous for transportation

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
Carbon black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

#### Global inventory status

Contact manufacturer for more information

### 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

## SECTION 16: Other information

### List of relevant H statements

EUH071 Corrosive to the respiratory tract.

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361d	Suspected of damaging the unborn child.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Revision information:**

- Section 1: Product identification numbers information was modified.
- Section 01: SAP Material Numbers information was modified.
- Section 3: Composition/ Information of ingredients table information was modified.
- Section 5: Fire - Advice for fire fighters information information was modified.
- Section 8: Occupational exposure limit table information was modified.
- Section 11: Acute Toxicity table information was modified.
- Section 11: Germ Cell Mutagenicity Table information was modified.
- Section 11: Reproductive Toxicity Table information was modified.
- Section 11: Serious Eye Damage/Irritation Table information was modified.
- Section 11: Skin Corrosion/Irritation Table information was modified.
- Section 11: Skin Sensitization Table information was modified.
- Section 11: Target Organs - Repeated Table information was modified.
- Section 12: Component ecotoxicity information information was modified.
- Section 12: Persistence and Degradability information information was modified.
- Section 12: Biocumulative potential information information was modified.
- Section 15: Chemical Safety Assessment information was modified.
- Section 15: Regulations - Inventories information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

**3M United Kingdom MSDSs are available at [www.3M.com/uk](http://www.3M.com/uk)**