

Fully featured, vandal resistant keyboards with numeric/arithmetic function keypad

- Vandal resistant (20J BS EN 60068-2-75: 1997)
- Weather resistant (IP65)
- Integral PS2/USB Interface (switchable)
- Optional PC connection cables (sold separately)
- Optional fixing kit for under panel installation (sold separately) or adapter kit for benchtop use (also sold separately)

- RFI / EMI Protection in accordance with current European and U.S. directives
- Operational life of more than 4 million cycles per key
- Resistant to most commonly used cleaning agents
- 92 keys with non embedded numeric/arithmetic keypad
- Space efficient footprint: 346.5 mm x 137.5 mm x 32.8 mm




















Storm Interface products include technology protected by international patents and design registration. All rights reserved.



2230 Series keyboards for public environments

STORM 2230 keyboards are constructed to survive in exposed, unsupervised, public environments. Their responsive key action ensures rapid, reliable and responsive data entry in tough, wet or hostile conditions. A hardened stainless steel front plate and high impact polymer keys ensure the keyboard's resistance to hard use, abuse and vandalism.



Electrical

Encoder

Languages

EMC Emissions EN55022 : 1998 Class B Limit
EMC Immunity to ESD EN55024 : 1998
EMC Immunity to Radiated Fields EN55024 : 1998
Electrical Safety EN60950, UL60950
Communication Industry Standard PS2

PS2/USB selectable

English UK, English USA, French, Spanish, German

Supply requirements

— voltage +5V nominal (5.5V to 4.75V)

Supply requirements

— current 60mA (with 2 LEDs illuminated)

Environmental

Sealing — Water / Particulates
Temperature

EN60529 (sealing to IP65)
-20°C to +60°C operating (dry)

Mechanical

Impact Resistance
Key Pitch20 Joules via 50mm dia steel striker
19mmSize11mm squareTravel1.5mm nominalActuation Force130g nominal

4 tormInterface

USA Office: Storm Interface Suite 202 364 Pennsylvania Avenue Glen Ellyn IL 60137 USA

Tel: (630) 469 2981 Fax: (630) 469 2975 Email: sales.usa@storm-keypads.com

UK Office.

Storm Interface 14 Bentinck Court Bentinck Road West Drayton Middlesex UB7 7RQ

Tel: +44 (0)1895 431421 Fax: +44 (0)1895 431132 Email: sales@storm-interface.com

www.storm-interface.com

Storm is a trademark of Keymat Technology Ltd m Interface is a trading name of Keymat Technology Ltd

Storm Interface products include technology protected by international patents and design registration. All rights reserved.



DescriptionStock Code2200 Underpanel Fixing Kit — contains clips2200-MK00012200 Foot Kit — required for benchtop use2200-FK000XKeyboard PS2 Cable — straight 2.5m long1200 -001001Keyboard USB Cable — straight 2.5m long1200 -002001

or USB Interface

Whilst every effort is made to ensure details are correct at time of print, specifications are subject to change without notice.



+44 (0)7810 551046

2230-LIT-01 Rev 2 Oct 2004



FM 39602