



EPOXY RESIN 2165 PART A #164-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3315

Version No:4

CD 2009/3 Page 1 of 21

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

EPOXY RESIN 2165 PART A #164-309

PROPER SHIPPING NAME

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(contains bisphenol A/ epichlorohydrin resin, liquid a tris(isopropylphenyl)phosphate)

PRODUCT USE

■ Used according to manufacturer's directions.

SUPPLIER


Company: RS Components	Company: RS Components
Address:	Address:
Units 30 & 31	25 Pavesi Street
Warehouse World	Smithfield
761 Great South Road	NSW2164
Penrose Auckland	AUS
	Telephone: 1300 656 636
	Emergency Tel: 1800 039 008
	Emergency Tel: 03 9573 3112
	Fax: 1300 656 696

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

CHEMWATCH HAZARD RATINGS



continued...

EPOXY RESIN 2165 PART A #164-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3315

Version No:4

CD 2009/3 Page 2 of 21

Section 2 - HAZARDS IDENTIFICATION



POISONS SCHEDULE

S5

RISK

- Irritating to eyes and skin.
- Limited evidence of a carcinogenic effect.
- May cause SENSITISATION by skin contact.
- Toxic to aquatic organisms may cause long-term adverse effects in the aquatic environment.
- Cumulative effects may result following exposure*.
- May produce discomfort of the respiratory system*.
- Possible respiratory sensitiser*.
- May possibly affect fertility*.

* (limited evidence).

SAFETY

- Do not breathe gas/fumes/vapour/spray.
- Avoid exposure - obtain special instructions before use.
- To clean the floor and all objects contaminated by this material use water and detergent.
- This material and its container must be disposed of in a safe way.
- Keep away from food drink and animal feeding stuffs.
- In case of contact with eyes rinse with plenty of water and contact Doctor or Poisons Information Centre.
- If swallowed IMMEDIATELY contact Doctor or Poisons Information Centre. (show this container or label).
- Use appropriate container to avoid environmental contamination.
- Avoid release to the environment. Refer to special instructions/Safety data sheets.
- This material and its container must be disposed of as hazardous waste.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
bisphenol A/ epichlorohydrin resin, liquid	25068-38-6	30-60
glycidyl neodecanoate	26761-45-5	5-10
tris(isopropylphenyl)phosphate	68937-41-7	5-10
antimony trioxide	1309-64-4	1-5
xylene	1330-20-7	<0.1

Section 4 - FIRST AID MEASURES

SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.

continued...

EPOXY RESIN 2165 PART A #164-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3315

Version No:4

CD 2009/3 Page 3 of 21

Section 4 - FIRST AID MEASURES

- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

EYE

- If this product comes in contact with the eyes:
 - Immediately hold eyelids apart and flush the eye continuously with running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
 - Transport to hospital or doctor without delay.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
 - Immediately remove all contaminated clothing, including footwear.
 - Flush skin and hair with running water (and soap if available).
 - Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

- Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

FIRE/EXPLOSION HAZARD

- Combustible.
- Slight fire hazard when exposed to heat or flame.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).
- May emit acrid smoke.
- Mists containing combustible materials may be explosive.

continued...

EPOXY RESIN 2165 PART A #164-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3315

Version No:4

CD 2009/3 Page 4 of 21

Section 5 - FIRE FIGHTING MEASURES

Combustion products include: carbon dioxide (CO₂), aldehydes, nitrogen oxides (NO_x), other pyrolysis products typical of burning organic material.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM: 2X

Personal Protective Equipment

Gas tight chemical resistant suit.

Section 6 - ACCIDENTAL RELEASE MEASURES


MINOR SPILLS

- Environmental hazard - contain spillage.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable, labelled container for waste disposal.

MAJOR SPILLS

- Environmental hazard - contain spillage.
- Moderate hazard.
- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

PROTECTIVE ACTIONS FOR SPILL



From IERG (Canada/Australia)

continued...

EPOXY RESIN 2165 PART A #164-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3315

Version No:4

CD 2009/3 Page 5 of 21

Section 6 - ACCIDENTAL RELEASE MEASURES

Isolation Distance -
Downwind Protection Distance 10 metres
IERG Number 47

FOOTNOTES

1 PROTECTIVE ACTION ZONE is defined as the area in which people are at risk of harmful exposure. This zone assumes that random changes in wind direction confines the vapour plume to an area within 30 degrees on either side of the predominant wind direction, resulting in a crosswind protective action distance equal to the downwind protective action distance.

2 PROTECTIVE ACTIONS should be initiated to the extent possible, beginning with those closest to the spill and working away from the site in the downwind direction. Within the protective action zone a level of vapour concentration may exist resulting in nearly all unprotected persons becoming incapacitated and unable to take protective action and/or incurring serious or irreversible health effects.

3 INITIAL ISOLATION ZONE is determined as an area, including upwind of the incident, within which a high probability of localised wind reversal may expose nearly all persons without appropriate protection to life-threatening concentrations of the material.

4 SMALL SPILLS involve a leaking package of 200 litres (55 US gallons) or less, such as a drum (jerrican or box with inner containers). Larger packages leaking less than 200 litres and compressed gas leaking from a small cylinder are also considered "small spills".

LARGE SPILLS involve many small leaking packages or a leaking package of greater than 200 litres, such as a cargo tank, portable tank or a "one-tonne" compressed gas cylinder.

5 Guide 171 is taken from the US DOT emergency response guide book.

6 IERG information is derived from CANUTEC - Transport Canada.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- DO NOT allow clothing wet with material to stay in contact with skin.
- Remove all ignition sources.
- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

- Avoid cross contamination between the two liquid parts of product (kit).
- If two part products are mixed or allowed to mix in proportions other than manufacturer's recommendation, polymerisation with gelation and evolution of heat (exotherm) may occur.
- This excess heat may generate toxic vapour.
- Avoid reaction with amines, mercaptans, strong acids and oxidising agents.

continued...

EPOXY RESIN 2165 PART A #164-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3315

Version No:4

CD 2009/3 Page 6 of 21

Section 7 - HANDLING AND STORAGE

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+: May be stored together

O: May be stored together with specific preventions

X: Must not be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA mg/m ³
Australia Exposure Standards	tris(isopropylphenyl)phosphate (Inspirable dust (not otherwise classified))	10
Australia Exposure Standards	antimony trioxide (Antimony trioxide, handling and use (as Sb))	0.5

The following materials had no OELs on our records

- bisphenol A/ epichlorohydrin resin, liquid: CAS:25068- 38- 6 CAS:25085- 99- 8
- glycidyl neodecanoate: CAS:26761- 45- 5 CAS:71206- 09- 2

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m ³)	Revised IDLH Value (ppm)
antimony trioxide	50	
xylene		900

MATERIAL DATA

EPOXY RESIN 2165 PART A #164-309:

Not available

BISPHENOL A/ EPICHLOROHYDRIN RESIN, LIQUID:

■ Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on

continued...

EPOXY RESIN 2165 PART A #164-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3315

Version No:4

CD 2009/3 Page 7 of 21

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

For epichlorohydrin

Odour Threshold Value: 0.08 ppm

NOTE: Detector tubes for epichlorohydrin, measuring in excess of 5 ppm, are commercially available.

Exposure at or below the recommended TLV-TWA is thought to minimise the potential for adverse respiratory, liver, kidney effects. Epichlorohydrin has been implicated as a human skin sensitiser, hence individuals who are hypersusceptible or otherwise unusually responsive to certain chemicals may NOT be adequately protected from adverse health effects.

Odour Safety Factor (OSF)

OSF=0.54 (EPICHLOROHYDRIN).

GLYCIDYL NEODECANOATE:

■ Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

TRIS(ISOPROPYLPHENYL)PHOSPHATE:

■ No exposure limits set by NOHSC or ACGIH.

CEL TWA: 3 mg/m³ [refer REL TWA Petro-Canada]

ANTIMONY TRIOXIDE:

■ The wide-ranging effects of antimony compounds have made it difficult to recommend an exposure standard which characterises the toxicology of these substances. One criteria, reflecting the irritant properties of antimony pentachloride, produced a calculated value of 5.0 mg/m³ (as antimony), which on the basis of experience was felt to be too high but did act as an "out-rider". The present value reflects this thinking.

XYLENE:

■ for xylenes:

IDLH Level: 900 ppm

Odour Threshold Value: 20 ppm (detection), 40 ppm (recognition)

NOTE: Detector tubes for o-xylene, measuring in excess of 10 ppm, are available commercially. (m-xylene and p-xylene give almost the same response).

Xylene vapour is an irritant to the eyes, mucous membranes and skin and causes narcosis at high

continued...

EPOXY RESIN 2165 PART A #164-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3315

Version No:4

CD 2009/3 Page 8 of 21

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

concentrations. Exposure to doses sufficiently high to produce intoxication and unconsciousness also produces transient liver and kidney toxicity. Neurologic impairment is NOT evident amongst volunteers inhaling up to 400 ppm though complaints of ocular and upper respiratory tract irritation occur at 200 ppm for 3 to 5 minutes.

Exposure to xylene at or below the recommended TLV-TWA and STEL is thought to minimise the risk of irritant effects and to produce neither significant narcosis or chronic injury. An earlier skin notation was deleted because percutaneous absorption is gradual and protracted and does not substantially contribute to the dose received by inhalation.

Odour Safety Factor(OSF)

OSF=4 (XYLENE).

Exposure limits with "skin" notation indicate that vapour and liquid may be absorbed through intact skin. Absorption by skin may readily exceed vapour inhalation exposure. Symptoms for skin absorption are the same as for inhalation. Contact with eyes and mucous membranes may also contribute to overall exposure and may also invalidate the exposure standard.

PERSONAL PROTECTION



EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

■ NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
 - Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.
- Suitability and durability of glove type is dependent on usage. Factors such as:
- frequency and duration of contact,
 - chemical resistance of glove material,
 - glove thickness and
 - dexterity,
- are important in the selection of gloves.
- When handling liquid-grade epoxy resins wear chemically protective gloves (e.g nitrile or nitrile-butadiene rubber), boots and aprons.
 - DO NOT use cotton or leather (which absorb and concentrate the resin), polyvinyl chloride, rubber or polyethylene gloves (which absorb the resin).
 - DO NOT use barrier creams containing emulsified fats and oils as these may absorb the resin; silicone-based barrier creams should be reviewed prior to use.

OTHER

- Overalls.
- P.V.C. apron.

continued...

EPOXY RESIN 2165 PART A #164-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3315

Version No:4

CD 2009/3 Page 9 of 21

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

RESPIRATOR

■ Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	A- AUS P	-
1000	50	-	A- AUS P
5000	50	Airline *	-
5000	100	-	A- 2 P
10000	100	-	A- 3 P
	100+		Airline**

* - Continuous Flow

** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

■ General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25- 0.5 m/s (50- 100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5- 1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200- 500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

- 1: Room air currents minimal or favourable to capture
- 2: Contaminants of low toxicity or of nuisance value only.
- 3: Intermittent, low production.
- 4: Large hood or large air mass in motion

Upper end of the range

- 1: Disturbing room air currents
- 2: Contaminants of high toxicity
- 3: High production, heavy use
- 4: Small hood- local control only

continued...

EPOXY RESIN 2165 PART A #164-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3315

Version No:4

CD 2009/3 Page 10 of 21

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Refer also to protective measures for the other component used with the product. Read both MSDS before using; store and attach MSDS together.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Black viscous liquid; does not mix with water.

PHYSICAL PROPERTIES

Liquid.

Does not mix with water.

Sinks in water.

Molecular Weight: Not Applicable

Specific Gravity (water=1): 1.48 @25C

pH (1% solution): Not Available

Evaporation Rate: Not Available

Lower Explosive Limit (%): Not Available

Decomposition Temp (°C): Not Available

Boiling Range (°C): Not Available

Solubility in water (g/L): Immiscible

Vapour Pressure (kPa): Not Available

Relative Vapour Density (air=1): Not Available

Upper Explosive Limit (%): Not Available

State: Liquid

Melting Range (°C): Not Available

pH (as supplied): Not Available

Volatile Component (%vol): Not Available

Flash Point (°C): > 200 (CC)

Autoignition Temp (°C): Not Available

Viscosity: Not Available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

■ Accidental ingestion of the material may be damaging to the health of the individual. Ingestion may result in nausea, abdominal irritation, pain and vomiting.

continued...

EPOXY RESIN 2165 PART A #164-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3315

Version No:4

CD 2009/3 Page 11 of 21

Section 11 - TOXICOLOGICAL INFORMATION

EYE

■ Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by a temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.

SKIN

■ Evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis. The material may accentuate any pre-existing dermatitis condition. Open cuts, abraded or irritated skin should not be exposed to this material. Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

■ Not normally a hazard due to non-volatile nature of product.

CHRONIC HEALTH EFFECTS

■ Practical experience shows that skin contact with the material is capable either of inducing a sensitisation reaction in a substantial number of individuals, and/or of producing a positive response in experimental animals.

Respiratory sensitisation may result in allergic/asthma like responses; from coughing and minor breathing difficulties to bronchitis with wheezing, gasping.

TOXICITY AND IRRITATION

■ Not available. Refer to individual constituents.

BISPHENOL A/ EPICHLOROHYDRIN RESIN, LIQUID:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: 11400 mg/kg

■ Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

Oxiranes (including glycidyl ethers and alkyl oxides, and epoxides) exhibit many common characteristics with respect to animal toxicology. One such oxirane is ethyloxirane; data presented here may be taken as representative.

for 1,2-butylene oxide (ethyloxirane):

Ethyloxirane increased the incidence of tumours of the respiratory system in male and female rats exposed via inhalation. Significant increases in nasal papillary adenomas and combined alveolar/bronchiolar adenomas and carcinomas were observed in male rats exposed to 1200 mg/m³ ethyloxirane via inhalation for 103 weeks. There was also a significant positive trend in the incidence of combined alveolar/bronchiolar adenomas and carcinomas. Nasal papillary adenomas were also observed in 2/50 high-dose female rats with none occurring in control or low-dose animals. In mice exposed chronically via inhalation, one male mouse developed a squamous cell papilloma in the nasal cavity (300 mg/m³) but other tumours were not observed. Tumours were not observed

IRRITATION

Eye (rabbit): 100mg - Mild

continued...

EPOXY RESIN 2165 PART A #164-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3315

Version No:4

CD 2009/3 Page 12 of 21

Section 11 - TOXICOLOGICAL INFORMATION

in mice exposed chronically via dermal exposure. When trichloroethylene containing 0.8% ethyloxirane was administered orally to mice for up to 35 weeks, followed by 0.4% from weeks 40 to 69, squamous-cell carcinomas of the forestomach occurred in 3/49 males ($p=0.029$, age-adjusted) and 1/48 females at week 106. Trichloroethylene administered alone did not induce these tumours and they were not observed in control animals. Two structurally related substances, oxirane (ethylene oxide) and methyloxirane (propylene oxide), which are also direct-acting alkylating agents, have been classified as carcinogenic.

GLYCIDYL NEODECANOATE:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: 9600 mg/kg

Dermal (rat) LD50: 3800 mg/kg [SHELL]

■ Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

The material has a low order of acute toxicity by the oral, dermal, and inhalation routes of exposure. It is mildly irritating to the eyes and non-irritating to the skin. Dermal sensitisation has been observed in guinea pigs and has been reported in humans following occupational exposure. In vitro genotoxicity testing indicated weak mutagenic activity in point mutation assays with metabolic activation using Salmonella, but not in E. coli or yeast. Mutagenic activity was not observed in an in vitro mammalian cell assay. A weak ability to produce chromosomal damage was observed in cultured rat liver cells, but no DNA damage was produced in an in vivo rat liver assay. A low order of toxicity was observed in subchronic dietary testing with a No Observed Adverse Effect Level (NOAEL) of 1000 ppm in the diet. At high concentrations of 5000 and 10000 ppm in the diet, kidney effects were observed that were more prominent in males than in females. No effects were noted in reproductive organs of either sex. Further testing to evaluate potential developmental or reproductive effects has not been identified.

Acute Toxicity

The material has a low order of acute toxicity by the oral, dermal, and inhalation routes of exposure. In rats, the oral LD50 was greater than 10 ml/kg (approximately 10 g/kg) and the dermal LD50 was greater than 4 ml/kg (approximately 4 g/kg). The rat 4-hour inhalation LC50 was greater than 0.24 mg/L (approximately 240 mg/m³), a concentration exceeding the saturated vapor pressure. Due to the low vapor pressure resulting in a low level of maximal attainable vapor concentration, inhalation exposure is expected to pose a negligible hazard.

Repeated Dose Toxicity

A low order of toxicity was observed in rats following five-week dietary testing. Treatment-related effects were limited to the upper two dietary dose levels of 5,000 and 10,000 ppm (approximately 478 and 888 mg/kg/day body weight, respectively). Dose-related effects at these two dietary levels included: decreased food intake and body weights, minor changes in hematology and clinical chemistry, increased liver and kidney weights and nephrotoxicity to the proximal tubules of the kidneys that was more pronounced in males than in females. The Lowest Observed Adverse Effect Level (LOAEL) was 5,000 ppm in the diet (approximately 478 mg/kg/day body weight) and the No Observed Adverse Effect Level (NOAEL) was 1,000 ppm in the diet (approximately 96 mg/kg/day body weight).

* HPV Chemical Challenge Program 2003

TRIS(ISOPROPYLPHENYL)PHOSPHATE:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: > 5000 mg/kg

Dermal (rabbit) LD50: > 2000 mg/kg

Inhalation (rat) LC50: > 6350 mg/m³/4h

IRRITATION

Skin: Mild **

Eye: Mild **

ANTIMONY TRIOXIDE:

continued...

EPOXY RESIN 2165 PART A #164-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3315

Version No:4

CD 2009/3 Page 13 of 21

Section 11 - TOXICOLOGICAL INFORMATION

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: >34600 mg/kg

Intraperitoneal (rat) LD50: 3250 mg/kg

Inhalation (rat) TCLO: 4.2 mg/m³/52W

■ Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production. The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.
(intermittent) [CCINFO]

Reproductive effector

XYLENE:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (human) LDLo: 50 mg/kg

Oral (rat) LD50: 4300 mg/kg

Inhalation (human) TCLO: 200 ppm

Inhalation (man) LCLo: 10000 ppm/6h

Inhalation (rat) LC50: 5000 ppm/4h

Oral (Human) LD: 50 mg/kg

Inhalation (Human) TCLO: 200 ppm/4h

Intraperitoneal (Rat) LD50: 2459 mg/kg

Subcutaneous (Rat) LD50: 1700 mg/kg

Oral (Mouse) LD50: 2119 mg/kg

Intraperitoneal (Mouse) LD50: 1548 mg/kg

Intravenous (Rabbit) LD: 129 mg/kg

Inhalation (Guinea) pig: LC 450 ppm/4h

■ The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

Reproductive effector in rats

IRRITATION

Nil Reported

IRRITATION

Skin (rabbit):500 mg/24h Moderate

Eye (human): 200 ppm Irritant

Eye (rabbit): 87 mg Mild

Eye (rabbit): 5 mg/24h SEVERE

CARCINOGEN

Antimony trioxide

International Agency
for Research on Cancer
(IARC) - Agents
Reviewed by the IARC
Monographs

Group

2B

continued...

EPOXY RESIN 2165 PART A #164-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3315

Version No:4

CD 2009/3 Page 14 of 21

Section 11 - TOXICOLOGICAL INFORMATION

CAS~	Australia Exposure Standards - Carcinogens	Carcinogen Category	2
Xylenes	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	3

REPROTOXIN

xylene	ILO Chemicals in the electronics industry that have toxic effects on reproduction	Reduced fertility or sterility
--------	---	--------------------------------

Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

EPOXY RESIN 2165 PART A #164-309:

XYLENE:

ANTIMONY TRIOXIDE:

GLYCIDYL NEODECANOATE:

BISPHENOL A/ EPICHLOROHYDRIN RESIN, LIQUID:

■ DO NOT discharge into sewer or waterways.

EPOXY RESIN 2165 PART A #164-309:

ANTIMONY TRIOXIDE:

BISPHENOL A/ EPICHLOROHYDRIN RESIN, LIQUID:

■ Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

BISPHENOL A/ EPICHLOROHYDRIN RESIN, LIQUID:

ANTIMONY TRIOXIDE:

GLYCIDYL NEODECANOATE:

■ Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters. Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

EPOXY RESIN 2165 PART A #164-309:

Marine Pollutant: Not Determined

BISPHENOL A/ EPICHLOROHYDRIN RESIN, LIQUID:

■ Significant environmental findings are limited. Oxiranes (including glycidyl ethers and alkyl oxides, and epoxides) exhibit common characteristics with respect to environmental fate and ecotoxicology. One such oxirane is ethyloxirane and data presented here may be taken as representative.

■ for 1,2-butylene oxide (ethyloxirane):

Environmental fate: Ethyloxirane is highly soluble in water and has a very low soil-adsorption coefficient, which suggests that if released to water, adsorption of ethyloxirane to sediment and suspended solids is not expected. Volatilisation of ethyloxirane from water surfaces would be expected based on the moderate estimated Henry's Law constant. If ethyloxirane is released to soil, it is expected to have low adsorption and thus very high mobility. Volatilisation from moist soil and dry soil surfaces is expected, based on its vapour pressure. It is expected that ethyloxirane exists solely as a vapour in ambient atmosphere, based on its very high vapour pressure. Ethyloxirane may also be removed from the atmosphere by wet deposition processes, considering its relatively high water solubility.

Persistence: The half-life in air is about 5.6 days from the reaction of ethyloxirane with photochemically produced hydroxyl radicals which indicates that this chemical meets the persistence criterion in air (half-life of = 2 days)*.

Ethyloxirane is hydrolysable, with a half-life of 6.5 days, and biodegradable up to 100% degradation and is not expected to persist in water. A further model-predicted biodegradation half-life of 15 days in water obtained and used to predict the half-life of this chemical in soil and sediment by applying Boethling's

continued...

EPOXY RESIN 2165 PART A #164-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3315

Version No:4

CD 2009/3 Page 15 of 21

Section 12 - ECOLOGICAL INFORMATION

extrapolation factors ($t_{1/2\text{water}} : t_{1/2\text{soil}} : t_{1/2\text{sediment}} = 1 : 1 : 4$) (Boethling 1995). According to these values, it can be concluded that ethyloxirane does not meet the persistence criteria in water and soil (half-lives = 182 days) and sediments (half-life = 365 days).

Experimental and modelled log Kow values of 0.68 and 0.86, respectively, indicate that the potential for bioaccumulation of ethyloxirane in organisms is likely to be low. Modelled bioaccumulation -factor (BAF) and bioconcentration -factor (BCF) values of 1 to 17 L/kg indicate that ethyloxirane does not meet the bioaccumulation criteria (BCF/BAF = 5000)*

Ecotoxicity:

Experimental ecotoxicological data for ethyloxirane (OECD 2001) indicate low to moderate toxicity to aquatic organisms. For fish and water flea, acute LC50/EC50 values vary within a narrow range of 70-215 mg/L; for algae, toxicity values exceed 500 mg/L, while for bacteria they are close to 5000 mg/L

* Persistence and Bioaccumulation Regulations (Canada 2000).

GLYCIDYL NEODECANOATE:

- Toxic to aquatic organisms.

- May cause long-term adverse effects in the aquatic environment.

Data are available to characterize the fish and invertebrate acute toxicity and alga toxicity. Although the data are associated with the parent substance, neodecanoic acid, 1,2-epoxypropyl ester, the results are interpreted to characterise the hydrolysed form of this substance because the parent epoxide rapidly forms the diol in aqueous systems.

Fish LC50 (96 h): rainbow trout (*Oncorhynchus mykiss*) 9.61 mg/l

Daphnia EC50 (48 h): 4.8 mg/l

Alga EC50: *Selenastrum capricornutum* 3.5 mg/l (biomass)

Biodegradability (28 d): 11.6% (OECD 301F)

Although the data are associated with the parent substance, neodecanoic acid, 1,2-epoxypropyl ester, the results are interpreted to characterize the hydrolyzed form of this substance because the parent epoxide rapidly forms the diol in aqueous systems, which is the case for biodegradation tests.

DOC (36 d): 66% removal (OECD 302A)

This suggests that the material can be removed in a wastewater treatment plant

Photodegradation ? Photolysis: not subject to photolytic processes in the aqueous environment.

has the potential to volatilize to air, based on a vapor pressure of 14.67 @ 20° C, where it is subject to atmospheric oxidation. In air, the material can react with photosensitized oxygen in the form of hydroxyl radicals (OH-). A calculated half-life in air of 13.3 hrs based on a rate constant of $23.71 \times 10^{-12} \text{ cm}^3 \cdot \text{mol}^{-1} \cdot \text{sec}^{-1}$ and an OH concentration of $1.5 \times 10^6 \text{ OH} \cdot \text{cm}^{-3}$

Hydrolysis: The material is an epoxide which is subject to hydrolysis to form neodecanoic acid, 1,2-propyldiol ester. Hydrolysis is estimated to occur at a relatively rapid rate, based on data for 14 epoxides that ranged in half-life from approximately 1 minute to 8 days at pH 7

ANTIMONY TRIOXIDE:

- Antimony exists in the atmosphere in low concentrations. Urban air contains 0.05 to 0.06 ppm of antimony. There are very low concentrations in water due to minimal solubility. Volatilisation from water is not likely. The soil usually contains 0.1 to 10 mg/kg dry weight. Antimony concentrations in freshwater fish are low, approximately 3 mg/kg wet weight.

Little is known of the adsorptive behavior of antimony, its compounds, and ions in soils and sediments. The binding of antimony to soil is determined by the nature of the soil and the form of antimony deposited on the soil. Some forms of antimony may bind to inorganic and organic ligands. On the other hand, a mineral form would be unavailable for binding. Some studies suggest that antimony is fairly mobile under diverse environmental conditions, while others suggest that it is strongly adsorbed to soil. Since antimony has an anionic character (e.g. $\text{Sb}(\text{OH})_3$), it is expected to have little affinity for organic carbon. It is not expected that cation exchange, which generally dominates adsorption to clay, would be important for anionic antimony. Antimony is known to form coprecipitates with hydrous iron, manganese, and aluminum oxides in soil and sediment. Antimony adsorbs strongly to colloidal material in soil. The partition coefficient of antimony to 0.05-0.003 μm colloids was 1,300. Antimony adsorbed to such material can be transported with the colloids in groundwater.

Leaching experiments performed with river sediment samples from a mining district in Idaho indicated that $\text{Sb}(\text{V})$ was the major species released during leaching. The fraction of antimony leached from sediment with deionized water after 10 days was highly correlated with the free iron and manganese oxide content of the sediment. The release of antimony from the sediment increased at low pH and increased sharply at high pH. The

continued...

EPOXY RESIN 2165 PART A #164-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3315

Version No:4

CD 2009/3 Page 16 of 21

Section 12 - ECOLOGICAL INFORMATION

form of released antimony was also sensitive to pH. At pH 2.7, the bulk of antimony released was as Sb(III); at pH 4.3, the concentrations of tri- and pentavalent antimony were comparable; and at pH 6.3 and above, Sb(V) was the predominant species.

Antimony does not appear to bioconcentrate appreciably in fish and aquatic organisms. No detectable bioconcentration occurred during a 28-day test in bluegills (EPA 1980). Only low levels of antimony have been reported in fish and aquatic organisms collected off the coast of Africa, Australia, and the Danube River in Austria. Bioconcentration factors for antimony ranged from 0.15 to 390. A study of the distribution of antimony around a smelter site indicated that antimony occurring in plants results from surface deposition. Uptake from soil is minor and appears to be correlated with the amount of available antimony (that which is soluble or easily exchangeable). Antimony bioconcentration was measured in voles, shrews, rabbits, and invertebrates around a smelter. Analysis of antimony in organs of the small mammals, compared with estimates of their antimony intake from food, showed that, although the amount of antimony in the organs was elevated, it was low compared to the amount ingested. The results suggest that antimony does not biomagnify from lower to higher trophic levels in the food chain.

Thermodynamically, most dissolved antimony in natural waters under aerobic conditions should be present in the +5 oxidation state as antimonate species. At 0.001 M total antimony, the dominant species were Sb(OH)₆⁻ and Sb(OH)₅⁰. A small quantity of polymeric hydroxy species were found, but these will be less significant when the total antimony concentration is low, such as in natural water. While industrial inputs will commonly contain antimony in the +3 oxidation state (e.g., antimony trioxide), it is not known how fast antimonite would oxidize to antimonate under natural conditions. Under reducing conditions, trivalent species such as Sb(OH)₃⁰, Sb(OH)₄⁻, and SbS₄⁴⁻ may be significant.

Antimony compounds may undergo photochemical reactions, but these do not appear to be significant in determining their aquatic fate. Antimony trioxide suspensions strongly absorb ultraviolet radiation below 325 nm and darken. The process is reversible, and when the light is removed, the white color slowly returns. The effect is believed to be due to peroxide radical formation on the crystal surface. Both water and oxygen seem to be necessary for the reoxidation of the reduced antimony.

Antimony can be reduced and methylated by microorganisms in the aquatic environment, similar to arsenic, and become mobilized. This reaction is most likely to occur in reducing environments, such as in bed sediment. In the case of arsenic, this reaction may be mediated by fungi and bacteria, but it is not known whether this is the case with antimony. The resulting trimethylstibine is initially oxidized by atmospheric oxygen to a mixture of trimethylstibine oxide ((CH₃)₃SbOH) and trimethylstibinic acid ((CH₃)₂SbO₃H), and then to antimony oxides and insoluble polymers. The rate constant is estimated to be of the order of 0.1 to 0.2 L/mol-sec. Trimethylstibine has a high vapor pressure, 103 mmHg at 25 deg C, and might volatilize before it is completely oxidized. The oxidation product, (CH₃)₃SbO, is much more soluble than trimethylstibine; therefore, oxidation will reduce volatilization. Oxidation of trimethylstibine in the gas phase is very rapid; the rate is 0.11/mmHg-sec or 2000 L/mol-sec. Trimethylstibine has been shown to react with alkyl iodides and bromides; this results in the formation of quaternary salts. Should antimony occur in a landfill with alkyl halides, the formation of quaternary salts should greatly enhance antimony's mobility.

There is evidence that phytoplankton can reduce Sb(V) to the Sb(III). Sb(III) decreases to very low levels at the base of the seasonal thermocline and remains low down to the sediment where increasing levels are again observed. Sb(III) only accounts for 44% of the inorganic antimony in the anoxic zone, and speciation in this region is unclear. Thermodynamically, the antimony should be in the trivalent state. Thiocomplexes are thought to account for some of the antimony in this zone. Methylated antimony species existed throughout the water column and made up 10% of total antimony. Monomethyl antimony species were more abundant in surface waters and in the anoxic zone. There was no sharp increase in methyl antimony near the sediment, which would be expected if these species were formed biosynthetically. Since the highest antimony concentration is at the surface, it is unlikely that antimony is taken up by phytoplankton, as is the case with arsenic. A decrease in antimony concentration with depth suggests scavenging by particulate matter and, at lower depths, by iron hydroxyoxides.

XYLENE:

■ Fish LC50 (96hr.) (mg/l):	13.5
■ BCF<100:	2.14- 2.20
■ log Kow (Prager 1995):	3.12- 3.20
■ Half- life Soil - High (hours):	672
■ Half- life Soil - Low (hours):	168
■ Half- life Air - High (hours):	44
■ Half- life Air - Low (hours):	2.6
■ Half- life Surface water - High (hours):	672

continued...

EPOXY RESIN 2165 PART A #164-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3315

Version No:4

CD 2009/3 Page 17 of 21

Section 12 - ECOLOGICAL INFORMATION

■ Half- life Surface water - Low (hours):	168
■ Half- life Ground water - High (hours):	8640
■ Half- life Ground water - Low (hours):	336
■ Aqueous biodegradation - Aerobic - High (hours):	672
■ Aqueous biodegradation - Aerobic - Low (hours):	168
■ Aqueous biodegradation - Anaerobic - High (hours):	8640
■ Aqueous biodegradation - Anaerobic - Low (hours):	4320
■ Photolysis maximum light absorption - High (nano- m):	269.5
■ Photolysis maximum light absorption - Low (nano- m):	265
■ Photooxidation half- life water - High (hours):	2.70E+08
■ Photooxidation half- life water - Low (hours):	3.90E+05
■ Photooxidation half- life air - High (hours):	44
■ Photooxidation half- life air - Low (hours):	2.6

■ Harmful to aquatic organisms.

■ For xylenes :

log Koc : 2.05-3.08

Koc : 25.4-204

Half-life (hr) air : 0.24-42

Half-life (hr) H₂O surface water : 24-672

Half-life (hr) H₂O ground : 336-8640

Half-life (hr) soil : 52-672

Henry's Pa m³ /mol: 637-879

Henry's atm m³ /mol: 7.68E-03

BOD 5 if unstated: 1.4,1%

COD : 2.56,13%

ThOD : 3.125

BCF : 23

log BCF : 1.17-2.41

Environmental Fate

Terrestrial fate:: Measured Koc values of 166 and 182, indicate that 3-xylene is expected to have moderate mobility in soil. Volatilisation of p-xylene is expected to be important from moist soil surfaces given a measured Henry's Law constant of 7.18×10^{-3} atm-cu m/mole. The potential for volatilisation of 3-xylene from dry soil surfaces may exist based on a measured vapor pressure of 8.29 mm Hg. p-Xylene may be degraded during its passage through soil). The extent of the degradation is expected to depend on its concentration, residence time in the soil, the nature of the soil, and whether resident microbial populations have been acclimated. p-Xylene, present in soil samples contaminated with jet fuel, was completely degraded aerobically within 5 days. In aquifer studies under anaerobic conditions, p-xylene was degraded, usually within several weeks, with the production of 3-methylbenzylfumaric acid, 3-methylbenzylsuccinic acid, 3-methylbenzoate, and 3-methylbenzaldehyde as metabolites.

Aquatic fate: Koc values indicate that p-xylene may adsorb to suspended solids and sediment in water. p-Xylene is expected to volatilise from water surfaces based on the measured Henry's Law constant. Estimated volatilisation half-lives for a model river and model lake are 3 hours and 4 days, respectively. BCF values of 14.8, 23.4, and 6, measured in goldfish, eels, and clams, respectively, indicate that bioconcentration in aquatic organisms is low. p-Xylene in water with added humic substances was 50% degraded following 3 hours irradiation suggesting that indirect photooxidation in the presence of humic acids may play an important role in the abiotic degradation of p-xylene. Although p-xylene is biodegradable and has been observed to degrade in pond water, there are insufficient data to assess the rate of this process in surface waters. p-Xylene has been observed to degrade in anaerobic and aerobic groundwater in several studies; however, it is known to persist for many years in groundwater, at least at sites where the concentration might have been quite high.

Atmospheric fate:

Most xylenes released to the environment will occur in the atmosphere and volatilisation is the dominant environmental fate process. In the ambient atmosphere, xylenes are expected to exist solely in the vapour phase. Xylenes are degraded in the atmosphere primarily by reaction with photochemically-produced hydroxyl radicals, with an estimated atmospheric lifetime of about 0.5 to 2 days. Xylenes' susceptibility to photochemical oxidation in the troposphere is to the extent that they may contribute to photochemical smog formation.

According to a model of gas/particle partitioning of semivolatile organic compounds in the atmosphere and from its vapour pressure, p-xylene, is expected to exist solely as a vapour in the ambient atmosphere. Vapour-

continued...

EPOXY RESIN 2165 PART A #164-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3315

Version No:4

CD 2009/3 Page 18 of 21

Section 12 - ECOLOGICAL INFORMATION

phase p-xylene is degraded in the atmosphere by reaction with photochemically-produced hydroxyl radicals; the half-life for this reaction in air is estimated to be about 16 hours. A half-life of 1.0 hr in summer and 10 hr in winter was measured for the reaction of p-xylene with photochemically-produced hydroxyl radicals. p-Xylene has a moderately high photochemical reactivity under smog conditions, higher than the other xylene isomers, with loss rates varying from 9-42% per hr. The photooxidation of p-xylene results in the production of carbon monoxide, formaldehyde, glyoxal, methylglyoxal, 3-methylbenzyl nitrate, m-tolualdehyde, 4-nitro-3-xylene, 5-nitro-3-xylene, 2,6-dimethyl-p-benzoquinone, 2,4-dimethylphenol, 6-nitro-2,4-dimethylphenol, 2,6-dimethylphenol, and 4-nitro-2,6-dimethylphenol.

Ecotoxicity:

for xylenes

Fish LC50 (96 h) Pimephales promelas 13.4 mg/l; Oncorhynchus mykiss 8.05 mg/l; Lepomis macrochirus 16.1 mg/l (all flow through values); Pimephales promelas 26.7 (static)

Daphnia EC50 948 h): 3.83 mg/l

Photobacterium phosphoreum EC50 (24 h): 0.0084 mg/l

Gammarus lacustris LC50 (48 h): 0.6 mg/l.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
Epoxy Resin 2165 Part A #164- 309		No data		
bisphenol A/ epichlorohydrin resin, liquid glycidyl neodecanoate	HIGH	No data	LOW	HIGH
tris(isopropylphen yl)phosphate	HIGH	No data	LOW	MED
antimony trioxide		No data		
xylene	LOW	LOW	LOW	

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Material may be disposed of by controlled burning in an approved incinerator or buried in an approved landfill.
- Prior to disposal in a landfill the material should be mixed with the other component and reacted to render the material inert.
- Extreme caution should be taken when heating the resin/curing agent mix.
- Recycle containers where possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION



■ Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 are not subject to this Code when transported by road or rail in;
(a) packagings;

continued...

EPOXY RESIN 2165 PART A #164-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3315

Version No:4

CD 2009/3 Page 19 of 21

Section 14 - TRANSPORTATION INFORMATION

(b) IBCs; or

(c) any other receptacle not exceeding 500 kg(L).

- Australian Special Provisions (SP AU01) - ADG Code 7th Ed.

Labels Required: MISCELLANEOUS

HAZCHEM: 2X (ADG6)

Land Transport UNDG:

Class or division: 9 Subsidiary risk: None

UN No.: 3082 UN packing group: III

Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(contains bisphenol A/ epichlorohydrin resin, liquid and tris(isopropylphenyl)phosphate)

Air Transport IATA:

ICAO/IATA Class: 9 ICAO/IATA Subrisk: ☐ ☐

UN/ID Number: 3082 Packing Group: III

Special provisions: A97

Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S. *(CONTAINS BISPHENOL A/ EPICHLOROHYDRIN RESIN,

LIQUID AND TRIS(ISOPROPYLPHENYL)PHOSPHATE)

Maritime Transport IMDG:

IMDG Class: 9 IMDG Subrisk: None

UN Number: 3082 Packing Group: III

EMS Number: F- A, S- F Special provisions: 274 909 944

Limited Quantities: 5 L Marine Pollutant: Not Determined

Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.(contains bisphenol A/ epichlorohydrin resin, liquid

and tris(isopropylphenyl)phosphate)

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE: S5

REGULATIONS

Regulations for ingredients

bisphenol A/ epichlorohydrin resin, liquid (CAS: 25068-38-6,25085-99-8) is found on the following regulatory lists;

"Australia Hazardous Substances", "Australia Inventory of Chemical Substances (AICS)", "OECD Representative List of High Production Volume (HPV) Chemicals"

glycidyl neodecanoate (CAS: 26761-45-5,71206-09-2) is found on the following regulatory lists;

"Australia Inventory of Chemical Substances (AICS)", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals"

tris(isopropylphenyl)phosphate (CAS: 68937-41-7) is found on the following regulatory lists;

"Australia Inventory of Chemical Substances (AICS)", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals"

antimony trioxide (CAS: 1309-64-4) is found on the following regulatory lists;

"Australia Exposure Standards", "Australia Hazardous Substances", "Australia Inventory of Chemical Substances (AICS)", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "International Chemical Secretariat (ChemSec) REACH SIN* List (*Substitute It Now!) 1.0", "OECD Representative List of High Production Volume (HPV) Chemicals"

xylene (CAS: 1330-20-7) is found on the following regulatory lists;

"Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals"

No data for Epoxy Resin 2165 Part A #164-309 (CW: 18-3315)

continued...

EPOXY RESIN 2165 PART A #164-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3315

Version No:4

CD 2009/3 Page 20 of 21

Section 16 - OTHER INFORMATION

Denmark Advisory list for selfclassification of dangerous substances

Substance	CAS	Suggested codes
glycidyl neodecanoate	26761- 45- 5	Mut3; R40 R43

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
bisphenol A/ epichlorohydrin resin, liquid	25068- 38- 6, 25085- 99- 8
glycidyl neodecanoate	26761- 45- 5, 71206- 09- 2

REPRODUCTIVE HEALTH GUIDELINES

■ Established occupational exposure limits frequently do not take into consideration reproductive end points that are clearly below the thresholds for other toxic effects. Occupational reproductive guidelines (ORGs) have been suggested as an additional standard. These have been established after a literature search for reproductive no-observed-adverse effect-level (NOAEL) and the lowest-observed-adverse-effect-level (LOAEL). In addition the US EPA's procedures for risk assessment for hazard identification and dose-response assessment as applied by NIOSH were used in the creation of such limits. Uncertainty factors (UFs) have also been incorporated.

Ingredient	ORG	UF	Endpoint	CR	Adeq TLV
xylene	1.5 mg/m3	10	D	NA	-

■ These exposure guidelines have been derived from a screening level of risk assessment and should not be construed as unequivocally safe limits. ORGS represent an 8-hour time-weighted average unless specified otherwise.

CR = Cancer Risk/10000; UF = Uncertainty factor:

TLV believed to be adequate to protect reproductive health:

LOD: Limit of detection

Toxic endpoints have also been identified as:

D = Developmental; R = Reproductive; TC = Transplacental carcinogen

Jankovic J., Drake F.: A Screening Method for Occupational Reproductive

American Industrial Hygiene Association Journal 57: 641-649 (1996).

EXPOSURE STANDARD FOR MIXTURES

■ "Worst Case" computer-aided prediction of spray/ mist or fume/ dust components and concentration:

■ Composite Exposure Standard for Mixture (TWA) :3 mg/m³.

■ Operations which produce a spray/mist or fume/dust, introduce particulates to the breathing zone.

If the breathing zone concentration of ANY of the components listed below is exceeded, "Worst Case" considerations deem the individual to be overexposed.

Component	Breathing Zone ppm	Breathing Zone mg/m3	Mixture Conc (%)
Component	Breathing zone (ppm)	Breathing zone (mg/m3)	
Mixture Conc (%)	tris(isopropylphenyl)phosphate	3.0000	
10.0			

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

continued...

EPOXY RESIN 2165 PART A #164-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3315

Version No:4

CD 2009/3 Page 21 of 21

Section 16 - OTHER INFORMATION

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 18-Dec-2008

Print Date: 5-Feb-2010

This is the end of the MSDS.



EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 1 of 26

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

EPOXY RESIN 2165 PART B #160-309

PROPER SHIPPING NAME

CORROSIVE LIQUID, N.O.S.(contains isophorone diamine)

PRODUCT USE

■ Used according to manufacturer's directions.

SUPPLIER


Company: RS Components	Company: RS Components
Address:	Address:
Units 30 & 31	25 Pavesi Street
Warehouse World	Smithfield
761 Great South Road	NSW2164
Penrose Auckland	AUS
	Telephone: 1300 656 636
	Emergency Tel: 1800 039 008
	Emergency Tel: 03 9573 3112
	Fax: 1300 656 696

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

CHEMWATCH HAZARD RATINGS



continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008


NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 2 of 26

Section 2 - HAZARDS IDENTIFICATION



POISONS SCHEDULE

S5

RISK

- Harmful in contact with skin and if swallowed.
- Causes burns.
- Risk of serious damage to eyes.
- May cause SENSITISATION by skin contact.
- Very toxic to aquatic organisms may cause long- term adverse effects in the aquatic environment.
- Possible risk of impaired fertility.
- Possible risk of harm to the unborn child.
- Inhalation may produce health damage*.
- Cumulative effects may result following exposure*.
- Limited evidence of a carcinogenic effect*.
- Possible respiratory sensitiser*.

* (limited evidence).

SAFETY

- Never add water to this product.
- Keep locked up.
- Do not breathe gas/fumes/vapour/spray.
- Keep container dry.
- Use only in well ventilated areas.
- Keep container in a well ventilated place.
- Avoid exposure - obtain special instructions before use.
- Keep container tightly closed.
- This material and its container must be disposed of in a safe way.
- Take off immediately all contaminated clothing.
- In case of accident or if you feel unwell IMMEDIATELY contact Doctor or Poisons Information Centre (show label if possible).
- Use appropriate container to avoid environmental contamination.
- Avoid release to the environment. Refer to special instructions/Safety data sheets.
- This material and its container must be disposed of as hazardous waste.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
isophorone diamine	2855-13-2	30-60
tris(isopropylphenyl)phosphate	68937-41-7	30-60
nonylphenol	25154-52-3	10-30
N- aminoethylpiperazine	140-31-8	5-10
salicylic acid	69-72-7	1-5
xylene	1330-20-7	<1

Section 4 - FIRST AID MEASURES

SWALLOWED

- For advice, contact a Poisons Information Centre or a doctor at once.
- Urgent hospital treatment is likely to be needed.

continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 3 of 26

Section 4 - FIRST AID MEASURES

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Transport to hospital or doctor without delay.

EYE

- If this product comes in contact with the eyes:
 - Immediately hold eyelids apart and flush the eye continuously with running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
 - Transport to hospital or doctor without delay.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
 - Immediately remove all contaminated clothing, including footwear.
 - Flush skin and hair with running water (and soap if available).
 - Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

- For acute or short-term repeated exposures to highly alkaline materials:
 - Respiratory stress is uncommon but present occasionally because of soft tissue edema.
 - Unless endotracheal intubation can be accomplished under direct vision, cricothyroidotomy or tracheotomy may be necessary.
 - Oxygen is given as indicated.
 - The presence of shock suggests perforation and mandates an intravenous line and fluid administration.
 - Damage due to alkaline corrosives occurs by liquefaction necrosis whereby the saponification of fats and solubilisation of proteins allow deep penetration into the tissue.

Alkalis continue to cause damage after exposure.

INGESTION:

- Milk and water are the preferred diluents
- No more than 2 glasses of water should be given to an adult.
- Neutralising agents should never be given since exothermic heat reaction may compound injury.
 - * Catharsis and emesis are absolutely contra-indicated.
 - * Activated charcoal does not absorb alkali.
 - * Gastric lavage should not be used.

Supportive care involves the following:

- Withhold oral feedings initially.
- If endoscopy confirms transmucosal injury start steroids only within the first 48 hours.
- Carefully evaluate the amount of tissue necrosis before assessing the need for surgical intervention.
- Patients should be instructed to seek medical attention whenever they develop difficulty in swallowing (dysphagia).

SKIN AND EYE:

- Injury should be irrigated for 20-30 minutes.

continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 4 of 26

Section 4 - FIRST AID MEASURES

Eye injuries require saline. [Ellenhorn & Barceloux: Medical Toxicology].

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Use fire fighting procedures suitable for surrounding area.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Combustible.
- Slight fire hazard when exposed to heat or flame.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).
- May emit acrid smoke.
- Mists containing combustible materials may be explosive.

Combustion products include: carbon dioxide (CO₂), nitrogen oxides (NO_x), phosphorus oxides (PO_x), other pyrolysis products typical of burning organic material.

May emit corrosive fumes.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM: 4W

Personal Protective Equipment

Gas tight chemical resistant suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Environmental hazard - contain spillage.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable, labelled container for waste disposal.

MAJOR SPILLS

- Environmental hazard - contain spillage.
- Clear area of personnel and move upwind.

continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 5 of 26

Section 6 - ACCIDENTAL RELEASE MEASURES

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Consider evacuation (or protect in place).
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Neutralise/decontaminate residue.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
- If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- DO NOT allow clothing wet with material to stay in contact with skin.
- DO NOT USE brass or copper containers / stirrers.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with moisture.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately. Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

- Lined metal can, lined metal pail/ can.
- Plastic pail.
- Polyliner drum.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.
- Avoid strong acids, acid chlorides, acid anhydrides and chloroformates.
- Avoid contact with copper, aluminium and their alloys.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.

continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 6 of 26

Section 7 - HANDLING AND STORAGE

- Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+: May be stored together

O: May be stored together with specific precautions

X: Must not be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³
Australia Exposure Standards	tris(isopropylphenyl)phosphate (Inspirable dust (not otherwise classified))		10		
Australia Exposure Standards	xylene (Xylene (o-, m-, p- isomers))	80	350	150	655

The following materials had no OELs on our records

- isophorone diamine: CAS:2855- 13- 2
- nonylphenol: CAS:25154- 52- 3 CAS:84852- 15- 3 CAS:139- 84- 4 CAS:136- 83- 4
- N- aminoethylpiperazine: CAS:140- 31- 8
- salicylic acid: CAS:69- 72- 7

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m ³)	Revised IDLH Value (ppm)
xylene		900

MATERIAL DATA

EPOXY RESIN 2165 PART B #160-309:

Not available

ISOPHORONE DIAMINE:

- No exposure limits set by NOHSC or ACGIH.

TRIS(ISOPROPYLPHENYL)PHOSPHATE:

- No exposure limits set by NOHSC or ACGIH.
- CEL TWA: 3 mg/m³ [refer REL TWA Petro-Canada]

NONYLPHENOL:

■ Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals,

continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 7 of 26

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

N-AMINOETHYLPIPERAZINE:

■ Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

SALICYLIC ACID:

■ It is the goal of the ACGIH (and other Agencies) to recommend TLVs (or their equivalent) for all substances for which there is evidence of health effects at airborne concentrations encountered in the workplace.

At this time no TLV has been established, even though this material may produce adverse health effects (as evidenced in animal experiments or clinical experience). Airborne concentrations must be maintained as low as is practically possible and occupational exposure must be kept to a minimum.

NOTE: The ACGIH occupational exposure standard for Particles Not Otherwise Specified (P.N.O.S) does NOT apply.

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this

continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 8 of 26

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

Airborne particulate or vapour must be kept to levels as low as is practicably achievable given access to modern engineering controls and monitoring hardware. Biologically active compounds may produce idiosyncratic effects which are entirely unpredictable on the basis of literature searches and prior clinical experience (both recent and past).

XYLENE:

■ for xylenes:

IDLH Level: 900 ppm

Odour Threshold Value: 20 ppm (detection), 40 ppm (recognition)

NOTE: Detector tubes for o-xylene, measuring in excess of 10 ppm, are available commercially. (m-xylene and p-xylene give almost the same response).

Xylene vapour is an irritant to the eyes, mucous membranes and skin and causes narcosis at high concentrations. Exposure to doses sufficiently high to produce intoxication and unconsciousness also produces transient liver and kidney toxicity. Neurologic impairment is NOT evident amongst volunteers inhaling up to 400 ppm though complaints of ocular and upper respiratory tract irritation occur at 200 ppm for 3 to 5 minutes.

Exposure to xylene at or below the recommended TLV-TWA and STEL is thought to minimise the risk of irritant effects and to produce neither significant narcosis or chronic injury. An earlier skin notation was deleted because percutaneous absorption is gradual and protracted and does not substantially contribute to the dose received by inhalation.

Odour Safety Factor(OSF)

OSF=4 (XYLENE).

Exposure limits with "skin" notation indicate that vapour and liquid may be absorbed through intact skin. Absorption by skin may readily exceed vapour inhalation exposure. Symptoms for skin absorption are the same as for inhalation. Contact with eyes and mucous membranes may also contribute to overall exposure and may also invalidate the exposure standard.

PERSONAL PROTECTION



EYE

- Chemical goggles.
- Full face shield may be required for supplementary but never for primary protection of eyes
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 9 of 26

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

HANDS/FEET

- When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.

NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

Suitability and durability of glove type is dependent on usage. Factors such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity,

are important in the selection of gloves.

- Leather wear not recommended: Contaminated leather footwear, watch bands, should be destroyed, i.e. burnt, as they cannot be adequately decontaminated.

OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

RESPIRATOR

■ Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	AK- AUS P	-
1000	50	-	AK- AUS P
5000	50	Airline *	-
5000	100	-	AK- 2 P
10000	100	-	AK- 3 P
	100+		Airline**

* - Continuous Flow

** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

■ General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:

solvent, vapours, degreasing etc., evaporating from tank (in still air).

aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)

direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts,

Air Speed:

0.25- 0.5 m/s (50- 100 f/min)

0.5- 1 m/s (100- 200 f/min.)

1- 2.5 m/s (200- 500 f/min.)

continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 10 of 26

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

gas discharge (active generation into zone of rapid air motion)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).

2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

1: Room air currents minimal or favourable to capture

2: Contaminants of low toxicity or of nuisance value only.

3: Intermittent, low production.

4: Large hood or large air mass in motion

Upper end of the range

1: Disturbing room air currents

2: Contaminants of high toxicity

3: High production, heavy use

4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Refer also to protective measures for the other component used with the product. Read both MSDS before using; store and attach MSDS together.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Liquid with characteristic odour.

PHYSICAL PROPERTIES

Corrosive.

Alkaline.

Molecular Weight: Not Applicable

Specific Gravity (water=1): 1.04 @25C

pH (1% solution): Not Available

Evaporation Rate: Not Available

Lower Explosive Limit (%): Not Available

Decomposition Temp (°C): Not Available

Boiling Range (°C): Not Available

Solubility in water (g/L): Not Available

Vapour Pressure (kPa): Not Available

Relative Vapour Density (air=1): Not Available

Upper Explosive Limit (%): Not Available

State: LIQUID

Melting Range (°C): Not Available

pH (as supplied): Not Available

Volatile Component (%vol): Not Available

Flash Point (°C): Not Available

Autoignition Temp (°C): Not Available

Viscosity: Not Available

continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 11 of 26

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

■ Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion. Aliphatic and alicyclic amines are generally well absorbed from the gut. Corrosive action may cause tissue damage throughout the gastrointestinal tract. Detoxification is thought to occur in the liver, kidney and intestinal mucosa with the enzymes, monoamine oxidase and diamine oxidase (histaminase) having a significant role.

Ingestion of amine epoxy-curing agents (hardeners) may cause severe abdominal pain, nausea, vomiting or diarrhoea. The vomitus may contain blood and mucous. If death does not occur within 24 hours there may be an improvement in the patients condition for 2-4 days only to be followed by the sudden onset of abdominal pain, board-like abdominal rigidity or hypo-tension; this indicates that delayed gastric or oesophageal corrosive damage has occurred.

EYE

■ The material can produce chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating.

The vapour when concentrated has pronounced eye irritation effects and this gives some warning of high vapour concentrations. If eye irritation occurs seek to reduce exposure with available control measures, or evacuate area.

Vapours of volatile amines cause eye irritation with lachrymation, conjunctivitis and minor transient corneal oedema which results in "halos" around lights (glauropsia, "blue haze", or "blue-grey haze"). Vision may become misty and halos may appear several hours after workers are exposed to the substance

This effect generally disappears spontaneously within a few hours of the end of exposure, and does not produce physiological after-effects. However oedema of the corneal epithelium, which is primarily responsible for vision disturbances, may take more than one or more days to clear, depending on the severity of exposure. Photophobia and discomfort from the roughness of the corneal surface also may occur after greater exposures. Although no detriment to the eye occurs as such, glauropsia predisposes an affected individual to physical accidents and reduces the ability to undertake skilled tasks such as driving a vehicle.

Direct local contact with the liquid may produce eye damage which may be permanent in the case of the lower molecular weight species.

SKIN

■ Skin contact with the material may be harmful; systemic effects may result following absorption.

The material can produce chemical burns following direct contact with the skin.

Open cuts, abraded or irritated skin should not be exposed to this material.

Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 12 of 26

Section 11 - TOXICOLOGICAL INFORMATION

INHALED

■ Inhalation of amine vapours may cause irritation of the mucous membranes of the nose and throat and lung irritation with respiratory distress and cough. Single exposures to near lethal concentrations and repeated exposures to sublethal concentrations produces tracheitis, bronchitis, pneumonitis and pulmonary oedema. Aliphatic and alicyclic amines are generally well absorbed from the respiratory tract. Systemic effects include headache, nausea, faintness and anxiety. These effects are thought to be transient and are probably related to the pharmacodynamic action of the amines. Histamine release by aliphatic amines may produce bronchoconstriction and wheezing.

Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.

CHRONIC HEALTH EFFECTS

■ Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Gastrointestinal disturbances may also occur. Chronic exposures may result in dermatitis and/or conjunctivitis.

Practical experience shows that skin contact with the material is capable either of inducing a sensitisation reaction in a substantial number of individuals, and/or of producing a positive response in experimental animals.

Exposure to the material may cause concerns for human fertility, generally on the basis that results in animal studies provide sufficient evidence to cause a strong suspicion of impaired fertility in the absence of toxic effects, or evidence of impaired fertility occurring at around the same dose levels as other toxic effects, but which are not a secondary non-specific consequence of other toxic effects.

Exposure to the material may cause concerns for humans owing to possible developmental toxic effects, generally on the basis that results in appropriate animal studies provide strong suspicion of developmental toxicity in the absence of signs of marked maternal toxicity, or at around the same dose levels as other toxic effects but which are not a secondary non-specific consequence of other toxic effects.

On the basis, primarily, of animal experiments, concern has been expressed by at least one classification body that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment.

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Limited evidence shows that inhalation of the material is capable of inducing a sensitisation reaction in a significant number of individuals at a greater frequency than would be expected from the response of a normal population.

Pulmonary sensitisation, resulting in hyperactive airway dysfunction and pulmonary allergy may be accompanied by fatigue, malaise and aching. Significant symptoms of exposure may persist for extended periods, even after exposure ceases. Symptoms can be activated by a variety of nonspecific environmental stimuli such as automobile exhaust, perfumes and passive smoking.

Sensitisation may give severe responses to very low levels of exposure, in situations where exposure may occur.

TOXICITY AND IRRITATION

■ Not available. Refer to individual constituents.

ISOPHORONE DIAMINE:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: 1030 mg/kg [Manufacturer HUE]

■ Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged

IRRITATION

continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 13 of 26

Section 11 - TOXICOLOGICAL INFORMATION

exposure to irritants may produce conjunctivitis.

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production. The material may produce respiratory tract irritation. Symptoms of pulmonary irritation may include coughing, wheezing, laryngitis, shortness of breath, headache, nausea, and a burning sensation. Unlike most organs, the lung can respond to a chemical insult or a chemical agent, by first removing or neutralising the irritant and then repairing the damage (inflammation of the lungs may be a consequence).

The repair process (which initially developed to protect mammalian lungs from foreign matter and antigens) may, however, cause further damage to the lungs (fibrosis for example) when activated by hazardous chemicals. Often, this results in an impairment of gas exchange, the primary function of the lungs. Therefore prolonged exposure to respiratory irritants may cause sustained breathing difficulties.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

TRIS(ISOPROPYLPHENYL)PHOSPHATE:

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: > 5000 mg/kg
Dermal (rabbit) LD50: > 2000 mg/kg
Inhalation (rat) LC50: > 6350 mg/m³/4h

IRRITATION

Skin: Mild **
Eye: Mild **

NONYLPHENOL:

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: 1620 mg/kg

IRRITATION

Skin(rabbit):10mg/24h(open)- SEVERE

Skin (rabbit) LD50: 2140 mg/kg Skin (rabbit): 500 mg(open)- Moderate
Eye (rabbit): 0.5 mg (open)- SEVERE

- The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may produce severe skin irritation after prolonged or repeated exposure, and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) thickening of the epidermis.

Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis. Prolonged contact is unlikely, given the severity of response, but repeated exposures may produce severe ulceration.

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating

continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 14 of 26

Section 11 - TOXICOLOGICAL INFORMATION

inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production. Nonylphenol was studied for oral toxicity in rats in a 28-day repeat dose toxicity test at doses of 0, 4, 15, 60 and 250 mg/kg/day. Changes suggesting renal dysfunction were mainly noted in both sexes given 250 mg/kg. Liver weights were increased in males given 60 mg/kg and in both sexes given 250 mg/kg group. Histopathologically, hypertrophy of the centrilobular hepatocytes was noted in both sexes given 250 mg/kg. Kidney weights were increased in males given 250 mg/kg and macroscopically, disseminated white spots, enlargement and pelvic dilatation were noted in females given 250 mg/kg. Histopathologically, the following lesions were noted in the 250 mg/kg group: basophilic change of the proximal tubules in both sexes, single cell necrosis of the proximal tubules, inflammatory cell infiltration in the interstitium and casts in females, basophilic change and dilatation of the collecting tubules in both sexes, simple hyperplasia of the pelvic mucosa and pelvic dilatation in females. In the urinary bladder, simple hyperplasia was noted in both sexes given 250 mg/kg. In the cecum, macroscopic dilatation was noted in both sexes given 250 mg/kg. Almost all changes except those in the kidney disappeared after a 14-day recovery period. The NOELs for males and females are considered to be 15 mg/kg/day and 60 mg/kg/day, respectively, under the conditions of the present study.

Nonylphenol was not mutagenic to *Salmonella typhimurium*, TA100, TA1535, TA98, TA1537 and *Escherichia coli* WP2 uvrA, with or without an exogenous metabolic activation system.

Nonylphenol induced neither structural chromosomal aberrations nor polyploidy in CHL/IU cells, in the absence or presence of an exogenous metabolic activation system.

N-AMINOETHYLPIPERAZINE:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: 2410 mg/kg

Dermal (rabbit) LD50: 880 mg/kg

Intraperitoneal (Mouse) LD50: 250 mg/kg

■ Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may produce severe skin irritation after prolonged or repeated exposure, and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) thickening of the epidermis.

Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis. Prolonged contact is unlikely, given the severity of response, but repeated exposures may produce severe ulceration.

Handling ethyleneamine products is complicated by their tendency to react with other chemicals, such as carbon dioxide in the air, which results in the formation of solid carbamates. Because of their ability to produce chemical burns, skin rashes, and asthma-like symptoms, ethyleneamines also require substantial care in handling. Higher molecular weight ethyleneamines are often handled at elevated temperatures further increasing the possibility of vapor exposure to these compounds.

Because of the fragility of eye tissue, almost any eye contact with any ethyleneamine may cause irreparable damage, even blindness. A single, short exposure to ethyleneamines, may cause severe skin burns, while a single, prolonged exposure may result in the material being absorbed through the skin in harmful amounts. Exposures have caused allergic skin reactions in some individuals. Single dose oral toxicity of ethyleneamines is low. The oral LD50 for rats is in the range of 1000 to 4500 mg/kg for the ethyleneamines. In general, the low-molecular weight polyamines have been positive in the Ames assay, increase sister chromatid exchange in Chinese hamster ovary (CHO) cells, and are positive for unscheduled DNA synthesis although they are negative in the mouse micronucleus assay. It is believed that the positive results are

continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 15 of 26

Section 11 - TOXICOLOGICAL INFORMATION

based on its ability to chelate copper.

for piperazine:

Exposure to piperazine and its salts has clearly been demonstrated to cause asthma in occupational settings. No NOAEL can be estimated for respiratory sensitisation (asthma).

Although the LD50 levels indicate a relatively low level of oral acute toxicity (LD50 1-5 g/kg bw), signs of neurotoxicity may appear in humans after exposure to lower doses. Based on exposure levels of up to 3.4 mg/kg/day piperazine base and a LOAEL of 110 mg/kg, there is no concern for acute toxicity

In pigs, piperazine is readily absorbed from the gastrointestinal tract, and the major part of the resorbed compound is excreted as unchanged piperazine during the first 48 hours. The principal route of excretion of piperazine and its metabolites is via urine, with a minor fraction recovered from faeces (16%). In humans the kinetics of the uptake and excretion of piperazine and its metabolites with urine appear to be roughly similar to that in the pig, and the nature and extent of conversion to metabolites has not been determined.

Piperazine has demonstrated a low acute toxicity (LD50 = 1-5 g/kg bw) by the oral, dermal, and subcutaneous route of administration to rodents, whereas adequate inhalation toxicity data have not been found. However, there are findings of EEG (electroencephalogram) changes in 37% of 89 children administered 90-130 mg/kg piperazine (two doses during one day), corroborated by a proposed GABA (gamma-aminobutyric acid) receptor agonism exerted by piperazine. Since clinical symptoms of neurotoxicity may occur after exposure to higher doses, a LOAEL of 110 mg/kg piperazine base for acute neurotoxicity in humans after acute exposure is proposed.

Piperazine, as concentrated aqueous solution, has strongly irritating properties with regard to skin, and should be regarded as corrosive with respect to the eye. Exposure to piperazine and its salts has been demonstrated to cause allergic dermatitis as well as respiratory sensitisation in humans. As shown by the LLNA, piperazine has a sensitising potential in animals. Although piperazine is clearly sensitising, no NOAEL can be set for this effect from the present database.

A NOAEL of 25 mg/kg/day of piperazine for liver toxicity in the beagle dog has been chosen after repeated exposure. A LOAEL of 30 mg/kg/day of piperazine for neurotoxicity is proposed based on documentation of (rare cases) of neurotoxicity from human clinical practice. Neurotoxicity also appears in other species (e.g., rabbits, dogs, cats, tigers, and horses), but not in rodents.

For reproductive effects of piperazine, there is a NOAEL of 125 mg/kg/day for effects on fertility, i.e., reduced pregnancy index, decreased number of implantation sites, and decreased litter sizes in rats. The teratogenic properties have been investigated in rats and rabbits in adequate studies. In rabbit, such effects may be elicited at a dose level that is also toxic to the dam. The LOAEL is 94 mg/kg/day, and the NOAEL 42 mg/kg/day piperazine base (maternal and embryotoxic). In the rat study, there were decreases in body weight of both dams and offspring at the top dose (2,100 mg/kg/day piperazine base), but there were no signs of any malformations.

The genotoxic properties have been investigated both in vitro (in the Ames test, in a nonstandard study on *Saccharomyces cerevisiae* and in Chinese hamster ovary cells) and in vivo, in a micronuclei assay on mice, all with negative results. There are no solid indications of a carcinogenic effect of piperazine, neither in animal studies, nor from the investigation on humans. In view of lack of genotoxic action, it appears unlikely that piperazine poses a carcinogenic risk.

There seems to be an additional cancer risk due to the formation of N-mononitrosopiperazine (NPZ) from piperazine. It is possible to calculate a hypothetical additional cancer risk posed by NPZ after exposure to piperazine, but the calculation would depend on several assumptions. We conclude that there seems to be an additional cancer risk due to the formation of NPZ from piperazine, and although it is difficult to estimate, it is probably small.

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

SALICYLIC ACID:

continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 16 of 26

Section 11 - TOXICOLOGICAL INFORMATION

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (man) LDLo: 50 mg/kg*

Oral (rat) LD50: 891 mg/kg

Oral (rat) TDLo: 1400 mg/kg** [*BDH], [**Extal]

Dermal (man) TDLo: 57 mg/kg

Intraperitoneal (Rat) LD50: 157 mg/kg

Oral (Mouse) LD50: 480 mg/kg

Intraperitoneal (Mouse) LD50: 300 mg/kg

Subcutaneous (Mouse) LD: 520 mg/kg

Intravenous (Mouse) LD50: 184 mg/kg

Oral (Cat) LD50: 400 mg/kg

Oral (Rabbit) LD50: 1300 mg/kg

■ Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production. The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

For certain benzyl derivatives:

All members of this group (benzyl, benzoate and 2-hydroxybenzoate (salicylate) esters) contain a benzene ring bonded directly to an oxygenated functional group (aldehyde or ester) that is hydrolysed and/or oxidised to a benzoic acid derivative. As a stable animal metabolite, benzoic acid derivatives are efficiently excreted primarily in the urine. These reaction pathways have been reported in both aquatic and terrestrial species. The similarity of their toxicologic properties is a reflection their participation in these common metabolic pathways.

In general, members of this group are rapidly absorbed through the gastrointestinal tract, metabolised primarily in the liver, and excreted in the urine either unchanged or as conjugates of benzoic acid derivatives. At high doses, conjugation pathways (e.g., glycine) may be saturated; in which case, free benzoic acid is excreted unchanged. Absorption, distribution and excretion studies have been conducted several members of this group and structural relatives. These substances exhibit remarkably similar patterns of pharmacokinetics and metabolism. The benzyl, benzoate, and 2-hydroxybenzoate (salicylate) esters which comprise this category are hydrolysed to the corresponding alcohols and carboxylic acids. The benzyl alcohol and benzaldehyde derivatives are oxidised to the corresponding benzoic acid derivatives that are subsequently excreted unchanged or as glycine or glucuronic acid conjugates. If methoxy or phenolic functional groups are present on the benzene ring, additional minor metabolic options become available. O-demethylation yields the corresponding phenol that is subsequently excreted as the glucuronic acid or sulfate conjugates. At high dose levels, gut microflora may act to produce minor amounts of reduction metabolites.

Acute toxicity: Oral LD50 values ranged from 887 to greater than 5,000 mg/kg bw demonstrating the low to moderate toxicity of these compounds.

Repeat dose toxicity: Overall, numerous repeat-dose studies using various routes of exposure have been conducted in different animal species with members of this chemical category or their close structural relatives. It is important to note that all the benzyl derivatives in this category are eventually metabolised to a common metabolite, benzoic acid, and are rapidly excreted in the urine as benzoic acid or as its glycine, sulfate, or glucuronic acid conjugate. For this reason, the repeat-dose studies currently available provide adequate support for the safety of the benzyl derivatives. Moreover, the levels at which no

continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 17 of 26

Section 11 - TOXICOLOGICAL INFORMATION

adverse effects were reported were sufficiently high to accommodate any potential differences among the members of the category.

Reproductive toxicity: Several reproductive toxicity studies have been conducted with representatives of this group and produced no evidence of reproductive toxicity. As with the repeat-dose studies, the benzyl derivatives generally follow the similar metabolic pathways and the studies conducted provide an adequate database for this endpoint. In addition, the dose levels tested provide margins of safety large enough to accommodate any differences among the group.

Developmental toxicity: Representative substances from this group were tested for developmental toxicity with uniform results, and indicated no teratogenic potential in the absence of maternal toxicity. Again, the representative substances undergo similar metabolism to the entire benzyl derivative group and therefore, provide an adequate representation for this endpoint.

Genetic toxicity: Overall, in vitro and in vivo genotoxicity studies have been conducted with substances representing the structural characteristics of the benzyl category. The results of these studies were predominantly negative demonstrating a low order of genotoxic potential. Limited positive and/or equivocal findings have been reported for 3 aldehydes and benzyl acetate, but, in most cases, other studies of the same endpoint with same test substance show no activity. Most importantly, in vivo studies on benzaldehyde derivatives and closely related benzyl esters have all yielded negative results. These negative in vivo genotoxicity assays are supported by the lack of tumorigenicity in chronic animal studies with representatives of this group.

Data available for more than 100 in vitro genotoxicity assays for 9 members of the category and five metabolic precursors or metabolites of benzyl derivatives indicate a low genotoxic potential for members of this chemical category.

Equivocal results have been reported mainly for aromatic aldehydes in the MLA and ABS assays.

XYLENE:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (human) LDLo: 50 mg/kg

Oral (rat) LD50: 4300 mg/kg

Inhalation (human) TCLo: 200 ppm

Inhalation (man) LCLo: 10000 ppm/6h

Inhalation (rat) LC50: 5000 ppm/4h

Oral (Human) LD: 50 mg/kg

Inhalation (Human) TCLo: 200 ppm/4h

Intraperitoneal (Rat) LD50: 2459 mg/kg

Subcutaneous (Rat) LD50: 1700 mg/kg

Oral (Mouse) LD50: 2119 mg/kg

Intraperitoneal (Mouse) LD50: 1548 mg/kg

Intravenous (Rabbit) LD: 129 mg/kg

Inhalation (Guinea) pig: LC 450 ppm/4h

■ The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

Reproductive effector in rats

IRRITATION

Skin (rabbit): 500 mg/24h Moderate

Eye (human): 200 ppm Irritant

Eye (rabbit): 87 mg Mild

Eye (rabbit): 5 mg/24h SEVERE

CARCINOGEN

Xylenes

International Agency
for Research on Cancer
(IARC) - Agents
Reviewed by the IARC
Monographs

Group

3

continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 18 of 26

Section 11 - TOXICOLOGICAL INFORMATION

REPROTOXIN

xylene

ILO Chemicals in the electronics industry
that have toxic effects on reproduction

Reduced fertility or
sterility

Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

ISOPHORONE DIAMINE:

XYLENE:

N-AMINOETHYLPIPERAZINE:

■ Harmful to aquatic organisms.

EPOXY RESIN 2165 PART B #160-309:

XYLENE:

SALICYLIC ACID:

N-AMINOETHYLPIPERAZINE:

NONYLPHENOL:

ISOPHORONE DIAMINE:

■ DO NOT discharge into sewer or waterways.

ISOPHORONE DIAMINE:

N-AMINOETHYLPIPERAZINE:

NONYLPHENOL:

■ Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters. Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

ISOPHORONE DIAMINE:

N-AMINOETHYLPIPERAZINE:

NONYLPHENOL:

■ Prevent, by any means available, spillage from entering drains or water courses.

EPOXY RESIN 2165 PART B #160-309:

NONYLPHENOL:

■ Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

EPOXY RESIN 2165 PART B #160-309:

Marine Pollutant: Not Determined

ISOPHORONE DIAMINE:

/53

LC50 (24h) Daphnae: 42 mg/L.

LD50 (48h) Leuciscus idus: 185 mg/L.

NOEC (21day) Daphnia magna: 3 mg/L *

EC10 (16hr) Pseudomonas putida: 1120 mg/L *

Persistence/Biodegradability: 42% (DOC, OECD 303A) *

8.0% (DOC, Die away test -9/69/EEC) *

* [Morton]

NONYLPHENOL:

■ Environmental toxicity is a function of the n-octanol/ water partition coefficient (log Pow, log Kow). Phenols with log Pow >7.4 are expected to exhibit low toxicity to aquatic organisms. However the toxicity of phenols with a lower log Pow is variable, ranging from low toxicity (LC50 values >100 mg/l) to highly toxic (LC50 values <1 mg/l) dependent on log Pow, molecular weight and substitutions on the aromatic ring. Dinitrophenols are more toxic than predicted from QSAR estimates. Hazard information for these groups is not

continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 19 of 26

Section 12 - ECOLOGICAL INFORMATION

generally available.

■ for alkylphenols and their ethoxylates, or propoxylates:

Environmental fate: Alkylphenols are ubiquitous in the environment after the introduction, generally as wastes, of their alkoxyated forms (ethoxylates and propoxylates, for example); these are extensively used throughout industry and in the home.

Alkylphenol ethoxylates are widely used surfactants in domestic and industrial products, which are commonly found in wastewater discharges and in sewage treatment plant (STP) effluent's. Degradation of APEs in wastewater treatment plants or in the environment generates more persistent shorter-chain APEs and alkylphenols (APs) such as nonylphenol (NP), octylphenol (OP) and AP mono- to triethoxylates (NPE1, NPE2 and NPE3). There is concern that APE metabolites (NP, OP, NPE1-3) can mimic natural hormones and that the levels present in the environment may be sufficient to disrupt endocrine function in wildlife and humans. The physicochemical properties of the APE metabolites (NP, NPE1-4, OP, OPE1-4), in particular the high Kow values, indicate that they will partition effectively into sediments following discharge from STPs. The aqueous solubility data for the APE metabolites indicate that the concentration in water combined with the high partition coefficients will provide a significant reservoir (load) in various environmental compartments.

Data from studies conducted in many regions across the world have shown significant levels in samples of every environmental compartment examined. In the US, levels of NP in air ranged from 0.01 to 81 ng/m³, with seasonal trends observed. Concentrations of APE metabolites in treated wastewater effluents in the US ranged from < 0.1 to 369 ug/l, in Spain they were between 6 and 343 ug/l and concentrations up to 330 ug/l were found in the UK. Levels in sediments reflected the high partition coefficients with concentrations reported ranging from < 0.1 to 13,700 ug/kg for sediments in the US. Fish in the UK were found to contain up to 0.8 ug/kg NP in muscle tissue. APEs degraded faster in the water column than in sediment. Aerobic conditions facilitate easier further biotransformation of APE metabolites than anaerobic conditions.

Nonylphenols are susceptible to photochemical degradation. Using natural, filtered, lake water it was found that nonylphenol had a half-life of approximately 10-15 h under continuous, noon, summer sun in the surface water layer, with a rate approximately 1.5 times slower at depths 20-25 cm. Photolysis was much slower with ethoxylated nonylphenol, and so it is unlikely to be a significant event in removal of the ethoxylates

Air: Alkylphenols released to the atmosphere will exist in the vapour phase and is thought to be degraded by reaction with photochemically produced hydroxyl radicals, with a calculated half-life, for nonylphenol, of 0.3 days.

Water: Abiotic degradation of alkylphenol is negligible. Biodegradation does not readily take place. The half-life in surface water may be around 30 days.

Degradation: Alkylphenol ethoxylates (APES) may abiotically degrade into the equivalent alkylphenol. During degradation ethylene oxide units are cleaved off the ethylene oxide chain until only short-chain alkylphenol ethoxylates remain, typically mono- and diethylene oxides. Oxidation of these oligomers creates the corresponding carboxylic acids. This leaves several degradation products: short-chain ethoxylates, their carboxylic acids, and alkylphenols.

Biodegradation: Alkylphenols are not readily biodegradable. Several mechanisms of microbial aromatic ring degradation have been reported, the most common being formation of catechol from phenol, followed by ring scission between or adjacent to the two hydroxyl groups.

The full breakdown pathway for APES has not yet been determined, and all studies have so far focused on identification of intermediates in bacterial culture media, rather than studying cell-free systems or purified enzymes. It is, however, likely that microbial metabolism usually starts by an attack on the ethoxylate chain, rather than on the ring or the hydrophobic chain. The ethoxylate groups are progressively removed, either by ether cleavage, or by terminal alcohol oxidation followed by cleavage of the resulting carboxylic acid

Biodegradation of APEs produces less biodegradable products: alkylphenol mono- and di-ethoxylates, alkylphenoxy acetic and alkylphenoxy polyethoxy acetic acids, and alkylphenols. These metabolites frequently persist through sewage treatment and in rivers. Anaerobic conditions generally lead to the accumulation of alkylphenols. The rate of biodegradation seems to decrease with increasing length of the ethylene oxide chain.

Bioaccumulation: Metabolites of APES accumulate in organisms, with bioconcentration factors varying from ten to several thousand, depending on species, metabolite and organ.

The metabolites of APES are generally more toxic than the original compounds. APES have LC50s above about 1.5 mg/l, whereas alkylphenols, such as nonylphenol, have LC50s are generally around 0.1 mg/l

Oestrogenic activity: The role of alkyl chain length and branching, substituent position, number of alkylated groups, and the requirement of a phenolic ring structure was assessed in fish. The results showed that most alkylphenols were oestrogenic, although with 3-300 thousand times lower potency than the endogenous estrogen 17beta-estradiol. Mono-substituted tertiary alkylphenols with moderate (C4-C5) and long alkyl chain length (C8-C9) in the para position exhibited the highest oestrogenic potency. Substitution with multiple

continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 20 of 26

Section 12 - ECOLOGICAL INFORMATION

alkyl groups, presence of substituents in the ortho- and meta-position and lack of a hydroxyl group on the benzene ring reduced the oestrogenic activity, although several oestrogenic alkylated non-phenolics were identified.

Human exposure: Alkylphenols were first found to be oestrogenic (oestrogen-mimicking) in the 1930s, but more recent research has highlighted the implications of these effects. The growth of cultured human breast cancer cells is affected by nonylphenol at concentrations as low as 1 μM (220 $\mu\text{g/l}$) or concentrations of octylphenol as low as 0.1 μM (20 $\mu\text{g/l}$). Oestrogenic effects have also been shown on rainbow trout hepatocytes, chicken embryo fibroblasts and a mouse oestrogen receptor.

The insecticide chlordecone (Kepone) shows similar behaviour to alkylphenols, accumulating in liver and adipose tissue, and eliciting oestrogenic activity. Workers exposed to this insecticide can suffer reproductive effects such as low sperm counts and sterility. In addition, the oestrogenic effects of chlordecone on MCF7 cells occur at similar concentrations to those of alkylphenols, suggesting that alkylphenols will be a similar health hazard if target cells are exposed to μM levels of these compounds. By comparing environmental concentrations, bioconcentration factors and in vitro oestrogenic effect levels, current environmental levels of alkylphenolic compounds are probably high enough to affect the hormonal control systems of some organisms. It is also possible that human health could be being affected.

■ The material is classified as an ecotoxin* because the Daphnia EC50 (48 hours) is less than or equal to 0.1 mg/l

* Classification of Substances as Ecotoxic (Dangerous to the Environment)

Appendix 8, Table 1

Compiler's Guide for the Preparation of International Chemical Safety Cards: 1993 Commission of the European Communities.

BCF: mussel 8-12

Toxicity Fish: LD50(96)7 mg/L

N-AMINOETHYLPIPERAZINE:

/53#90piperz

SALICYLIC ACID:

■ log Pow (Verschuereen 1983):	2.21/2.26
■ BOD5:	0.95 (41%)
■ COD:	1.58 (100%)
■ ThOD:	1.623

■ For salicylic acid:

log Kow : 0.35-2.26

BOD5: 0.95,41%

COD : 1.58,100%

ThOD : 1.623

BOD = 141%, 5 days

Environmental fate:

Due to the chemical structure of salicylic acid volatilisation and bioconcentration are not expected to be important environmental fate processes. Biodegradation is expected to be the dominant removal mechanism of salicylic acid from soil and water. It may also undergo photochemical degradation in sunlight environmental media

In air, it is expected to exist in both the vapor and particulate phase. Vapor phase reaction with photochemically produced hydroxyl radicals may be important (estimated half-life of 1.2 days). Removal by wet and dry deposition can also occur..

This chemical is not likely to bioconcentrate.

Biodegradable

Ecotoxicity:

Daphnia EC50 (24 h): 180 mg/l

Algae EC50 (72 h): 60 mg/l

Dangerous to aquatic life in high concentrations.

■ For certain benzyl derivatives:

Environmental fate:

All members of this group (benzyl, benzoate and 2-hydroxybenzoate (salicylate) esters) contain a benzene ring bonded directly to an oxygenated functional group (aldehyde or ester) that is hydrolysed and/or oxidised to a

continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 21 of 26

Section 12 - ECOLOGICAL INFORMATION

benzoic acid derivative:

Photodegradation: The calculated half lives for hydroxyl radical reactions range from 4.7 to 64.5 hours. The calculated photodegradation half-lives for three benzaldehyde derivatives in this chemical category are in the narrow range from 4.7 hours for m-methoxy-p-hydroxybenzaldehyde to 7.2 hours for the less substituted derivative benzaldehyde. The relative half-lives reflect the increased reactivity of a phenolic OH group. The half-lives for the aldehydes are shorter than those for the corresponding benzyl and benzoate esters in this category (12.7 for methyl benzoate to 64.5 hours for methyl p-methylbenzoate) Generally, the carb

function of the ester is more stable to reaction with hydroxyl radicals than The calculated half lives for hydroxyl radical reactions range from 4.7 to 64.5 hours. The calculated photodegradation half-lives for three benzaldehyde derivatives in this chemical category are in the narrow range from 4.7 hours for m-methoxy-phydroxybenzaldehyde to 7.2 hours for the less substituted derivative benzaldehyde . The relative half-lives reflect the increased reactivity of a phenolic OH group. The half-lives for the aldehydes are shorter than those for the corresponding benzyl and benzoate esters in this category (12.7 for methyl benzoate to 64.5 hours for methyl p-methylbenzoate). Generally, the carboxylate function of the ester is more stable to reaction with hydroxyl radicals than is the aldehyde function. The presence of an aromatic phenol function capable of undergoing ready hydrogen abstraction of the phenolic hydroxyl group decreases predicted photodegradation half-lives. Therefore, the methyl, pentyl and benzyl esters of 2-hydroxybenzoic acid have calculated half-lives of 11.6, 7.6, and 7.4 hours, respectively

Stability in Water: Benzaldehydes in this group cannot hydrolyse. However, they are likely to be slowly oxidized to their corresponding acids. The calculated hydrolysis half-lives for esters range from 20 days at pH 8 and 198 days at pH 7 for benzyl acetate to 1.1 years at pH 8 and 10.8 years at pH 7 for methyl p-methylbenzoate. Benzyl acetate, like several other benzyl esters, was shown to be 50% hydrolysed in 2 hours at pH 7.5 in the presence of pancreatin in an in vitro simulation experiment . These esters are all expected to be readily hydrolysed in vivo.

Biodegradation: All are readily and ultimately biodegradable using a standard OECD 301B test or 301F protocol. The parent acid benzoic acid, its sodium salt, and 2-hydroxybenzoic acid were all readily biodegradable in a COD (chemical oxygen demand) test. Since hydrolysis of the esters and ready oxidation of the aldehydes yields corresponding acid derivatives, the data on benzoic acid, its sodium salt, and 2-hydroxybenzoic acid validate the observations that the aldehydes and esters in this chemical category are readily biodegradable.

Ecotoxicity:

Experimental data indicate a low to moderate toxicity for the benzyl derivatives. Benzyl esters and 2-hydroxybenzoate esters (salicylates) exhibit higher acute toxicity to fish than do benzoate esters or benzaldehyde derivatives. Measured values for benzyl and salicylate esters are in the 1-5 mg/l range with salicylates being slightly more toxic. Benzoate ester and benzaldehyde derivatives exhibit 96-hour LC50 values above 10 mg/L

Benzaldehyde derivatives exhibit lower acute toxicity compared to the parent substance.

Fish LC50 (14-d): guppy 0.17 mg/l (benzaldehyde)

Fish LC50 (96 h): guppy 88-116 mg/l (m-methoxy-p-hydroxybenzaldehyde)

Fish LC50 (96 h): 13-23.5 mg/l (benzaldehyde, p-methoxybenzaldehyde, m-methoxy-p-hydroxybenzaldehyde; estimated values).

Acute toxicity for aquatic invertebrates parallels that for fish in the benzyl chemical category. Benzoate esters exhibit moderate experimental and calculated acute toxicity to invertebrates.

XYLENE:

■ Fish LC50 (96hr.) (mg/l):	13.5
■ BCF<100:	2.14- 2.20
■ log Kow (Prager 1995):	3.12- 3.20
■ Half- life Soil - High (hours):	672
■ Half- life Soil - Low (hours):	168
■ Half- life Air - High (hours):	44
■ Half- life Air - Low (hours):	2.6
■ Half- life Surface water - High (hours):	672
■ Half- life Surface water - Low (hours):	168
■ Half- life Ground water - High (hours):	8640
■ Half- life Ground water - Low (hours):	336
■ Aqueous biodegradation - Aerobic - High (hours):	672
■ Aqueous biodegradation - Aerobic - Low (hours):	168
■ Aqueous biodegradation - Anaerobic - High (hours):	8640

continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 22 of 26

Section 12 - ECOLOGICAL INFORMATION

■ Aqueous biodegradation - Anaerobic - Low (hours):	4320
■ Photolysis maximum light absorption - High (nano- m):	269.5
■ Photolysis maximum light absorption - Low (nano- m):	265
■ Photooxidation half- life water - High (hours):	2.70E+08
■ Photooxidation half- life water - Low (hours):	3.90E+05
■ Photooxidation half- life air - High (hours):	44
■ Photooxidation half- life air - Low (hours):	2.6

■ For xylenes :

log Koc : 2.05-3.08

Koc : 25.4-204

Half-life (hr) air : 0.24-42

Half-life (hr) H2O surface water : 24-672

Half-life (hr) H2O ground : 336-8640

Half-life (hr) soil : 52-672

Henry's Pa m3 /mol: 637-879

Henry's atm m3 /mol: 7.68E-03

BOD 5 if unstated: 1.4,1%

COD : 2.56,13%

ThOD : 3.125

BCF : 23

log BCF : 1.17-2.41

Environmental Fate

Terrestrial fate:: Measured Koc values of 166 and 182, indicate that 3-xylene is expected to have moderate mobility in soil. Volatilisation of p-xylene is expected to be important from moist soil surfaces given a measured Henry's Law constant of 7.18×10^{-3} atm-cu m/mole. The potential for volatilisation of 3-xylene from dry soil surfaces may exist based on a measured vapor pressure of 8.29 mm Hg. p-Xylene may be degraded during its passage through soil). The extent of the degradation is expected to depend on its concentration, residence time in the soil, the nature of the soil, and whether resident microbial populations have been acclimated. p-Xylene, present in soil samples contaminated with jet fuel, was completely degraded aerobically within 5 days. In aquifer studies under anaerobic conditions, p-xylene was degraded, usually within several weeks, with the production of 3-methylbenzylfumaric acid, 3-methylbenzylsuccinic acid, 3-methylbenzoate, and 3-methylbenzaldehyde as metabolites.

Aquatic fate: Koc values indicate that p-xylene may adsorb to suspended solids and sediment in water. p-Xylene is expected to volatilise from water surfaces based on the measured Henry's Law constant. Estimated volatilisation half-lives for a model river and model lake are 3 hours and 4 days, respectively. BCF values of 14.8, 23.4, and 6, measured in goldfish, eels, and clams, respectively, indicate that bioconcentration in aquatic organisms is low. p-Xylene in water with added humic substances was 50% degraded following 3 hours irradiation suggesting that indirect photooxidation in the presence of humic acids may play an important role in the abiotic degradation of p-xylene. Although p-xylene is biodegradable and has been observed to degrade in pond water, there are insufficient data to assess the rate of this process in surface waters. p-Xylene has been observed to degrade in anaerobic and aerobic groundwater in several studies; however, it is known to persist for many years in groundwater, at least at sites where the concentration might have been quite high.

Atmospheric fate:

Most xylenes released to the environment will occur in the atmosphere and volatilisation is the dominant environmental fate process. In the ambient atmosphere, xylenes are expected to exist solely in the vapour phase. Xylenes are degraded in the atmosphere primarily by reaction with photochemically-produced hydroxyl radicals, with an estimated atmospheric lifetime of about 0.5 to 2 days. Xylenes' susceptibility to photochemical oxidation in the troposphere is to the extent that they may contribute to photochemical smog formation.

According to a model of gas/particle partitioning of semivolatile organic compounds in the atmosphere and from its vapour pressure, p-xylene, is expected to exist solely as a vapour in the ambient atmosphere. Vapour-phase p-xylene is degraded in the atmosphere by reaction with photochemically-produced hydroxyl radicals; the half-life for this reaction in air is estimated to be about 16 hours. A half-life of 1.0 hr in summer and 10 hr in winter was measured for the reaction of p-xylene with photochemically-produced hydroxyl radicals. p-Xylene has a moderately high photochemical reactivity under smog conditions, higher than the other xylene isomers, with loss rates varying from 9-42% per hr. The photooxidation of p-xylene results in the production of carbon monoxide, formaldehyde, glyoxal, methylglyoxal, 3-methylbenzylnitrate, m-tolualdehyde, 4-nitro-3-xylene, 5-nitro-3-xylene, 2,6-dimethyl-p-benzoquinone, 2,4-dimethylphenol, 6-nitro-2,4-dimethylphenol, 2,6-

continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 23 of 26

Section 12 - ECOLOGICAL INFORMATION

dimethylphenol, and 4-nitro-2,6-dimethylphenol.

Ecotoxicity:

for xylenes

Fish LC50 (96 h) Pimephales promelas 13.4 mg/l; Oncorhynchus mykiss 8.05 mg/l; Lepomis macrochirus 16.1 mg/l (all flow through values); Pimephales promelas 26.7 (static)

Daphnia EC50 948 h): 3.83 mg/l

Photobacterium phosphoreum EC50 (24 h): 0.0084 mg/l

Gammarus lacustris LC50 (48 h): 0.6 mg/l.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
Epoxy Resin 2165 Part B #160- 309		No data		
isophorone diamine	HIGH	No data	LOW	MED
tris(isopropylphenyl)phosphate		No data		
nonylphenol	HIGH	No data	LOW	LOW
N-aminoethylpiperazine	HIGH	No data	LOW	MED
salicylic acid	LOW	No data	LOW	HIGH
xylene	LOW	LOW	LOW	

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Material may be disposed of by controlled burning in an approved incinerator or buried in an approved landfill.
- Prior to disposal in a landfill the material should be mixed with the other component and reacted to render the material inert.
- Extreme caution should be taken when heating the resin/curing agent mix.
- Recycle containers where possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: CORROSIVE

HAZCHEM: 4W (ADG6)

Land Transport UNDG:

Class or division:	8	Subsidiary risk:	None
UN No.:	1760	UN packing group:	III
Shipping Name:	CORROSIVE LIQUID, N.O.S. (contains isophorone diamine)		

Air Transport IATA:

ICAO/IATA Class:	8	ICAO/IATA Subrisk:	None
UN/ID Number:	1760	Packing Group:	III

continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 24 of 26

Section 14 - TRANSPORTATION INFORMATION

Special provisions: A3
Shipping Name: CORROSIVE LIQUID, N.O.S. *(CONTAINS ISOPHORONE DIAMINE)

Maritime Transport IMDG:

IMDG Class:	8	IMDG Subrisk:	None
UN Number:	1760	Packing Group:	III
EMS Number:	F- A, S- B	Special provisions:	223 274 944
Limited Quantities:	5 L	Marine Pollutant:	Not Determined

Shipping Name: CORROSIVE LIQUID, N.O.S.(contains isophorone diamine)

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE: S5

REGULATIONS

Regulations for ingredients

isophorone diamine (CAS: 2855-13-2) is found on the following regulatory lists;

"Australia Hazardous Substances", "Australia Inventory of Chemical Substances (AICS)", "GESAMP/EHS Composite List of Hazard Profiles - Hazard evaluation of substances transported by ships", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals"

tris(isopropylphenyl)phosphate (CAS: 68937-41-7) is found on the following regulatory lists;

"Australia Inventory of Chemical Substances (AICS)", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals"

nonylphenol (CAS: 25154-52-3, 84852-15-3, 139-84-4, 136-83-4) is found on the following regulatory lists;

"Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "OECD Representative List of High Production Volume (HPV) Chemicals", "OSPAR List of Substances of Possible Concern"

N-aminoethylpiperazine (CAS: 140-31-8) is found on the following regulatory lists;

"Australia Hazardous Substances", "Australia Inventory of Chemical Substances (AICS)", "GESAMP/EHS Composite List of Hazard Profiles - Hazard evaluation of substances transported by ships", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals"

salicylic acid (CAS: 69-72-7) is found on the following regulatory lists;

"Australia Inventory of Chemical Substances (AICS)", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals"

xylene (CAS: 1330-20-7) is found on the following regulatory lists;

"Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals"

No data for Epoxy Resin 2165 Part B #160-309 (CW: 18-3316)

Section 16 - OTHER INFORMATION

Denmark Advisory list for selfclassification of dangerous substances

Substance	CAS	Suggested codes
nonylphenol	25154- 52-3	Xn; R22 R43 N; R50/53

continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 25 of 26

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
nonylphenol	25154- 52- 3, 84852- 15- 3, 139- 84- 4, 136- 83- 4

REPRODUCTIVE HEALTH GUIDELINES

■ Established occupational exposure limits frequently do not take into consideration reproductive end points that are clearly below the thresholds for other toxic effects. Occupational reproductive guidelines (ORGs) have been suggested as an additional standard. These have been established after a literature search for reproductive no-observed-adverse effect-level (NOAEL) and the lowest-observed-adverse-effect-level (LOAEL). In addition the US EPA's procedures for risk assessment for hazard identification and dose-response assessment as applied by NIOSH were used in the creation of such limits. Uncertainty factors (UFs) have also been incorporated.

Ingredient	ORG	UF	Endpoint	CR	Adeq TLV
xylene	1.5 mg/m ³	10	D	NA	-

■ These exposure guidelines have been derived from a screening level of risk assessment and should not be construed as unequivocally safe limits. ORGS represent an 8-hour time-weighted average unless specified otherwise.

CR = Cancer Risk/10000; UF = Uncertainty factor:

TLV believed to be adequate to protect reproductive health:

LOD: Limit of detection

Toxic endpoints have also been identified as:

D = Developmental; R = Reproductive; TC = Transplacental carcinogen

Jankovic J., Drake F.: A Screening Method for Occupational Reproductive

American Industrial Hygiene Association Journal 57: 641-649 (1996).

EXPOSURE STANDARD FOR MIXTURES

■ "Worst Case" computer-aided prediction of spray/ mist or fume/ dust components and concentration:

■ Composite Exposure Standard for Mixture (TWA) :3 mg/m³.

■ Operations which produce a spray/mist or fume/dust, introduce particulates to the breathing zone.

If the breathing zone concentration of ANY of the components listed below is exceeded, "Worst Case" considerations deem the individual to be overexposed.

Component	Breathing Zone ppm	Breathing Zone mg/m ³	Mixture Conc (%)
Component	Breathing zone (ppm)	Breathing zone (mg/m ³)	
Mixture Conc (%)	tris(isopropylphenyl)phosphate	3.0000	
60.0			

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 18-Dec-2008

continued...

EPOXY RESIN 2165 PART B #160-309

Chemwatch Independent Material Safety Data Sheet

Issue Date: 18-Dec-2008

NA317TC

CHEMWATCH 18-3316

Version No:4

CD 2009/3 Page 26 of 26

Section 16 - OTHER INFORMATION

Print Date: 5-Feb-2010

This is the end of the MSDS.