

Eaton 101486

Catalog Number: 101486

Eaton Moeller® series DILM Secondary terminal wire kit, star-delta, DILM80-95



General specifications

Product Name	Catalog Number
Eaton Moeller® series DILM wiring kit	101486
EAN	Product Length/Depth
4015081014064	225 mm
Product Height	Product Width
50 mm	85 mm
Product Weight	Certifications
0.52 kg	UL File No.: E36332
	UL 508
	UL
	CSA
	CE
	CSA File No.: 012528
	IEC/EN 60947-4-1
	UL Category Control No.: NLRV
	CSA Class No.: 2411-03, 3211-04
	CSA-C22.2 No. 14-05

Features Functions

Functions

Main current wiring for star-delta combination

Fitted with:

Star-point bridge

General

Accessory/spare part type

Connecting bridge

Product category

Accessories

Climatic environmental conditions

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

60 °C

Design verification

Equipment heat dissipation, current-dependent P_{vid}

9.6 W

Heat dissipation capacity P_{diss}

0 W

Heat dissipation per pole, current-dependent P_{vid}

3.2 W

Rated operational current for specified heat dissipation (I_n)

130 A

Static heat dissipation, non-current-dependent P_{vs}

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

Catalogs

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[Product Range Catalog Switching and protecting motors](#)

[SmartWire-DT Catalog](#)

Declarations of conformity

[DA-DC-00004781.pdf](#)

[DA-DC-00004818.pdf](#)

[DA-DC-00004774.pdf](#)

Drawings

[eaton-contactors-star-delta-dilm-wiring-kit-3d-drawing.eps](#)

eCAD model

[ETN.101486.edz](#)

Installation instructions

[IL03407045Z](#)

Installation videos

[WIN-WIN with push-in technology](#)

mCAD model

[dilm95_xsl](#)

[dilm95_xsl.stp](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia