

# Leadership in fusible circuit protection

Eaton's Bussmann series  
British Standard fuse links  
for Industrial and Motor  
protection address many  
application needs.

## Features and benefits

- Great choice of rated current, voltage and tags variants; you will find a fuse links to suit your applications
- Standard and Red Spot fuse links and fuse holders available: your applications will be protected by the best circuit protection solutions.
- Comprehensive range of fuse holders to complement our fuse links range will help VBR (Vendor Based Reduction) programs.
- Compliant with BS88 and IEC standards guarantee our fuses can be used in UK and IEC based applications.
- Team of Electrical experts on hand to help find the correct circuit protection solutions for your applications.



**EATON**

*Powering Business Worldwide*

## Low voltage - BS88 Standard fuse links for industrial and standard applications

Catalogue numbers structure	Rated current	Rated voltage	Breaking capacity	Operating class
Offset bolted tags				
NITD, AAO, BAO, CEO, OSD, DEO	2 to 200 A	Up to 550 V a.c. (gG) Up to 500 V a.c. (gM)	80 kA	gG and gM
Centre bolted tags				
AC, BC, AD, BD, CD, DD, ED, EFS, EF, FF, GF, FG, GG, GH	2 to 1250 A	gG: Up to 690 V a.c./400 V d.c. gM: Up to 550 V a.c./250 V d.c.	80 kA	gG and gM
Offset bladed tags				
SSD, XS, NSD, ESD	2 to 125 A	gG: Up to 550 V a.c. gM: Up to 415 V a.c.	80 kA	gG and gM
Special DC range offset/centre bolted tags				
HS07, KS07 to 09	10 to 63 A	gG: 550 V d.c.	40	gG
Offset bolted tags				
H07	2 to 32 A	gG: 690 V a.c.	80	gG
Special tags				
M13, N15, P35, R40, N20, P20, R20, S20	125 to 800 A	gG: 690 V a.c. / 400 V d.c.	80	gG

## Low voltage - BS88 Red Spot fuse links for industrial and standard applications

Catalogue numbers structure	Rated current	Rated voltage	Breaking capacity	Operating class
Offset bolted tags				
NIT, TIA, TIS, TCP, TFP	2 to 200 A	Up to 660-690 V a.c. Up to 460 V d.c.	80 kA	gG and gM
Centre bolted tags				
TB, TBC, TC, TF, TKF, TKM, TMF, TM, TMT, TTM, TLM, TT, TLU, TXU	2 to 1250 A	gG: Up to 690 V a.c./460 V d.c. gM: Up to 690 V a.c./550 V d.c.	80 kA	gG and gM

## Low voltage - BS88 Compatible fuse holders

Fuse holder	Camaster					Red Spot					
Rated current	20 A	32 A Compact	32 A	63 A	100 A	20 A	32 A	63 A	100 A	200 A	400 A
Catalogue numbers	CM20F	CM32FC	CM32F	CM63F	CM100F	RS20	RS32	RS63	RS100	RS200	RS400
Compatible fuse links	NITD	NITD	AA0	BA0	OSD	NITD	AA0	BA0	CEO	AD	EFS
	NIT	NIT	HS07	KS07		NIT	TIA	TIS	TCP	BD	EF
			H07	TIS			H07	KS07		CD	TKM
			TIA				HS07			DD	TM
										TBC	
										TC	
										TF	

Fuse holder	Safeloc		Safeclip				
Rated current	32 A	63 A	20 A	32 A	63 A	100 A	125 A
Catalogue numbers	32NNS	63ENS	SC20	SC32	SC63	SC100	SC125
Fuse links	NSD	ESD	SSD	NSD (gG)	ESD (gG)	OSD	XS

Red spot fuse links / Standard fuse links

**Eaton**  
EMEA Headquarters  
Route de la Longeraie 7  
1110 Morges, Switzerland

**Eaton**  
Melton Road, Burton-on-the-Wolds  
Leicestershire, LE12 5TH  
United Kingdom

© 2017 Eaton  
All Rights Reserved  
PDF only  
PA134003EN  
February 2017

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

