

"KIT FLUSH-MOUNTING POUR ATV T5"

NSYPTDS5

EAN Code: 3606485442488

Main

| Range | PanelSeT | |
|--|--|--|
| Product or component type | Drive flush mounting kit | |
| accessory category | Mounting and fixing accessory | |
| Product specific application | Process and utilities | |
| Range compatibility | Altivar variable speed drive ATV630 Altivar variable speed drive ATV930 PanelSeT SF and SM enclosures Altivar variable speed drive ATV340 | |
| compatibility for Altivar Process 630-930, size: | 5 | |
| Motor power kW | 30 kW 220/240 V 37 kW 220/240 V 45 kW 220/240 V 55 kW 380/480 V 75 kW 380/480 V 90 kW 380/480 V | |
| Mounting location | Mode 1: back of enclosure on mounting plate Mode 2: inside enclosure | |
| Kit composition | 1 x mounting plate with flanges and integrated gasket, steel with anti-corrosive coating. Fixing by screws and nuts 1 x fixing accessories 1 x drilling template 1 x instruction sheet 1 x edge protector profile, plastic. 1 x fan support 1 x cover for fan protection | |

Complementary

| Permanent permissible load | 58.5 kg | |
|----------------------------|---|--|
| Colour | Grey (RAL 7035) | |
| Height | External: 975 mm Cut-out: 920 mm | |
| Width | Cut-out: 380 mm External: 427 mm | |
| Depth | Wall-enclosure separation : 205.5 mm | |
| Product weight | 11.086 kg | |
| Services | Configuration of enclosurepre-drilled back at requested dimensions Factory installation drive flush mounting kit on enclosure | |

Environment

IP degree of protection IP55 conforming to IEC 60529

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|------------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 101.000 cm |
| Package 1 Width | 45.000 cm |
| Package 1 Length | 15.000 cm |
| Package 1 Weight | 11.086 kg |
| Unit Type of Package 2 | PAM |
| Number of Units in Package 2 | 20 |
| Package 2 Height | 166.000 cm |
| Package 2 Width | 100.000 cm |
| Package 2 Length | 120.000 cm |
| Package 2 Weight | 235.000 kg |

Logistical informations

Country of origin F

Contractual warranty

| Coverage | Core product |
|----------|--------------|
| Warranty | 18 months |



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint

Environmental Disclosure

Product Environmental Profile

Use Better

| ⊗ Materials and Substances | |
|--|--|
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | No |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| SCIP Number | Ba0ee14c-eebb-47d8-a070-ade906247bb0 |
| REACh Regulation | REACh Declaration |

Use Again

| ○ Repack and remanufacture | |
|----------------------------|--|
| Circularity Profile | No need of specific recycling operations |
| Take-back | No |