

Angle Grinder LXT®

DGA519

18V • 125 mm • 3 000 – 8 500 min⁻¹

The X-LOCK mechanism allows the installation / removal of X-LOCK discs without the need for a tool.

With X-Lock, one click is all you need. Insert the wheel into the X-Lock bracket and press it into place. To replace the wheel, simply pull the lever and remove wheel. The X-Lock allows you to change wheels quickly and easily - without the need for a key and even when wearing gloves.



LXT **BL** **ADT** **AFT** **BRAKE** **XLOCK**

Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Brushless Motor	✓
No load speed	8500 min ⁻¹
Bore Size (Arbor Diameter)	22,23 mm
Disc Diameter	125 mm
Anti-Restart Function (NVR Switch)	✓
Dead Man's Switch (No Lock-On)	✓
Electronic brake	✓
Vibration Level, Disc Sanding	≤ 2,5 m/s ²
Vibration Uncertainty (K Factor), Disc Sanding	1,5 m/s ²
Vibration Level, Surface Grinding	7,0 m/s ²
Vibration Uncertainty (K Factor), Surface Grinding	1,5 m/s ²
Sound Power Level (L _{WA})	91 dB(A)

User benefits

- Brushless maintenance-free and long-life motor
- Slim body design for a good grip
- Variable speed
- Electronic overload protection protects the user and the device
- Electric brake for maximum productivity and increased operator safety
- Battery protection circuit protects against overloading, over-discharging and over-heating
- 3-stage LED gauge indicates battery charge level / overheating / overload
- Large paddle switch trigger for easy operation

Link to product - www.makitauk.com



Related products

■ Optional AC

158237-4

Grip 36 complete



■ Other

User manual

Parts drawing