



## TRAFFIC FILM REMOVERS

**TRAFFIC FILM REMOVERS** are blends of surfactants, builders and chelating agents, carried in water. Available in heavy, medium or light duty formulations, the products are ideal for use by hand, swab, brush or immersion.

Highly effective as High Pressure Washer Additives, the products can also be used through power washers and other automated equipment.

### APPLICATIONS

Suitable for hot and cold use, the products will easily remove oily soiling and grime from vehicle bodies, chassis and side curtains in a variety of different industries:

- \* Automotive
- \* Transport
- \* Haulage
- \* Engineering
- \* Railways
- \* Local Authorities

Light Duty - Day to day cleaning of cars, light vehicles and equipment.

Medium Duty - General purpose removal of soiling from commercial vehicles, plant and machinery.

Heavy Duty - Removal of heavy soiling from commercial vehicles, plant and machinery.

When cleaning, apply the solution upwards to avoid streaks and always rinse thoroughly with clean water after use.

### TECHNICAL DATA

Appearance	:	Clear, pale yellow liquid
Odour	:	Slightly sour
SG @ 25°C	:	1.10
pH	:	13.5
Solubility	:	Water soluble
Dilution rates	:	20 : 1 by hand, 50 : 1 to 200 : 1 by machine
Compatibility	:	Safe on plastics, rubber, painted surfaces and bodywork
Foaming properties	:	Medium foam
Flammability	:	Non-flammable

Irritancy : Classified as irritant under current EC Regulations

Packaging : 5 litres (4 per carton), 25 litres, 200 litres

### **STORAGE**

The product may be stored at normal ambient temperatures and has a shelf life of not less than 12 months with correct storage.

### **HEALTH AND SAFETY**

Health and Safety sheet available separately.

### **TECHNICAL SERVICE**

Ambersil provides a technical support service and maintains a constant programme of research and development. We are able to assist customers by specific product development to meet particular requirements.

### **MISREPRESENTATION ACT 1967 TRADE DESCRIPTIONS ACT 1968**

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

CRC Industries UK Limited, Wylds Road, Bridgwater, Somerset, TA6 4DD

Tel: +44 (0) 1278 727200  
Fax: +44 (0) 1278 425644

Web: [www.ambersilindustrial.com](http://www.ambersilindustrial.com)  
E-mail: [sales.uk@crcind.com](mailto:sales.uk@crcind.com)