

CABLE END-SLEEVES


DIN 46228, part 4, 0.5 – 50 mm²

















Material: copper

Surface: tin plated

Insulated, free of halide

synthetic material: Polypropylene



Conductor mm ²	Part No.	Colour	Dimensions mm					Tools	1000 pcs ~ kg	pcs
			d ₁	d ₃	l ₁	l ₂	s ₁			
 0.5	469/6	white	1	3.1	12	6	0.15	Chart Page 6.09 – 6.10	0.070	1000
	469/8				14	8	0.070			
	469/10				16	10	0.085			
 0.75	470/6	grey	1.2	3.3	12	6	0.15		0.080	1000
	470/8				14	8	0.080			
	470/10				16	10	0.100			
	470/12				18	12	0.105			
 1	471/6	red	1.4	3.5	12	6	0.15		0.090	1000
	471/8				14	8	0.100			
	471/10				16	10	0.120			
	471/12				18	12	0.125			
 1.5	472/6	black	1.7	4	12	6	0.15	0.105	1000	
	472/8				14	8	0.110			
	472/10				16	10	0.130			
	472/12				18	12	0.150			
	472/18				24	18	0.190			
 2.5	473/8	blue	2.2	4.7	14	8	0.15	0.150	1000	
	473/12				18	12	0.200			
	473/18				24	18	0.250			
 4	474/10	grey	2.8	5.4	17	10	0.2	0.210	1000	
	474/12				20	12	0.250			
	474/18				26	18	0.320			
 6	475/12	yellow	3.5	6.9	20	12	0.2	0.350	100	
	475/18				26	18	0.460			
 10	476/12	red	4.5	8.4	22	12	0.2	0.450	100	
	476/18				28	18	0.650			
 16	477/12	blue	5.8	9.6	24	12	0.2	0.650	100	
	477/18				28	18	0.800			
 25	478/16	yellow	7.3	12	30	16	0.2	1.600	50	
	478/18				32	18	1.700			
	478/22				36	22	2.000			
 35	479/16	red	8.3	13.5	30	16	0.2	1.900	50	
	479/18				32	18	2.100			
	479/25				39	25	2.500			
 50	480/20	blue	10.3	16	36	20	0.3	3.300	50	
	480/25				40	25	3.600			
 70*	481/21	yellow	13.5	17.2	37	21	0.4	4.620	25	
 95*	482/25	red	14.7	19.2	44	25	0.4	6.000	25	
 120*	483/27	blue	16.7	21.4	48	27	0.45	7.850	25	
 150*	484/32	yellow	19.5	25	58	32	0.5	12.330	25	

* Not standardized