

DIN-Signal high current f, 20A screw



Image is for illustration purposes only. Please refer to product description.

Part number	09 03 000 6245
Specification	DIN-Signal high current f, 20A screw
HARTING eCatalogue	https://harting.com/09030006245

Identification

Category	Contacts
Series	DIN 41612
Type of contact	Screw contact
Contacts for	DIN 41612 Type M DIN 41612 Type MH 21+5

Version

Termination method	Screw termination
Termination method	Screw fixing on busbar
Gender	Female contact for female connectors
Manufacturing process	Turned contacts

Technical characteristics

Rated current	≤ 20 A
Insertion force	≤ 10 N
Withdrawal force	≥ 1.6 N
Performance level	1
Mating cycles	≥ 500

Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Noble metal over Ni Mating side
RoHS	compliant with exemption



Pushing Performance
Since 1945

Material properties

RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	ecef7555-f643-4ceb-a337-fc54762297f1
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead

Specifications and approvals

Specifications	DIN 41626
----------------	-----------

Commercial data

Packaging size	100
Net weight	3 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140215313
eCl@ss	27440204 Contact for industrial connectors
ETIM	EC000796
UNSPSC 24.0	39121522



Pushing Performance
Since 1945

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques acc. to IEC 60512-5-2

