



# Solius ecodomo

Extensive heating surface with integrated presence sensor for energy savings



#### **COMFORT**

- Extensive-heat panel with black painted extruded aluminium heating element & digital display
- Extruded aluminium heating element with wide radiating surface area
- Front electric air outlet

#### **SAVINGS**

- Up to 30% energy savings<sup>\*</sup> thanks to integrated presence detector
- Models starting at 500 W for low-energy consumption homes
- Presence /absence detection functions
- Consumption indicator for responsible & informed use of the equipment
- 6-command pilot wire: Comfort, Comfort 1 °C, Comfort - 2 °C, Eco, Frost-free, Off
- Mode switch: Comfort, Eco, Frost-free, Off, Programme

#### **USER-FRIENDLINESS**

- · Control locking device
- ASP (Anti-Staining Process) to reduce staining on wall and on equipment

#### **DESIGN**

- Light indicator for heating
- Colour shade: white (RAL 9016)





<sup>\*</sup> Compared to a mechanical convector

<sup>\*\*</sup> Model types : A : Vertical wall mounted / B : Horizontal wall mounted / C : Vertical Floor standing / D : Plinth





6 Anti fall-down system


- 1 Digital controls
- 2 Over-heating safety device
- 3 Perforated frontal air outlet
- 4 Extruded aluminium heating element




- 1 Comfort mode setting dial
- 2 Mode setting cursor (Shutdown, Frost-free, Programming, Comfort, Eco)
- 3 Heating light
- 4 Function selection dial: Absence, Air, Absence + Air, Off). Function selection dial: Absence, Air, Absence + Air, Off). Absence detection: more savings when the user is absent thanks to automatic temperature reduction. Window open/close detection: switches to Anti-frost mode when the window ins open
- 5 Energy consumption indicator



## INSTALLATION DIMENSIONS (in mm)





### **SOLIUS ECODOMO**

#### TECHNICAL DATA

| TECHNICAL DATA |                 |            |           |     |     |     |            |
|----------------|-----------------|------------|-----------|-----|-----|-----|------------|
| OUTPUT<br>(W)  | DIMENSIONS (mm) |            |           |     |     |     | NET WEIGHT |
|                | Width (W)       | Height (H) | Depth (D) | A   | B1  | B2  | (kg)       |
| 500            | 443             | 451        | 120       | 195 | 256 | 158 | 4.8        |
| 1 000          | 517             | 451        | 120       | 343 | 256 | 158 | 6.2        |
| 1 500          | 813             | 451        | 120       | 565 | 256 | 158 | 7.9        |
| 2 000          | 1 035           | 451        | 120       | 787 | 256 | 158 | 9.8        |

