Statement of Product Conformity

BM Polyco Ltd
Great Cambridge Industrial Estate
Lincoln Road
Enfield
EN1 1SH
Great Britain

Certified to ISO 9002

declare that the new PPE described hereafter



PURA

A flocklined, mediumweight vinyl glove

is in conformity with the provisions of Council Directive 89/686/EEC and where such is the case, with National Standards transposing harmonised standards EN374-1:1994, EN374-2:1994, EN374-3:1994, EN388:1994 and EN420:1994

is identical to the PPE, ref. Pura which is the subject of EC certificate of conformity No 1280 issued by SATRA Services Ltd, Rockingham, Kettering, Northamptonshire, NH16 9JH (Approved Body No 0321)

is subject to the procedure set out in Article 11B of Directive 89/686/EEC under the supervision of the Notified Body, LRQA Ltd, Hiramford, Middlemarch Office Village, Siskin Drive, Coventry, CV3 4FJ (Approved Body No 0088).



BSEN388 Mechanical Hazards



BSEN374 Micro-organism Hazards



BSEN374 Chemical Hazards

Test	Standard	Performance Level
Abrasion	EN388:1994	3
Blade cut	EN388:1994	0
Tear	EN388:1994	0
Puncture	EN388:1994	0
Dexterity	EN420:1994	5

Permeation EN374-3:1994	Performance Level	
Ammonium Hydroxide 10%	6	
Sulphuric acid 80%	6	
Sodium Hydroxide 40%	6	
Propanol	2	
Hydrochloric acid 37%	3	

User Information

Pura is made from PVC and is an excellent alternative for people who are allergic to natural rubber latex proteins of sensitive to the chemical accelerators used in rubber gloves. It is anatomically shaped to ensure comfort and reduce hand fatigue. Its slip resistant pattern ensures good grip in wet and dry conditions.

Important: You are advised to test and inspect the gloves before and after use and periodically during use, punctures will significantly affect the protection provided.

Range Available: Size and codes

	Size	7	8	9	10
Colour					
Blue		474	475	476	477
Green		374	375	376	-
Yellow		274	275	276	-

Length: 31cm **Thickness:** 0.55 (single wall measured at palm)

Glove Care

To get the best service from your gloves ensure that after use all contaminant is removed.

Store in dry conditions away from direct sunlight and heat.

For further information and advice on suitability for protection against specific substances or applications please contact us.