




The Timken Company
4500 Mt Pleasant St. NW
N. Canton, OH 44720
Phone: (234) 262-3000
E-Mail: CustomerCAD@timken.com • Web site: www.timken.com

Timken Part Number 15100 - 15245, Tapered Roller Bearings - TS (Tapered Single) Imperial

This is the most basic and most widely used type of tapered roller bearing. It consists of two main separable parts: the cone (inner ring) assembly and the cup (outer ring). It is typically mounted in opposing pairs on a shaft.



[Specifications](#) | [Dimensions](#) | [Abutment and Fillet Dimensions](#) | [Basic Load Ratings](#) | [Factors](#)

Specifications	
Series	15000
Cone Part Number	15100
Cup Part Number	15245
Design Units	Imperial
Bearing Weight	0.60 lb 0.300 Kg
Cage Type	Stamped Steel

Dimensions	
d - Bore	1.0000 in 25.400 mm
D - Cup Outer Diameter	2.4409 in 61.999 mm

B - Cone Width	0.8125 in 20.638 mm
C - Cup Width	0.5625 in 14.288 mm
T - Bearing Width	0.7500 in 19.050 mm

Abutment and Fillet Dimensions

R - Cone Backface "To Clear" Radius¹	0.14 in 3.560 mm
r - Cup Backface "To Clear" Radius²	0.050 in 1.27 mm
da - Cone Frontface Backing Diameter	1.24 in 31.50 mm
db - Cone Backface Backing Diameter	1.50 in 38.10 mm
Da - Cup Frontface Backing Diameter	2.30 in 58.42 mm
Db - Cup Backface Backing Diameter	2.17 in 55.12 mm
Ab - Cage-Cone Frontface Clearance	0.07 in 1.8 mm
Aa - Cage-Cone Backface Clearance	0.03 in 0.8 mm
a - Effective Center Location³	-0.23 in -5.80 mm

Basic Load Ratings

C90 - Dynamic Radial Rating (90 million revolutions)⁴	3490 lbf 15500 N
C1 - Dynamic Radial Rating (1 million revolutions)⁵	13500 lbf 59900 N
C0 - Static Radial Rating	12100 lbf 53900 N
C_{a90} - Dynamic Thrust Rating (90 million revolutions)⁶	2090 lbf 9310 N

Factors



K - Factor⁷	1.67
e - ISO Factor⁸	0.35
Y - ISO Factor⁹	1.71
G1 - Heat Generation Factor (Roller-Raceway)	14.6
G2 - Heat Generation Factor (Rib-Roller End)	7.58
Cg - Geometry Factor	0.0606

¹ These maximum fillet radii will be cleared by the bearing corners.

² These maximum fillet radii will be cleared by the bearing corners.

³ Negative value indicates effective center inside cone backface.

⁴ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values.


⁵ Based on 1×10^6 revolutions L_{10} life, for the ISO life calculation method.

⁶ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.

⁷ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁸ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁹ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.



IMPERIAL UNITS

ISO Factor - e 0.35
 ISO Factor - Y 1.71
 Bearing Weight 0.6 lb
 Number of Rollers Per Row 15
 Effective Center Location -0.23 inch

TIMKEN®

THE TIMKEN COMPANY
 NORTH CANTON, OHIO USA

15100 - 15245
 TS BEARING ASSEMBLY

K Factor 1.67
 Dynamic Radial Rating - C90 3490 lbf
 Dynamic Thrust Rating - Ca90 2090 lbf
 Static Radial Rating - C0 12100 lbf
 Dynamic Radial Rating - C1 13500 lbf

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY