



Main

Range of product	Zelio Relay
Series name	Interface relay
Control circuit voltage	24 V DC
Contacts type and composition	2 C/O
[I _{th}] conventional enclosed thermal current	8 A at ≤ 40 °C
[U _i] rated insulation voltage	400 V conforming to EN/IEC 60947
Contacts material	Silver alloy (Ag/Ni)
Resistive rated load	8 A 250 V AC 8 A 28 V DC

Complementary

Fixing mode	Plastic compression spring
Status LED	Without
Shape of pin	Flat (PCB type)
Average resistance	1440 Ohm DC at 20 °C +/- 10 %
Rated operational voltage limits	19.2...26.4 V DC
[U _{imp}] rated impulse withstand voltage	4 kV conforming to IEC 61000-4-5
[I _e] rated operational current	4 A NC AC-1/DC-1 conforming to IEC 8 A NO AC-1/DC-1 conforming to IEC
Minimum switching current	5 mA
Maximum switching voltage	300 V DC 400 V AC
Minimum switching voltage	5 V
Maximum switching capacity	224 W DC 2000 VA AC
Minimum switching capacity	300 mW
Operating rate	≤ 10 cyc/mn under load ≤ 1200 cyc/mn no-load
Mechanical durability	≥ 30000000 cycles
Electrical durability	≥ 100000 cycles for resistive load at 8 A 250 V
Operating time	4 ms DC between coil de-energisation and making of the Off-delay contact 9 ms DC between coil energisation and making of the On-delay contact 10 ms AC between coil de-energisation and making of the Off-delay contact 12 ms AC between coil energisation and making of the On-delay contact
Protection category	RT I
Operating position	Any position
Product weight	0.014 kg
Average consumption	AC: 0.75 VA DC: 0.45 W
Drop-out voltage threshold	AC: ≥ 0.15 U _c DC: ≥ 0.1 U _c

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Dielectric strength	1000 V AC between contacts 2500 V AC between poles 5000 V AC between coil and contact
Standards	CSA C22-2 No 14 EN/IEC 61810-1 UL 508
Product certifications	CSA UL
Ambient air temperature for storage	-40...85 °C
Vibration resistance	> 10 gn (f = 10...150 Hz) conforming to EN/IEC 60068-2-6
IP degree of protection	IP40 conforming to EN/IEC 60529
Shock resistance	5 gn on opening conforming to EN/IEC 60068-2-27 10 gn on closing conforming to EN/IEC 60068-2-27
Ambient air temperature for operation	-40...85 °C DC
RoHS EUR conformity date	0401
RoHS EUR status	Compliant