

Eaton 100428

Catalog Number: 100428

Eaton Moeller® series E71 Proximity switch, optical, long range
80cm, 4L, 10-30VDC, PNP, M8



General specifications

Product Name	Catalog Number
Eaton Moeller® series E71 Proximity switch	100428
	EAN
	4015081643127
Product Length/Depth	Product Height
502.31 mm	9.91 mm
Product Width	Product Weight
9.91 mm	0.09 kg

Certifications

CE
CSA-C22.2 No. 14
CSA File No.: UL report applies to both
US and Canada
UL
IEC/EN 60947-5-2
UL 508
Certified by UL for use in Canada
UL Category Control No.: NRKH, NRKH7

UL File No.: E166051

Product specifications

Type

Optical sensors

Electric connection type

Connector M8

Enclosure material

Plastic

Enclosure type

Cuboid

Operating mode

Switching principle: Adjustable bright/dark switching

Explosion safety category for dust

None

Explosion safety category for gas

None

Functions

For combination with reflector

Reflected-light beam

Detection of transparent objects

Short-circuit protection

Protection against polarity reversal

Voltage type

DC

Connection type

Plug-in connection M8 x 1

4-wire

Light type

Polarity free red light

Degree of protection

IP66

NEMA Other

Interface type

Other

LED indicator

Status indication of Switching state: Yellow LED

Status indication of Operating voltage: Green LED

Switch function type

Other

Resources

Brochures

[eaton-sensors-brochure-br053001en-en-us.pdf](#)

Catalogs

[Product Range Catalog Sensors – products, basic information, applications](#)

Drawings

[eaton-proximity-switches-proximity-switch-dimensions-024.eps](#)

[eaton-proximity-switches-e71-proximity-switch-3d-drawing-002.eps](#)

Installation instructions

[IL05305006Z](#)

mCAD model

[DA-CS-90_28292_002](#)

[DA-CD-90_28292_002](#)

Load current

Max. 100 mA (I_e)

Laser protection class

None

Shock resistance

30 g, Mechanical, Shock duration 11 ms

Optical surface material

Plastic

Output current (mA) - max

100 mA

Output current at protected output - max

0 mA

Rated control supply voltage (U_s) at AC, 50 Hz - max

0 V

Rated control supply voltage (U_s) at AC, 50 Hz - min

0 V

Rated control supply voltage (U_s) at AC, 60 Hz - max

0 V

Rated control supply voltage (U_s) at AC, 60 Hz - min

0 V

Rated control supply voltage (U_s) at DC - max

30 V

Rated control supply voltage (U_s) at DC - min

10 V

Rated switching distance (S_n)

800 mm

Reflector distance - min

0 mm

Sensor height

32 mm

Sensor length

20 mm

Switching distance - max

800 mm

Switching voltage of OSSD at state high

30 V

Transmission range of the safety field

0 m

Voltage rating - max

30 V

Safety type (IEC 61496-1)

1

Switching frequency

500 Hz

Sensing mode

Light-/dark switching

Switching output type

PNP

Sensor material

Insulated material

Vibration resistance

According to IEC/EN 60068-2-6

10 - 55 Hz, Amplitude 0.5 mm

Wavelength of the sensor

660 nm

Width sensor

12 mm

Product category

E71 NanoView Series

Response time

1 ms

Ambient operating temperature - max

55 °C

Ambient operating temperature - min

-25 °C

Ambient storage temperature - max

70 °C

Ambient storage temperature - min

-25 °C

Diameter sensor

0 mm

Light dot size

0 mm²

Number of contact energized outputs with signalling function

0

Number of outputs (protected contact energized)

0

Number of outputs (protected semiconductor)

0

Number of outputs (semiconductor with signaling function)

1

Operating temperature - max

55 °C

Operating temperature - min

-25 °C

Adjustment type

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.
All other trademarks are property of their respective owners.



Eaton.com/socialmedia