



**Part Number: 9501NH**

Computer Cable for EIA RS-232 Applications

**Product Description**

24 AWG stranded (7x32) TC conductors, PE insulation, twisted pairs, overall Beldfoil shield (100% coverage), 24 AWG stranded TC drain Wire, LSZH jacket, Flame resistance IEC 60332-3C

**Technical Specifications**

**Product Overview**

Environmental Space:	Indoor - Euroclass Dca
Suitable Applications:	Instrumentation and computer cable; For EIA RS-232 data transmission applications

**Physical Characteristics (Overall)**

**Conductor**

AWG	Stranding	Material	No. of Conductors	No. of Pairs
24	7x32	TC - Tinned Copper	2	1

Conductor Count:	2
Total Number of Pairs:	1
Conductor Size:	24 AWG

**Insulation**

Material	Nominal Diameter	Diameter +/- Tolerance
Polyethylene	1.12 mm	0.05 mm

**Color Chart**

Number	Color
Pair 1	Black & Red

**Outer Shield Material**

Type	Material	Material Trade Name	Thickness of Foil	Drainwire Material	Drainwire AWG
Tape	Aluminum/Polyester	Beldfoil®	9 / 12 µm	TC - Tinned Copper	AWG24/7

**Outer Jacket Material**

Material	Color	Nominal Diameter	Nominal Wall Thickness
LSZH / FRNC (UV stabilised)	Chrome (RAL 7037)	4.15 mm	0.9 mm

**Electrical Characteristics**

**Conductor DCR**

Nominal Conductor DCR	Nominal Outer Shield DCR
78.7 Ohm/km	59.1 Ohm/km

**Capacitance**

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
131.2 pF/m	242.8 pF/m

**Impedance**

Frequency [MHz]	Nominal Characteristic Impedance
-----------------	----------------------------------

N/A	75 Ohm
-----	--------

#### Current

Element	Max. Recommended Current [A]
Conductor	2.2 A

#### Voltage

Voltage Rating [V]
300 V

#### Temperature Range

Installation Temp Range:	-15°C To +80°C
Storage Temp Range:	-45°C To +80°C
Operating Temp Range (Flexible Install):	-15°C To +80°C
Operating Temp Range (Fixed Install):	-45°C To +80°C

#### Mechanical Characteristics

Oil Resistance:	IEC 60811-404
Max Recommended Pulling Tension:	50 N
Min Bend Radius During Installation:	41.5 mm

#### Standards

CPR Euroclass:	Dca-s1,d1,a1
CENELEC Compliance:	EN 50290-2-27

#### Applicable Environmental and Other Programs

EU RoHS Compliance Date (yyyy-mm-dd):	2005-01-01
---------------------------------------	------------

#### Flammability, LSOH, Toxicity Testing

ISO/IEC Flammability:	IEC 60332-3-24
Amount of Halogen acc. to IEC 60754-1 & EN50267-1:	Zero

#### Part Number

#### Variants

Item #	Color
9501NH.001000	Chrome
9501NH.00152	Chrome
9501NH.00305	Chrome
9501NH.00500	Chrome

#### History

Revision Number:	7
------------------	---

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.