

Eaton 127672

Catalog Number: 127672

Eaton S811 Soft starters, opt.690 V MOV (T frame)

General specifications



Product Name	Catalog Number
Eaton S811 Accessory Transient voltage surge suppression	127672

EAN
4015081250806

Product Length/Depth	Product Height
190.5 mm	107.95 mm

Product Width	Product Weight
107.95 mm	0.215 kg

Certifications

UL 508

CSA-C22.2 No. 14

CSA File No.: LR 353

UL File No.: E202571

General

Accessory/spare part type

Other

Conditions of acceptability

UL and CSA Investigated Component, (UL/CSA)

Climatic environmental conditions

Ambient operating temperature - min

-30 °C

Ambient operating temperature - max

50 °C

Main conducting paths

Voltage rating - max

1000 V

Design verification

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

Brochures

[eaton-softstarter-s811-ds7-brochure-br039001en-en-us.pdf](#)

Catalogs

[Product Range Catalog Drives Engineering](#)