

Torque screwdriver - TSD-M 3NM - 1212225

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 1.2 - 3 Nm

Why buy this product

- ✓ High-precision, finely adjustable torque screwdrivers according to EN ISO 6789
- ✓ TSD-M ... torque screwdrivers are adjustable from 0.3 - 6.0 Nm
- ✓ Torque screwdrivers with hexagonal fast connection holder



Key commercial data

Packing unit	1 pc
GTIN	 4 046356 455565
Weight per Piece (excluding packing)	179.0 g
Custom tariff number	82054000
Country of origin	Czech Republic

Technical data

Dimensions

Length (b)	150 mm
Height	36.5 mm
Width (a)	36.5 mm

General

Color	black
-------	-------

Classifications

eCl@ss

eCl@ss 4.0	21040401
eCl@ss 4.1	21040401
eCl@ss 5.0	21040401

Torque screwdriver - TSD-M 3NM - 1212225

Classifications

eCl@ss

eCl@ss 5.1	21040401
eCl@ss 6.0	21040401
eCl@ss 7.0	21040409

ETIM

ETIM 2.0	EC000158
ETIM 3.0	EC000158
ETIM 4.0	EC002132
ETIM 5.0	EC002132

UNSPSC

UNSPSC 6.01	27111701
UNSPSC 7.0901	27111701
UNSPSC 11	27111701
UNSPSC 12.01	27111701
UNSPSC 13.2	27111701

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Approval details

EAC

Accessories

Accessories

Adapter

Torque screwdriver - TSD-M 3NM - 1212225

Accessories

Screw insert - BF 6,3 - 1209936



Adapter for 1/4" bit holder

Screwdriver tools

Screw insert - BHN 5,5 - 1209965



Nut, hexagonal, 5.5 mm

Screw insert - BHN 8 - 1209978



Nut, hexagonal, 8 mm

Screw insert - BHN 10 - 1209981



Socket wrench insert, magnetic, hexagonal, 10 mm wrench size, 1/4" drive, suitable for holders according to DIN 3126-F 6,3/ISO 1173

Screw insert - BHN 13 - 1209994



Nut, hexagonal, 13 mm

Torque screwdriver - TSD-M 3NM - 1212225

Accessories

Adapter insert - TSD-M SAC-BIT ADAPTER - 1212600



Adapter bit for TSD-M...torque tools, E6.3-1/4" drive with 4 mm hexagon to accommodate SAC bits

Phoenix Contact 2015 © - all rights reserved
<http://www.phoenixcontact.com>