DATASHEET - FAZ6-C10/1



Miniature circuit breaker (MCB), 10 A, 1p, characteristic: C, 6 kA

Part no. FAZ6-C10/1 Catalog No. 239035 Alternate Catalog FAZ6-C10/1



Similar to illustration

Design verification as per IEC/EN 61439

| Design vernication as per icc/civ 01439 | | | |
|---|------------------|---|--|
| Technical data for design verification | | | |
| Rated operational current for specified heat dissipation | In | Α | 10 |
| Equipment heat dissipation, current-dependent | P _{vid} | W | 1.5 |
| EC/EN 61439 design verification | | | |
| 10.2 Strength of materials and parts | | | |
| 10.2.2 Corrosion resistance | | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | | Meets the product standard's requirements. |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects $$ | | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | | Meets the product standard's requirements. |
| 10.2.5 Lifting | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | | Meets the product standard's requirements. |
| 10.3 Degree of protection of ASSEMBLIES | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | | Is the panel builder's responsibility. |
| 10.9 Insulation properties | | | |
| 10.9.2 Power-frequency electric strength | | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | | Is the panel builder's responsibility. The specifications for the switch gear must be observed. |
| 10.12 Electromagnetic compatibility | | | Is the panel builder's responsibility. The specifications for the switch gear must lobserved. |

Technical data ETIM 8.0

| Toomitour data ETHN 5.5 | | | | |
|---|-----|----------|--|--|
| Circuit breakers and fuses (EG000020) / Miniature circuit breaker (MCB) (EC000042) | | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Miniature circuit breaker system (MCB) / Miniature circuit breaker (MCB) (ecl@ss10.0.1-27-14-19-01 [AAB905014]) | | | | |
| Built-in depth | mm | 70.5 | | |
| Release characteristic | | С | | |
| Number of poles (total) | | 1 | | |
| Number of protected poles | | 1 | | |
| Rated current | Α | 10 | | |
| Rated voltage | V | 230 | | |
| Rated insulation voltage Ui | V | 440 | | |
| Rated impulse withstand voltage Uimp | kV | 4 | | |
| Rated short-circuit breaking capacity Icn according to EN 60898 at 230 V | kA | 6 | | |
| Voltage type | | AC | | |
| Rated short-circuit breaking capacity Icn according to EN 60898 at 400 V | kA | 6 | | |
| Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 230 V | kA | 10 | | |
| Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 400 V | kA | 10 | | |
| Frequency | Hz | 50 - 60 | | |
| Current limiting class | | 3 | | |
| Flush-mounted installation | | No | | |
| Concurrently switching neutral conductor | | No | | |
| Over voltage category | | 3 | | |
| Pollution degree | | 2 | | |
| Additional equipment possible | | Yes | | |
| Width in number of modular spacings | | 1 | | |
| Degree of protection (IP) | | IP20 | | |
| Ambient temperature during operating | °C | -25 - 75 | | |
| Connectable conductor cross section multi-wired | mm² | 1 - 25 | | |
| Connectable conductor cross section solid-core | mm² | 1 - 25 | | |
| Explosion-proof | | No | | |
| | | | | |

Additional product information (links)

| Temperature dependency, derating | https://www.eaton.com/content/dam/eaton/technicaldocumentation/technical-data-tables/Derating table |
|----------------------------------|---|
| | FAZ6.pdf |