

Product data sheet

Specifications



Earth leads section 25mm², length 220mm, eyelet hole 8,3mm.
Packaging unit: 10.

NSYEL2225D8

Main

Range	PanelSeT
Anwendung	Multi-purpose
Product or component type	Earthing wire
Device composition	1 lead
Quantity per set	Set of 10

Complementary

Material	PVC (polyvinyl chloride) green and yellow for sheath Brass and copper alloy for terminal
Fixing mode	Nut and washer - on earth connection location
Length	220 mm
Nominal cross section	25 mm ²
Diameter	8.3 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.600 cm
Package 1 Width	3.000 cm
Package 1 Length	22.000 cm
Package 1 Weight	70.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	3.000 cm
Package 2 Width	6.000 cm
Package 2 Length	25.000 cm
Package 2 Weight	736.000 g
Unit Type of Package 3	P12
Number of Units in Package 3	1600
Package 3 Height	52.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 3 Weight	131.000 kg
------------------	------------

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

EU RoHS Directive

[Compliant](#)

REACH Regulation

[Free of Substances of Very High Concern above the threshold](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

End of life manual availability

No need of specific recycling operations

Take-back

No