

## FEATURES

- **2:1 shrink ratio:** Provides a tight fit over irregular shapes and connectors, ensuring secure insulation.
- **Halogen-free:** Reduces toxic emissions in case of fire, enhancing safety.
- **Polyolefin material:** Offers excellent resistance to chemicals and abrasion, increasing durability.
- **25 mm shrunk diameter:** Suitable for a wide range of cable sizes, offering versatility.
- **1 m sleeve length:** Allows for coverage of longer cable sections, reducing the need for multiple pieces.
- **REACH and RoHS compliant:** Meets key environmental and safety standards, ensuring regulatory compliance.

## RS PRO 2:1 Heat Shrink Tubing, 25 mm Shrunk Diameter

RS Stock No: 671-575



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description

This RS PRO heat shrink tubing is designed for insulating and protecting electrical connections. With a shrink ratio of 2:1, it efficiently reduces in size to provide a snug fit over cables and connectors, ensuring enhanced protection against environmental factors. The tubing is halogen-free, making it suitable for applications where low toxicity is essential.

## General Specifications

Colour	Black
Flame Retardant	No
Halogen Free	Yes
Product Type	Heat Shrink Tubing
Shrink Ratio	2:1

## Mechanical Specifications

Material	Polyolefin
Shrunk Diameter	25 mm
Sleeve Diameter	95 mm
Sleeve Length	1 m

## Approvals

Standards/Approvals	REACH, RoHS
---------------------	-------------