

Control Knobs for Panel Potentiometers



FEATURES







- Large knob diameter range
- Designed to provide good grip for bare hands or gloves
- With lateral screw fixing
- Plastic or aluminum material
- Custom metallic knob on request (shape, marking, color, and hole for shaft diameter)
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

RoHS
COMPLIANT

LINKS TO ADDITIONAL RESOURCES





Control knobs suited for panel potentiometers, encoders and rotary switches. Whether the user wears gloves or operates with bare hands, the knob's haptic structure and pleasant grip surface reliably apply the necessary torque to the potentiometer shaft across all application situations.



CONTROL KNOB INDEX		
	PLASTIC CONTROL KNOBS	METALLIC CONTROL KNOBS
ROUND RANGE	 Page 2	 Page 5
POINTER RANGE	 Page 4	 Page 6
SKIRTED RANGE	 Page 3	 Page 7




For "Quick Search / Available Series" table see [page 12](#)

PLASTIC CONTROL KNOBS

ROUND RANGE

SERIES  PR1417NLS	
SPECIFICATION <ul style="list-style-type: none"> Material: plastic (ABS) Indicator: white line on side Product color: black With lateral screw fixing 	
 <p>SECTION A-A</p> <p>Brass insert</p>	
PART NUMBER	SHAFT DIAM. "F"
ACCKPR1417NLS18	1/8" (3.175)
ACCKPR1417NLS14	1/4" (6.35)
ACCKPR1417NLS3	3
ACCKPR1417NLS6	6

SERIES  IR1612NLP	
SPECIFICATION <ul style="list-style-type: none"> Material: plastic (ABS) Indicator: white line on side and top Product color: black With lateral screw fixing 	
 <p>SECTION A-A</p> <p>Brass insert</p>	
PART NUMBER	SHAFT DIAM. "F"
ACCKIR1612NLP18	1/8" (3.175)
ACCKIR1612NLP14	1/4" (6.35)
ACCKIR1612NLP3	3
ACCKIR1612NLP6	6



SERIES <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>PR1817NLT</p> </div> <div style="text-align: center;">  <p>PR1417NLT</p> </div> </div>						
SPECIFICATION <ul style="list-style-type: none"> Material: plastic (ABS) Product color: black Indicator: white line on top With lateral screw fixing 						
 <p style="text-align: center;">SECTION A-A</p>						
PART NUMBER	DIMENSIONS in millimeters					
	SHAFT DIAM. "F"	A	B	C	D	E
ACCKPR1817NLT18	1/8" (3.175)	18.4	17.4	16.2	2.4	14.7
ACCKPR1817NLT14	1/4" (6.35)					
ACCKPR1817NLT3	3					
ACCKPR1817NLT6	6					
ACCKPR1417T18	1/8" (3.175)	13.8	16.6	14.6	0	9.5
ACCKPR1417NLT14	1/4" (6.35)					
ACCKPR1417T3	3					
ACCKPR1417NLT6	6					

PLASTIC CONTROL KNOBS

SKIRTED RANGE

SERIES <div style="display: flex; justify-content: space-around; align-items: center;"> </div> <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;"> IS2716NLD </div> <div style="text-align: center;"> IS2012NLD </div> </div>						
SPECIFICATION <ul style="list-style-type: none"> Material: plastic (ABS) with aluminum top inlay Product color: black Indicator: white line on side, top, and skirt With lateral screw fixing 						
PART NUMBER	DIMENSIONS in millimeters					
	SHAFT DIAM. "F"	A	B	C	D	E
ACCKIS2716NLD18	1/8" (3.175)	27	16	13.8	3.8	21.7
ACCKIS2716NLD14	1/4" (6.35)					
ACCKIS2716NLD6	6					
ACCKIS2012NLD18	1/8" (3.175)	20	12	10	1.8	13.8
ACCKIS2012NLD14	1/4" (6.35)					
ACCKIS2012NLD3	3					
ACCKIS2012NLD6	6					

SERIES <div style="display: flex; justify-content: space-around; align-items: center;"> </div> <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;"> PS2015NLR </div> <div style="text-align: center;"> PS1412NLR </div> </div>							
SPECIFICATION <ul style="list-style-type: none"> Material: plastic (ABS) Product color: black Indicator: white line on top, and skirt With lateral screw fixing 							
PART NUMBER	DIMENSIONS in millimeters						
	SHAFT DIAM. "F"	A	B	C	D	E	I
ACCKPS2015NLR18	1/8" (3.175)	20	17.3	25.3	1.5	15	12.7
ACCKPS2015NLR14	1/4" (6.35)						
ACCKPS2015NLR3	3						
ACCKPS2015NLR6	6						
ACCKPS1412NLR18	1/8" (3.175)	14.3	13.8	19	2.5	12.3	10
ACCKPS1412NLR14	1/4" (6.35)						
ACCKPS1412NLR3	3						
ACCKPS1412NLR6	6						

SERIES  PS1715NLT	
SPECIFICATION <ul style="list-style-type: none"> Material: plastic (ABS) Product color: black Indicator: white line on top and dot on skirt With lateral screw fixing 	
	
PART NUMBER	SHAFT DIAM. "F"
ACCKPS1715NLT18	1/8" (3.175)
ACCKPS1715NLT14	1/4" (6.35)
ACCKPS1715NLT3	3
ACCKPS1715NLT6	6

SERIES

PS1515NDT



SPECIFICATION

- Material: plastic (ABS)
- Product color: black
- Indicator: white dot on top
- With lateral screw fixing




PART NUMBER	DIMENSIONS in millimeters					
	SHAFT DIAM. "F"	A	B	C	D	E
ACCKPS1515NDT18	1/8" (3.175)	15	15	13.2	7.5	11.5
ACCKPS1515NDT14	1/4" (6.35)					
ACCKPS1515NDT3	3					
ACCKPS1515NDT6	6					



PLASTIC CONTROL KNOBS

POINTER RANGE

SERIES  PP1915NLP	
SPECIFICATION <ul style="list-style-type: none"> Material: plastic (ABS) Product color: black Indicator: white line on top and side With lateral screw fixing 	
 <p>Technical drawing showing dimensions and section A-A. Dimensions include: 14.5, 11, 4.5, 1.8, 8.2, 18.1, 15, 19, and F. A threaded metal insert is indicated.</p>	
PART NUMBER	SHAFT DIAM. "F"
ACCKPP1915NLP18	1/8" (3.175)
ACCKPP1915NLP14	1/4" (6.35)
ACCKPP1915NLP3	3
ACCKPP1915NLP6	6

METALLIC CONTROL KNOBS
ROUND RANGE


SERIES <div style="display: flex; justify-content: space-around; align-items: center;">   </div> <div style="display: flex; justify-content: space-around; align-items: center;"> MR1316NLT MR1916NLT </div>				
SPECIFICATION <ul style="list-style-type: none"> Material: aluminum Product color: black Indicator: white line on top With lateral screw fixing 				
				
PART NUMBER	DIMENSIONS in millimeters			
	SHAFT DIAM. "F"	A	B	C
ACCKMR1316NLT18	1/8" (3.175)	12.8	15.8	9.5
ACCKMR1316NLT14	1/4" (6.35)			
ACCKMR1316NLT3	3			
ACCKMR1316NLT6	6			
ACCKMR1916NLT18	1/8" (3.175)	19	15.8	15
ACCKMR1916NLT14	1/4" (6.35)			
ACCKMR1916NLT3	3			
ACCKMR1916NLT6	6			

SERIES <div style="text-align: center;">  </div> MR1920NLT	
SPECIFICATION <ul style="list-style-type: none"> Material: aluminum Product color: black Indicator: white line on top With lateral screw fixing 	
	
PART NUMBER	SHAFT DIAM. "F"
ACCKMR1920NLT18	1/8" (3.175)
ACCKMR1920NLT14	1/4" (6.35)
ACCKMR1920NLT3	3
ACCKMR1920NLT6	6

SERIES

SPECIFICATION

- Material: aluminum
- Indicator: white line on top
- Product color: black
- With lateral screw fixing



PART NUMBER	DIMENSIONS in millimeters						
	SHAFT DIAM. "F"	A	B	C	D	E	G
ACCKMR1617NLT18	1/8" (3.175)	15.5	16.5	13.5	14.5	8.4	4.5
ACCKMR1617NLT14	1/4" (6.35)						
ACCKMR1617NLT3	3						
ACCKMR1617NLT6	6						
ACCKMR2020NLT18	1/8" (3.175)	20	19.5	17.5	15	9.1	5.5
ACCKMR2020NLT14	1/4" (6.35)						
ACCKMR2020NLT3	3						
ACCKMR2020NLT6	6						
ACCKMR2219NLT18	1/8" (3.175)	22	19	19.6	13.6	8.6	4
ACCKMR2219NLT14	1/4" (6.35)						
ACCKMR2219NLT3	3						
ACCKMR2219NLT6	6						
ACCKMR3022NLT14	1/4" (6.35)	29.7	22	28	11.6	8	4.2
ACCKMR3022NLT6	6						





METALLIC CONTROL KNOBS



POINTER RANGE



SERIES							
<div>MP1325NLP</div> <div>MP1627NLP</div> <div>MP1925NLP</div>							
SPECIFICATION							
<ul style="list-style-type: none"> Material: aluminum Product color: black Indicator: white line on top and side With lateral screw fixing 							
PART NUMBER	DIMENSIONS in millimeters						
	SHAFT DIAM. "F"	A	B	C	E	G	H
ACCKMP1325NLP18	1/8" (3.175)	12.7	25.4	13	9.5	4.5	7.5
ACCKMP1325NLP14	1/4" (6.35)						
ACCKMP1325NLP3	3						
ACCKMP1325NLP6	6						
ACCKMP1627NLP18	1/8" (3.175)	16	26.7	16.3	14.1	5	10.5
ACCKMP1627NLP14	1/4" (6.35)						
ACCKMP1627NLP3	3						
ACCKMP1627NLP6	6						
ACCKMP1925NLP18	1/8" (3.175)	19	25.4	13	15	4.5	7.5
ACCKMP1925NLP14	1/4" (6.35)						
ACCKMP1925NLP3	3						
ACCKMP1925NLP6	6						

SERIES						
<div>MP1316NLS</div> <div>MP1916NLS</div> <div>MP2416NLS</div>						
SPECIFICATION						
<ul style="list-style-type: none"> Material: aluminum Product color: black Indicator: white line on side With lateral screw fixing 						
PART NUMBER	DIMENSIONS in millimeters					
	SHAFT DIAM. "F"	A	B	C	D	E
ACCKMP1316NLS18	1/8" (3.175)	12.7	11.3	6.4	9.5	9
ACCKMP1316NLS14	1/4" (6.35)					
ACCKMP1316NLS3	3					
ACCKMP1316NLS6	6					
ACCKMP1916NLS18	1/8" (3.175)	19	17.6	6.4	15	10
ACCKMP1916NLS14	1/4" (6.35)					
ACCKMP1916NLS3	3					
ACCKMP1916NLS6	6					
ACCKMP2416NLS18	1/8" (3.175)	23.8	22.4	3.2	17.6	9.5
ACCKMP2416NLS14	1/4" (6.35)					
ACCKMP2416NLS6	6					


METALLIC CONTROL KNOBS
SKIRTED RANGE




SERIES  MS1316NLD	
SPECIFICATION <ul style="list-style-type: none"> Material: aluminum Product color: black Indicator: white line on side and skirt With lateral screw fixing 	
	
PART NUMBER	DIMENSIONS in millimeters SHAFT DIAM. "F"
ACCKMS1316NLD18	1/8" (3.175)
ACCKMS1316NLD14	1/4" (6.35)
ACCKMS1316NLD3	3
ACCKMS1316NLD6	6

SERIES  MS1916NAS	
SPECIFICATION <ul style="list-style-type: none"> Material: aluminum Product color: black Indicator: arrow on skirt With lateral screw fixing 	
	
PART NUMBER	DIMENSIONS in millimeters SHAFT DIAM. "F"
ACCKMS1916NAS18	1/8" (3.175)
ACCKMS1916NAS14	1/4" (6.35)
ACCKMS1916NAS3	3
ACCKMS1916NAS6	6












SERIES  MS1316NLK	
SPECIFICATION <ul style="list-style-type: none"> Material: aluminum Product color: black Indicator: white line on side and top With lateral screw fixing 	
	
PART NUMBER	SHAFT DIAM. "F"
ACCKMS1316NLK18	1/8" (3.175)
ACCKMS1316NLK14	1/4" (6.35)
ACCKMS1316NLK3	3
ACCKMS1316NLK6	6








METALLIC CONTROL KNOBS

SKIRTED RANGE

SERIES <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>MS1316NGJ</p> </div> <div style="text-align: center;">  <p>MS1916NGJ</p> </div> </div>				
SPECIFICATION <ul style="list-style-type: none"> Material: aluminum Product color: black Indicator: graduation to 10 With lateral screw fixing 				
				
PART NUMBER	DIMENSIONS in millimeters			
	SHAFT DIAM. "F"	A	B	C
ACCKMS1316NGJ18	1/8" (3.175)	12.7	17.5	9.5
ACCKMS1316NGJ14	1/4" (6.35)			
ACCKMS1316NGJ3	3			
ACCKMS1316NGJ6	6			
ACCKMS1916NGJ18	1/8" (3.175)	19.1	25.4	15
ACCKMS1916NGJ14	1/4" (6.35)			
ACCKMS1916NGJ3	3			
ACCKMS1916NGJ6	6			

QUICK SEARCH / AVAILABLE SERIES											
SERIES	SHAFT DIAMETER				DIAMETER (mm)	HEIGHT (mm)	IMAGE	MATERIAL	RANGE	COLOR	INDICATOR
	3 mm	1/4" (6.35 mm)	1/8" (3.175 mm)	6 mm							
MS1316NLD	✓	✓	✓	✓	12.7	16		Aluminum	Skirted	Black	Line on side and skirt
MP1316NLS	✓	✓	✓	✓	12.7	15.9		Aluminum	Pointer	Black	Line on side
MS1316NLK	✓	✓	✓	✓	12.7	15.9		Aluminum	Skirted	Black	Line on skirt
MS1316NGJ	✓	✓	✓	✓	12.7	15.9		Aluminum	Skirted	Black	Graduation to 10
MP1325NLP	✓	✓	✓	✓	12.7	25.4		Aluminum	Pointer	Black	Line on top and side
MR1316NLT	✓	✓	✓	✓	12.8	15.8		Aluminum	Round	Black	Line on top
PR1417NLS	✓	✓	✓	✓	13.5	17.3		ABS	Round	Black	Line on side
PR1417NLT		✓	✓	✓	13.8	16.6		ABS	Round	Black	Line on top
PS1412NLR	✓	✓	✓	✓	14.3	12.3		ABS	Skirted	Black	Line on top and skirt
PS1515NDT	✓	✓	✓	✓	15	15		ABS	Skirted	Black	Dot on top
MR1617NLT	✓	✓	✓	✓	15.5	16.5		Aluminum	Round	Black	Line on top

QUICK SEARCH / AVAILABLE SERIES											
SERIES	SHAFT DIAMETER				DIAMETER (mm)	HEIGHT (mm)	IMAGE	MATERIAL	RANGE	COLOR	INDICATOR
	3 mm	1/4" (6.35 mm)	1/8" (3.175 mm)	6 mm							
IR1612NLP	✓	✓	✓	✓	16	11.8		ABS	Round	Black	Line on top and side
MP1627NLP	✓	✓	✓	✓	16	26.7		Aluminum	Pointer	Black	Line on top and side
PS1715NLT	✓	✓	✓	✓	16.6	15		ABS	Skirted	Black	Line on top
PR1817NLT	✓	✓	✓	✓	18.4	17.4		ABS	Round	Black	Line on top
PP1915NLP	✓	✓	✓	✓	19	14.5		ABS	Pointer	Black	Line on top and side
MR1916NLT	✓	✓	✓	✓	19	15.8		Aluminum	Round	Black	Line on top
MP1916NLS	✓	✓	✓	✓	19	15.9		Aluminum	Pointer	Black	Line on side
MR1920NLT	✓	✓	✓	✓	19	20		Aluminum	Round	Black	Line on top
MP1925NLP	✓	✓	✓	✓	19	25.4		Aluminum	Pointer	Black	Line on top and side
MR1916NGJ	✓	✓	✓	✓	19.1	15.9		Aluminum	Round	Black	Graduation to 10
MS1916NAS	✓	✓	✓	✓	19.1	15.9		Aluminum	Skirted	Black	Arrow on skirt

QUICK SEARCH / AVAILABLE SERIES											
SERIES	SHAFT DIAMETER				DIAMETER (mm)	HEIGHT (mm)	IMAGE	MATERIAL	RANGE	COLOR	INDICATOR
	3 mm	1/4" (6.35 mm)	1/8" (3.175 mm)	6 mm							
IS2012NLD	✓	✓	✓	✓	20	12		ABS	Skirted	Black	Line on side and skirt
PS2015NLR	✓	✓	✓	✓	20	15		ABS	Skirted	Black	Line on top and skirt
MR2020NLT	✓	✓	✓	✓	20	19.5		Aluminum	Round	Black	Line on top
MR2219NLT	✓	✓	✓	✓	22	19		Aluminum	Round	Black	Line on top
MP2416NLS		✓	✓	✓	23.8	15.9		Aluminum	Pointer	Black	Line on side
IS2716NLD		✓	✓	✓	27	16		ABS	Skirted	Black	Line on side and skirt
MR3022NLT		✓		✓	29.7	22		Aluminum	Round	Black	Line on top

MECHANICAL SPECIFICATIONS	
Locking system	Lateral screw fixing
Knob hole shape for the shaft	Round
Plastic knob material	ABS
Metallic knob material	Aluminum

Notes

- For control knob customization need, knob shape, marking, color, and hole of the shaft diameter can be customized on metallic versions to meet customer requirements. For plastic knobs, only the markings and knob color can be customized to meet customer requirements.
- For knobs compatibilities with panel potentiometers portfolio: refer to application note "Control Knobs" www.vishay.com/doc?51104
- Nothing stated herein shall be construed as a guarantee of quality or durability



ORDERING INFORMATION (part number)																	
A	C	C	K	P	R	1	9	1	4	N	L	T	6				
MODEL	MATERIAL		KNOB RANGE		KNOB DIAMETER		KNOB HEIGHT		COLOR		INDICATOR		SHAFT DIAMETER		SPECIAL NUMBER		
ACCK	P = plastic M = metallic I = plastic with aluminum insert (on request)		R = round P = pointer S = skirted		From 10 mm to 35 mm Unit: mm		From 12 mm to 27 mm Unit: mm		N = black On request: W = white G = grey B = blue R = red Y = yellow N = green S = silver		LT = line on top LS = line on side LP = line on top and side LR = line on top and skirt LK = line on skirt LD = line on side and skirt DT = dot on top DS = dot on skirt AS = arrow on skirt AT = arrow on top GJ = graduation to 10		3 = 3 mm 18 = 3.17 mm (1/8") 6 = 6 mm 14 = 6.35 mm (1/4") On request: 4 = 4 mm		(If applicable) Given by Vishay for custom design		
																SERIES	

PART NUMBER DESCRIPTION (for information only)							
ACCK	P	R	19	14	N	LT	14
MODEL	MATERIAL	KNOB RANGE	KNOB DIAMETER	KNOB HEIGHT	COLOR	INDICATOR	SHAFT DIAMETER
SERIES							

RELATED DOCUMENTS	
APPLICATION NOTES	
Control Knobs	www.vishay.com/doc?51104
Potentiometers and Trimmers	www.vishay.com/doc?51001
Guidelines for Vishay Sfernice Resistive and Inductive Components	www.vishay.com/doc?52029
OTHER	
Link to Panel Potentiometers Portfolio	www.vishay.com/en/potentiometers/



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.