

VS-OE-OE-94A/300,0 - Data cable



1403664

<https://www.phoenixcontact.com/in/products/1403664>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



By the meter, Data cable, Ethernet CAT5 (1 Gbps), shielded, PUR halogen-free, water blue RAL 5021, 8-wire (4x2xAWG24/1, SF/UTP), color single wire: white/blue-blue, white/orange-orange, white/green-green, white/brown-brown, cable length: 300 m

Commercial data

Item number	1403664
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	BF1
Product key	AF1LFA
GTIN	4046356662857
Weight per piece (including packing)	20,388.1 g
Weight per piece (excluding packing)	20,388.1 g
Customs tariff number	85444210
Country of origin	DE

VS-OE-OE-94A/300,0 - Data cable

1403664

<https://www.phoenixcontact.com/in/products/1403664>



Technical data

Product properties

Product type	Data cable by the meter
Sensor type	Ethernet
Number of positions	8
Shielded	yes

Electrical properties

Nominal voltage U_N	30 V AC
	30 V DC
Transmission medium	Copper


Interfaces

Bus system	Ethernet
Signal type/category	Ethernet CAT5 (IEC 11801), 1 Gbps

Cable/line

Cable length	300 m
--------------	-------

Ethernet [94A]

Dimensional drawing	
UL AWM Style	20549 (80°C/300 V)
Number of positions	8
Shielded	yes
Cable type	Ethernet [94A]
Conductor structure	4x2xAWG24/1, SF/UTP
Signal runtime	5.7 ns/m
Signal speed	0.6 c
Conductor structure signal line	1x 0.50 mm
AWG signal line	24
Conductor cross section	4x 2x 0.25 mm ²
Wire diameter incl. insulation	1.1 mm ±0.05 mm
External cable diameter	6.40 mm ±0.2 mm
Outer sheath, material	PUR
External sheath, color	water blue RAL 5021
Conductor material	Bare Cu wire

VS-OE-OE-94A/300,0 - Data cable



1403664

<https://www.phoenixcontact.com/in/products/1403664>

Material wire insulation	PE
Single wire, color	white/blue-blue, white/orange-orange, white/green-green, white/brown-brown
Thickness, outer sheath	0.40 mm
Twisted pairs	2 cores to the pair
Overall twist	4 pairs for core
Optical shield covering	85 %
Max. conductor resistance	< 93.8 Ω /km
Insulation resistance	$\geq 5 \text{ G}\Omega \cdot \text{km}$
Cable capacity	< 56 nF/km
	< 1600 pF/km (Pair-Ground)
Nominal voltage, cable	72 V DC
	300 V AC (in acc. with UL)
Test voltage Core/Core	2500 V DC
Smallest bending radius, fixed installation	30 mm
Smallest bending radius, movable installation	60 mm (for installation)
Tensile strength	80 N
Halogen-free	According to IEC 60754-2
Flame resistance	According to FT-2
Resistance to oil	according to IEC 60811-2-1
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation)
Ambient temperature (installation)	0 °C ... 50 °C

VS-OE-OE-94A/300,0 - Data cable



1403664

<https://www.phoenixcontact.com/in/products/1403664>

Classifications

ECLASS

ECLASS-11.0	27061801
ECLASS-12.0	27061801
ECLASS-13.0	27061801

ETIM

ETIM 9.0	EC003249
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

VS-OE-OE-94A/300,0 - Data cable



1403664

<https://www.phoenixcontact.com/in/products/1403664>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

VS-OE-OE-94A/300,0 - Data cable

1403664

<https://www.phoenixcontact.com/in/products/1403664>



Accessories

VS-CABLE-STRIP-VARIO - Stripping tool

1657407

<https://www.phoenixcontact.com/in/products/1657407>

Stripping tool, for the multi-level stripping of shielded cables



Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

info@phoenixcontact.co.in