Acti9 - comb busbar - 3L - 18 mm pitch - 20 modules - 100A



A9XPH320

! Discontinued on: 01 Dec 2024

① To be discontinued

Main

Range	Acti9	
Product or component type	Comb busbar	
Mounting mode	Horizontal	
Accessory / separate part category	Connection accessory	
Lines description	3L	
Length in 18 mm modules	20	
Standards	EN/IEC 61439-1	

Complementary

Number of ways	6 ways 3 L	
Distribution type	L1 L2 L3	
Poles configuration for 1 way	1 x 3P	
Connection pitch	18 mm	
Connector type	Tooth	
Distance between way	54 mm	
Marking	L1 L2 L3	
Insulation	Insulated	
Device presentation	Cuttable	
[le] rated operational current	100 A at 40 °C	
[Ue] rated operational voltage	415 V AC	
[Ui] rated insulation voltage	500 V AC conforming to IEC 61439-2	
Mounting location	Top or bottom on tunnel type terminals Top or bottom on double terminal	
9 mm pitches	40	
Width	360 mm	
Colour	White (RAL 9003)	
Range compatibility	Acti9 Acti9 iC60 Acti9 Acti9 iK60 Acti9 Acti9 iID Acti9 Acti9 iID K Acti9 Acti9 iSW Acti9 Acti9 iSW-NA Multi9 Multi9 C60	

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Environment

Fire resistance	960 °C (30 s) conforming to IEC 60695-2-1	
Pollution degree	3 conforming to IEC 60947-7-1	
IP degree of protection	IP20 with end-pieces and tooth covers	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.800 cm
Package 1 Width	3.000 cm
Package 1 Length	35.800 cm
Package 1 Weight	187.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	6.200 cm
Package 2 Width	9.000 cm
Package 2 Length	47.000 cm
Package 2 Weight	1.052 kg
Unit Type of Package 3	S04
Number of Units in Package 3	50
Package 3 Height	30.000 cm
Package 3 Width	40.000 cm
Package 3 Length	60.000 cm
Package 3 Weight	11.296 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint

Environmental Disclosure

Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
SCIP Number	12618b2a-bc0e-4c2d-bb7b-9185c26e01fe
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins