### AMP | AMPSEAL

TE Internal #: 1-776230-5

PCB Mount Header, Vertical, Wire-to-Board, 35 Position, 4 mm [.

157 in] Centerline, Fully Shrouded, Gold (Au), Through Hole -

Solder, Sealable, AMPSEAL

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles > AMPSEAL PCB Vertical Headers











PCB Connector Type: PCB Mount Header

PCB Mount Orientation: Vertical
Connector System: Wire-to-Board

Number of Positions: **35**Number of Rows: **3** 

All AMPSEAL PCB Vertical Headers (56)

## **Features**

## **Product Type Features**

PCB Connector Type	PCB Mount Header
Connector System	Wire-to-Board
Header Type	Fully Shrouded
Sealable	Yes
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

## **Configuration Features**

PCB Mount Orientation	Vertical
Number of Positions	35
Number of Rows	3

# **Body Features**

Connector & Keying Code	5
-------------------------	---



Primary Product Color	Blue
Contact Features	
Contact Mating Area Plating Material	Gold (Au)
Contact Type	Pin
Contact Current Rating (Max)	17 A
Termination Features	
Termination Method to PCB	Through Hole - Solder
Mechanical Attachment	
PCB Mount Retention	Without
PCB Mount Alignment	With
Connector Mounting Type	Board Mount
Mating Alignment	With
Housing Features	
Centerline (Pitch)	4 mm[.157 in]
Usage Conditions	
Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Method	Tray

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC



Halogen Content	Not Low Halogen - contains Br or Cl > 900
	ppm.

#### Solder Process Capability

Wave solder capable to 265°C


#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**







# Also in the Series | AMPSEAL







Automotive Terminals(8)



Rectangular Power Connectors(123)

# Customers Also Bought

PCB Mount Header, Vertical, Wire-to-Board, 35 Position, 4 mm [.157 in] Centerline, Fully Shrouded, Gold (Au), Through Hole - Solder, Sealable, AMPSEAL





















## **Documents**

**Product Drawings** 

35POS,PIN DIA 1.3,HDR ASSY,180DEG,COD 5

English

**CAD Files** 

3D PDF

English

**Customer View Model** 

ENG\_CVM\_1-776230-5\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_1-776230-5\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_1-776230-5\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

PCB Mount Header, Vertical, Wire-to-Board, 35 Position, 4 mm [.157 in] Centerline, Fully Shrouded, Gold (Au), Through Hole - Solder, Sealable, AMPSEAL



**AMPSEAL Connector Series** 

English

AMPSEAL Connector Catalog

English

ICT Terminals and Connectors Catalogue

English

**Product Specifications** 

**Application Specification** 

English

**Agency Approvals** 

**UL Report** 

English