




		REVISIONS			
REV	ECO	DESCRIPTION	DATE	BY	APPR
A3	-	RELEASE NEW DWG FORMAT	18/JUN/13	DRP	-








NOTES: UNLESS OTHERWISE SPECIFIED


- MATERIAL:
 HOUSING: THERMOPLASTIC
 SEAL: SILICONE RUBBER
- 2. MODIFICATIONS: N/A
- 3. SPECIFICATIONS:
 - 3.1 CURRENT RATING: 7.5 AMPS
 - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
 - 3.5 MOISTURE RESISTANCE: IP67 (MATED CONDITION)
 - 3.6 MATING CYCLE DURABILITY: 100 CYCLES
 - 3.7 RoHS COMPLIANT
- 4. MATING PART: ATM04-3P* RECEPTACLE. (* = MODIFICATIONS AND/OR COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.



-			
CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL
SIZE	O.D.	O.D.	WIRE RANGE
20	1.35 mm (.053 in)	3.05 mm (.120 in)	16 - 22 AWG



PART NUMBER CHART				
COLOR	PART NUMBER			
GREY	ATM06-3S			
BLACK	ATM06-3S-BLK			
BLUE	ATM06-3S-BLU			
BROWN	ATM06-3S-BRN			
GREEN	ATM06-3S-GRN			
RED	ATM06-3S-RED			
WHITE	ATM06-3S-WHT			
YELLOW	ATM06-3S-YEL			



STANDARD MOLDED COLOR IS GREY. ADDITIONAL COLORS SHOWN IN PART NUMBER CHART ARE AVAILABLE VIA SPECIAL ORDER.

	CEEDADTN	UMBER CHART					
	SEEPARIN	UIVIDER CHART					
	PART NUMBER		DESCRIPTION			ITEM	
QUANTITY MATERIALS LIST							
UNLESS OTHER		SIGNATUR	ES DATE	Amphonol			
1 Planteness of the Control of the C		D.PARKS	18/JUN/13	Amphenol			
		CHECKED:		Sine Systems - www.amphenol-sine.com			_
		ENGINEER:		44724 Morley Drive Clinton Township, MI 48036			
		APPROVAL:					
		CUSTOMER:	PLUG. 3 SOCKET. ATM SERIES				
		THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED, ALL DIMENSIONS ARE SUBJECT TO NORMAL		1	,,		
PROCESS SPECIFICATIONS:				B C-	ATM06-3S		A3
		MANUFACTURING VARIAT	IONS.	SCALE NONE		SHEET 1 OF	1