



Datasheet

ENGLISH



Á

ÁÙÀ FFĒ € Ĩ Á
ÙĲ ^ & ã ã ã } • KÓ ã ã X ^ Ĩ ã ã Á Ü Ö W Á ã ã ã
Ē FG Á MS Á Ü FH Ĩ HÜ ã @ P ã ã ã ã * Ĩ ã Á Ü Ĩ & ^ ã Á
Ē ã ^ Ĩ } Á ã ã ã Ĩ Á
Ē Ĩ Á Ĩ ^ Ĩ Á Ü Ĩ { Á Ü Ĩ } ã ã ã Á
Ē Ĩ X Ĩ Ĩ Ĩ Ü ã * Ĩ Á Ü ã ^ Á Ü Á Ĩ Ĩ Á Ü Ĩ * Á
Ē Ü ã ã Á ã ã @

Quantity Of Inputs	1
Voltage	230V
Amperage	32A
VA per Input (Load Capacity)	7.3kW
Frequency	50/60 Hz
Over Current Protection	None
Switch	No
Power Cable Wire Gauge	4.0mm ² H07RN-F
Power Cable Length	3m
Plug Type	IEC60309 2P+E, 32A, 230V
Combined Total Receptacle/Socket Quantity	12
Receptacle/Socket Type #1	UK BS1363
Quantity on Face #1	12
Style #1	Individual - Right Hand Angled
Maximum Output per Receptacle/Socket #1	13A
Voltage per Receptacle/Socket #1	230V
Heavy Steel -Black Powder Coat	Yes
Configuration	978mm Vertical Rackmount
GE Vertical Mounting Bracket	Yes
Toolless Mounting Hardware - Center to Center Spacing	933.45 mm
Product Warranty	Lifetime
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	CE Marked
Certification/Agency Approvals	Complies with EN 60950
Chassis Dimensions (LxWxD)	978mm x 54mm x 51mm

Á