



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 27

Loctite AA 330

SDS No. : 416828
V011.1

Revision: 28.07.2023

printing date: 31.10.2023

Replaces version from: 22.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Loctite AA 330

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Acrylic Adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

| | |
|---|-------------|
| Skin irritation | Category 2 |
| H315 Causes skin irritation. | |
| Serious eye damage | Category 1 |
| H318 Causes serious eye damage. | |
| Skin sensitizer | Category 1 |
| H317 May cause an allergic skin reaction. | |
| Toxic to reproduction | Category 1B |
| H360D May damage the unborn child. | |
| Specific target organ toxicity - single exposure | Category 3 |
| H335 May cause respiratory irritation. | |
| Target organ: respiratory tract irritation | |
| Chronic hazards to the aquatic environment | Category 3 |
| H412 Harmful to aquatic life with long lasting effects. | |

2.2. Label elements

Label elements (CLP):

Hazard pictogram:**Contains**

Tetrahydrofurfuryl methacrylate

methacrylic acid

2-Ethylhexyl methacrylate

1-Methyltrimethylene dimethacrylate

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)
methyl methacrylate

Signal word:

Danger

Hazard statement:

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H360D May damage the unborn child.

H412 Harmful to aquatic life with long lasting effects.

Supplemental information

For use in industrial installations only.
Restricted to professional users.

**Precautionary statement:
Prevention**

P201 Obtain special instructions before use.

P261 Avoid breathing vapors.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

**Precautionary statement:
Response**

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

None if used properly.

Classified as Skin irritation Category 2, H315 based on Expert Judgement and experimental data of an OECD 431 test or based on analogy to similar products tested.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. EC Number REACH-Reg No. | Concentration | Classification | Specific Conc. Limits, M-factors and ATEs | Add. Information |
|---|---------------|---|--|------------------|
| Tetrahydrofurfuryl methacrylate 2455-24-5 219-529-5 01-2120748481-53 | 25- 50 % | Skin Sens. 1, H317 Repr. 1B, H360D Aquatic Chronic 3, H412 | | |
| methacrylic acid 79-41-4 201-204-4 01-2119463884-26 | 5- < 10 % | Acute Tox. 4, Oral, H302 Acute Tox. 3, Dermal, H311 Acute Tox. 4, Inhalation, H332 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335 | STOT SE 3; H335; C >= 1 % ===== dermal:ATE = 500 mg/kg inhalation:ATE = 3,61 mg/l;dust/mist | |
| 2-Ethylhexyl methacrylate 688-84-6 211-708-6 01-2119490166-35 | 5- < 10 % | Skin Sens. 1B, H317 STOT SE 3, H335 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 3, H412 | STOT SE 3; H335; C >= 10 % | |
| 1-Methyltrimethylene dimethacrylate 1189-08-8 214-711-0 01-2119969461-31 | 1- < 5 % | Skin Sens. 1B, H317 | | |
| reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6 | 0,1- < 1 % | Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411 Eye Irrit. 2, H319 | Skin Irrit. 2; H315; C >= 5 % Eye Irrit. 2; H319; C >= 5 % | |
| Butyl hydroxytoluene 128-37-0 204-881-4 01-2119565113-46 | 0,1- < 1 % | Aquatic Acute 1, H400 Aquatic Chronic 1, H410 | M acute = 1 M chronic = 1 | |
| methyl methacrylate 80-62-6 201-297-1 01-2119452498-28 | 0,1- < 1 % | Flam. Liq. 2, H225 STOT SE 3, H335 Skin Irrit. 2, H315 Skin Sens. 1, H317 | | EU OEL |
| Cumene hydroperoxide 80-15-9 201-254-7 01-2119475796-19 | 0,1- < 1 % | STOT RE 2, H373 Skin Corr. 1B, H314 Acute Tox. 2, Inhalation, H330 Aquatic Chronic 2, H411 Acute Tox. 4, Oral, H302 Acute Tox. 4, Dermal, H312 Org. Perox. E, H242 STOT SE 3, H335 | Eye Irrit. 2; H319; C 1 - < 3 % Skin Irrit. 2; H315; C 3 - < 10 % Eye Dam. 1; H318; C 3 - < 10 % STOT SE 3; H335; C >= 1 % Skin Corr. 1B; H314; C >= 10 % ===== dermal:ATE = 1.100 mg/kg | |
| Tetrahydrofurfuryl alcohol 97-99-4 202-625-6 | 0,1- < 0,3 % | Eye Irrit. 2, H319 Repr. 1B, H360 | | |
| 1,1,2-trichloroethane 79-00-5 201-166-9 | 0,1- < 1 % | Acute Tox. 4, Inhalation, H332 Acute Tox. 4, Oral, H302 Acute Tox. 4, Dermal, H312 Carc. 2, H351 | | |

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.

For full text of the H - statements and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

SKIN: Rash, Urticaria.

After eye contact: Corrosive, may cause permanent damage to eyes (impairment of vision).

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

Keep away from sources of ignition.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.
See advice in section 8

Hygiene measures:

Do not eat, drink or smoke while working.
Wash hands before work breaks and after finishing work.
Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.
Refer to Technical Data Sheet

7.3. Specific end use(s)

Acrylic Adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|--|-----|-------------------|-----------------------------------|--|-----------------|
| Methacrylic acid 79-41-4 [METHACRYLIC ACID] | 20 | 72 | Time Weighted Average (TWA): | | EH40 WEL |
| Methacrylic acid 79-41-4 [METHACRYLIC ACID] | 40 | 143 | Short Term Exposure Limit (STEL): | 15 minutes | EH40 WEL |
| 2,6-di-tert-Butyl-p-cresol 128-37-0 [2,6-DI-TERT-BUTYL-P-CRESOL] | | 10 | Time Weighted Average (TWA): | | EH40 WEL |
| Methyl methacrylate 80-62-6 [METHYL METHACRYLATE] | 50 | 208 | Time Weighted Average (TWA): | | EH40 WEL |
| Methyl methacrylate 80-62-6 [METHYL METHACRYLATE] | 100 | | Short Term Exposure Limit (STEL): | Indicative | ECLTV |
| Methyl methacrylate 80-62-6 [METHYL METHACRYLATE] | 50 | | Time Weighted Average (TWA): | Indicative | ECLTV |
| Methyl methacrylate 80-62-6 [METHYL METHACRYLATE] | 100 | 416 | Short Term Exposure Limit (STEL): | 15 minutes | EH40 WEL |

Occupational Exposure Limits

Valid for
Ireland

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|--|-----|-------------------|-----------------------------------|--|-----------------|
| Methacrylic acid 79-41-4 [METHACRYLIC ACID] | 20 | 70 | Time Weighted Average (TWA): | | IR_OEL |
| Methacrylic acid 79-41-4 [METHACRYLIC ACID] | 40 | 140 | Short Term Exposure Limit (STEL): | 15 minutes | IR_OEL |
| 2,6-di-tert-Butyl-p-cresol 128-37-0 [2,6-DITERTIARY-BUTYL-PARA-CRESOL] | | 2 | Time Weighted Average (TWA): | | IR_OEL |
| Methyl methacrylate 80-62-6 [METHYL METHACRYLATE] | 50 | | Time Weighted Average (TWA): | Indicative OELV | IR_OEL |
| Methyl methacrylate 80-62-6 [METHYL METHACRYLATE] | 100 | | Short Term Exposure Limit (STEL): | Indicative | ECLTV |
| Methyl methacrylate 80-62-6 [METHYL METHACRYLATE] | 50 | | Time Weighted Average (TWA): | Indicative | ECLTV |
| Methyl methacrylate 80-62-6 [METHYL METHACRYLATE] | 100 | | Short Term Exposure Limit (STEL): | 15 minutes Indicative OELV | IR_OEL |
| 1,1,2-Trichloroethane 79-00-5 [1,1,2-TRICHLOROETHANE] | 10 | 45 | Time Weighted Average (TWA): | | IR_OEL |
| 1,1,2-Trichloroethane 79-00-5 [1,1,2-TRICHLOROETHANE] | | | Skin designation: | Can be absorbed through the skin. | IR_OEL |

Predicted No-Effect Concentration (PNEC):

| Name on list | Environmental Compartment | Exposure period | Value | | | | Remarks |
|--|------------------------------------|-----------------|------------------|-----|------------------|--------|---------|
| | | | mg/l | ppm | mg/kg | others | |
| Tetrahydrofurfuryl methacrylate 2455-24-5 | aqua (freshwater) | | 0,347 mg/l | | | | |
| Tetrahydrofurfuryl methacrylate 2455-24-5 | aqua (marine water) | | 0,035 mg/l | | | | |
| Tetrahydrofurfuryl methacrylate 2455-24-5 | sewage treatment plant (STP) | | 15,8 mg/l | | | | |
| Tetrahydrofurfuryl methacrylate 2455-24-5 | sediment (freshwater) | | | | 2,12 mg/kg | | |
| Tetrahydrofurfuryl methacrylate 2455-24-5 | sediment (marine water) | | | | 0,212 mg/kg | | |
| Tetrahydrofurfuryl methacrylate 2455-24-5 | aqua (intermittent releases) | | 0,347 mg/l | | | | |
| Tetrahydrofurfuryl methacrylate 2455-24-5 | Soil | | | | 0,221 mg/kg | | |
| methacrylic acid 79-41-4 | aqua (freshwater) | | 0,82 mg/l | | | | |
| methacrylic acid 79-41-4 | aqua (marine water) | | 0,82 mg/l | | | | |
| methacrylic acid 79-41-4 | sewage treatment plant (STP) | | 10 mg/l | | | | |
| methacrylic acid 79-41-4 | aqua (intermittent releases) | | 0,82 mg/l | | | | |
| methacrylic acid 79-41-4 | Soil | | | | 1,2 mg/kg | | |
| 2-Ethylhexyl methacrylate 688-84-6 | aqua (freshwater) | | 0,003 mg/l | | | | |
| 2-Ethylhexyl methacrylate 688-84-6 | aqua (marine water) | | 0 mg/l | | | | |
| 2-Ethylhexyl methacrylate 688-84-6 | sediment (freshwater) | | | | 2,24 mg/kg | | |
| 2-Ethylhexyl methacrylate 688-84-6 | sediment (marine water) | | | | 0,224 mg/kg | | |
| 2-Ethylhexyl methacrylate 688-84-6 | sewage treatment plant (STP) | | 10 mg/l | | | | |
| 2-Ethylhexyl methacrylate 688-84-6 | Soil | | | | 0,446 mg/kg | | |
| 1-Methyltrimethylene dimethacrylate 1189-08-8 | aqua (freshwater) | | 0,043 mg/l | | | | |
| 1-Methyltrimethylene dimethacrylate 1189-08-8 | aqua (marine water) | | 0,004 mg/l | | | | |
| 1-Methyltrimethylene dimethacrylate 1189-08-8 | sewage treatment plant (STP) | | | | 20 mg/kg | | |
| 1-Methyltrimethylene dimethacrylate 1189-08-8 | sediment (freshwater) | | | | 3,12 mg/kg | | |
| 1-Methyltrimethylene dimethacrylate 1189-08-8 | sediment (marine water) | | | | 0,312 mg/kg | | |
| 1-Methyltrimethylene dimethacrylate 1189-08-8 | Soil | | | | 0,573 mg/kg | | |
| 2,6-Di-tert-butyl-p-cresol 128-37-0 | aqua (freshwater) | | 0,000199 mg/l | | | | |
| 2,6-Di-tert-butyl-p-cresol 128-37-0 | aqua (marine water) | | 0,00002 mg/l | | | | |
| 2,6-Di-tert-butyl-p-cresol 128-37-0 | sewage treatment plant (STP) | | 0,17 mg/l | | | | |
| 2,6-Di-tert-butyl-p-cresol 128-37-0 | sediment (freshwater) | | | | 0,0996 mg/kg | | |
| 2,6-Di-tert-butyl-p-cresol 128-37-0 | sediment (marine water) | | | | 0,00996 mg/kg | | |
| 2,6-Di-tert-butyl-p-cresol 128-37-0 | Soil | | | | 0,04769 mg/kg | | |
| 2,6-Di-tert-butyl-p-cresol 128-37-0 | oral | | | | 8,33 mg/kg | | |

| | | | | | | | |
|---|---------------------------------|--|--------------|--|--------------|--|----------------------|
| 2,6-Di-tert-butyl-p-cresol 128-37-0 | aqua (intermittent releases) | | 0,00199 mg/l | | | | |
| 2,6-Di-tert-butyl-p-cresol 128-37-0 | Air | | | | | | no hazard identified |
| methyl methacrylate 80-62-6 | aqua (freshwater) | | 0,94 mg/l | | | | |
| methyl methacrylate 80-62-6 | aqua (marine water) | | 0,94 mg/l | | | | |
| methyl methacrylate 80-62-6 | aqua (intermittent releases) | | 0,94 mg/l | | | | |
| methyl methacrylate 80-62-6 | sewage treatment plant (STP) | | 10 mg/l | | | | |
| methyl methacrylate 80-62-6 | sediment (freshwater) | | | | 5,74 mg/kg | | |
| methyl methacrylate 80-62-6 | Soil | | | | 1,47 mg/kg | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | aqua (freshwater) | | 0,0031 mg/l | | | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | aqua (intermittent releases) | | 0,031 mg/l | | | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | aqua (marine water) | | 0,00031 mg/l | | | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | sewage treatment plant (STP) | | 0,35 mg/l | | | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | sediment (freshwater) | | | | 0,023 mg/kg | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | sediment (marine water) | | | | 0,0023 mg/kg | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | Soil | | | | 0,0029 mg/kg | | |
| Tetrahydrofurfuryl alcohol 97-99-4 | aqua (freshwater) | | 1,9 mg/l | | | | |
| Tetrahydrofurfuryl alcohol 97-99-4 | aqua (intermittent releases) | | 0,917 mg/l | | | | |
| Tetrahydrofurfuryl alcohol 97-99-4 | aqua (marine water) | | 0,19 mg/l | | | | |
| Tetrahydrofurfuryl alcohol 97-99-4 | sewage treatment plant (STP) | | 10 mg/l | | | | |
| Tetrahydrofurfuryl alcohol 97-99-4 | sediment (freshwater) | | | | 8,6 mg/kg | | |
| Tetrahydrofurfuryl alcohol 97-99-4 | sediment (marine water) | | | | 0,86 mg/kg | | |
| Tetrahydrofurfuryl alcohol 97-99-4 | Soil | | | | 0,6 mg/kg | | |

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|--|--------------------|-------------------|---|---------------|------------------------|----------------------|
| Tetrahydrofurfuryl methacrylate 2455-24-5 | Workers | inhalation | Long term exposure - systemic effects | | 3,53 mg/m ³ | |
| Tetrahydrofurfuryl methacrylate 2455-24-5 | Workers | dermal | Long term exposure - systemic effects | | 1 mg/kg | |
| Tetrahydrofurfuryl methacrylate 2455-24-5 | General population | inhalation | Long term exposure - systemic effects | | 0,87 mg/m ³ | |
| Tetrahydrofurfuryl methacrylate 2455-24-5 | General population | dermal | Long term exposure - systemic effects | | 0,5 mg/kg | |
| Tetrahydrofurfuryl methacrylate 2455-24-5 | General population | oral | Long term exposure - systemic effects | | 0,5 mg/kg | |
| methacrylic acid 79-41-4 | Workers | Inhalation | Long term exposure - local effects | | 88 mg/m ³ | |
| methacrylic acid 79-41-4 | Workers | Inhalation | Long term exposure - systemic effects | | 29,6 mg/m ³ | |
| methacrylic acid 79-41-4 | Workers | dermal | Long term exposure - systemic effects | | 4,25 mg/kg | |
| methacrylic acid 79-41-4 | General population | Inhalation | Long term exposure - local effects | | 6,55 mg/m ³ | |
| methacrylic acid 79-41-4 | General population | Inhalation | Long term exposure - systemic effects | | 6,3 mg/m ³ | |
| methacrylic acid 79-41-4 | General population | dermal | Long term exposure - systemic effects | | 2,55 mg/kg | |
| 2-Ethylhexyl methacrylate 688-84-6 | worker | dermal | Long term exposure - systemic effects | | 5 mg/kg | |
| 1-Methyltrimethylene dimethacrylate 1189-08-8 | Workers | inhalation | Long term exposure - systemic effects | | 14,5 mg/m ³ | |
| 1-Methyltrimethylene dimethacrylate 1189-08-8 | Workers | dermal | Long term exposure - systemic effects | | 4,2 mg/kg | |
| 1-Methyltrimethylene dimethacrylate 1189-08-8 | General population | oral | Long term exposure - systemic effects | | 2,5 mg/kg | |
| 1-Methyltrimethylene dimethacrylate 1189-08-8 | General population | dermal | Long term exposure - systemic effects | | 2,5 mg/kg | |
| 1-Methyltrimethylene dimethacrylate 1189-08-8 | General population | inhalation | Long term exposure - systemic effects | | 4,3 mg/m ³ | |
| 2,6-Di-tert-butyl-p-cresol 128-37-0 | Workers | inhalation | Long term exposure - systemic effects | | 3,5 mg/m ³ | no hazard identified |
| 2,6-Di-tert-butyl-p-cresol 128-37-0 | Workers | dermal | Long term exposure - systemic effects | | 0,5 mg/kg | no hazard identified |
| 2,6-Di-tert-butyl-p-cresol 128-37-0 | General population | inhalation | Long term exposure - systemic effects | | 0,86 mg/m ³ | no hazard identified |
| 2,6-Di-tert-butyl-p-cresol 128-37-0 | General population | dermal | Long term exposure - systemic effects | | 0,25 mg/kg | no hazard identified |
| 2,6-Di-tert-butyl-p-cresol 128-37-0 | General population | oral | Long term exposure - systemic effects | | 0,25 mg/kg | no hazard identified |
| methyl methacrylate 80-62-6 | Workers | dermal | Acute/short term exposure - local effects | | 1,5 mg/cm ² | |
| methyl methacrylate 80-62-6 | Workers | dermal | Long term exposure - | | 13,67 mg/kg | |

| | | | | | |
|---|--------------------|------------|--|--|-------------|
| | | | systemic effects | | |
| methyl methacrylate 80-62-6 | Workers | Inhalation | Long term exposure - systemic effects | | 208 mg/m3 |
| methyl methacrylate 80-62-6 | Workers | dermal | Long term exposure - local effects | | 1,5 mg/cm2 |
| methyl methacrylate 80-62-6 | Workers | Inhalation | Long term exposure - local effects | | 208 mg/m3 |
| methyl methacrylate 80-62-6 | General population | dermal | Acute/short term exposure - local effects | | 1,5 mg/cm2 |
| methyl methacrylate 80-62-6 | General population | dermal | Long term exposure - systemic effects | | 8,2 mg/kg |
| methyl methacrylate 80-62-6 | General population | Inhalation | Long term exposure - systemic effects | | 74,3 mg/m3 |
| methyl methacrylate 80-62-6 | General population | dermal | Long term exposure - local effects | | 1,5 mg/cm2 |
| methyl methacrylate 80-62-6 | General population | Inhalation | Long term exposure - local effects | | 104 mg/m3 |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | Workers | inhalation | Long term exposure - systemic effects | | 6 mg/m3 |
| Tetrahydrofurfuryl alcohol 97-99-4 | Workers | inhalation | Long term exposure - systemic effects | | 1,4 mg/m3 |
| Tetrahydrofurfuryl alcohol 97-99-4 | Workers | inhalation | Acute/short term exposure - systemic effects | | 1,4 mg/m3 |
| Tetrahydrofurfuryl alcohol 97-99-4 | Workers | dermal | Long term exposure - systemic effects | | 0,35 mg/kg |
| Tetrahydrofurfuryl alcohol 97-99-4 | Workers | dermal | Acute/short term exposure - systemic effects | | 0,35 mg/kg |
| Tetrahydrofurfuryl alcohol 97-99-4 | General population | inhalation | Long term exposure - systemic effects | | 0,25 mg/m3 |
| Tetrahydrofurfuryl alcohol 97-99-4 | General population | inhalation | Acute/short term exposure - systemic effects | | 0,25 mg/m3 |
| Tetrahydrofurfuryl alcohol 97-99-4 | General population | dermal | Long term exposure - systemic effects | | 0,175 mg/kg |
| Tetrahydrofurfuryl alcohol 97-99-4 | General population | dermal | Acute/short term exposure - systemic effects | | 0,175 mg/kg |
| Tetrahydrofurfuryl alcohol 97-99-4 | General population | oral | Long term exposure - systemic effects | | 0,175 mg/kg |
| Tetrahydrofurfuryl alcohol 97-99-4 | General population | oral | Acute/short term exposure - systemic effects | | 0,175 mg/kg |

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | |
|---|---|
| Delivery form | liquid |
| Colour | amber |
| Odor | Acrylic |
| Physical state | liquid |
| Melting point | Not applicable, Product is a liquid |
| Solidification temperature | < 0 °C (< 32 °F) |
| Initial boiling point | > 148,9 °C (> 300 °F) |
| Flammability | The product is not flammable. |
| Explosive limits | Not applicable, The product is not flammable. |
| Flash point | 83 °C (181.4 °F); Tagliabue closed cup |
| Auto-ignition temperature | Not applicable, The product is not flammable. |
| Decomposition temperature | Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use |
| pH | 10 |
| (20 °C (68 °F); Conc.: 100 % product; Solvent: Water) | |
| Viscosity (kinematic) | 47.600 - 76.100 mm ² /s |
| (25 °C (77 °F);) | |
| Solubility (qualitative) | Slight |
| (20 °C (68 °F); Solvent: Water) | |
| Partition coefficient: n-octanol/water | Not applicable |
| | Mixture |
| Vapour pressure | < 10 mm hg |
| (26,6 °C (79,9 °F)) | |
| Vapour pressure | < 700 mbar;no method / method unknown |
| (50 °C (122 °F)) | |
| Density | 1,05 g/cm ³ None |
| (20 °C (68 °F)) | |

| | |
|-------------------------------------|---------------------------------------|
| Relative vapour density: (20 °C) | Heavier than air |
| Particle characteristics | Not applicable Product is a liquid |

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity**10.1. Reactivity**

Reacts with strong oxidants.

Acids.

Reducing agents.

Strong bases.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

Hydrocarbons

nitrogen oxides

Rapid polymerisation may generate excessive heat and pressure.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|--|---------------|---------------|---------|---|
| Tetrahydrofurfuryl methacrylate 2455-24-5 | LD50 | 3.945 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| methacrylic acid 79-41-4 | LD50 | 1.320 mg/kg | rat | equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity) |
| 2-Ethylhexyl methacrylate 688-84-6 | LD0 | > 2.000 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| 2-Ethylhexyl methacrylate 688-84-6 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| 1-Methyltrimethylene dimethacrylate 1189-08-8 | LD50 | > 5.000 mg/kg | rat | not specified |
| reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 420 (Acute Oral Toxicity) |
| Butyl hydroxytoluene 128-37-0 | LD50 | > 6.000 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| methyl methacrylate 80-62-6 | LD50 | 9.400 mg/kg | rat | not specified |
| Cumene hydroperoxide 80-15-9 | LD50 | 382 mg/kg | rat | other guideline: |
| Tetrahydrofurfuryl alcohol 97-99-4 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 423 (Acute Oral toxicity) |

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|--|--|----------------------|---------|---|
| methacrylic acid 79-41-4 | LD50 | 500 - 1.000 mg/kg | rabbit | Dermal Toxicity Screening |
| methacrylic acid 79-41-4 | Acute toxicity estimate (ATE) | 500 mg/kg | | Expert judgement |
| 2-Ethylhexyl methacrylate 688-84-6 | LD50 | > 20.000 mg/kg | rat | not specified |
| 1-Methyltrimethylene dimethacrylate 1189-08-8 | LD50 | > 3.000 mg/kg | rabbit | not specified |
| reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 402 (Acute Dermal Toxicity) |
| Butyl hydroxytoluene 128-37-0 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 402 (Acute Dermal Toxicity) |
| methyl methacrylate 80-62-6 | LD50 | > 5.000 mg/kg | rabbit | equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity) |
| Cumene hydroperoxide 80-15-9 | Acute toxicity estimate (ATE) | 1.100 mg/kg | | Expert judgement |

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Test atmosphere | Exposure time | Species | Method |
|---------------------------------|--|------------|-----------------|------------------|---------|--|
| methacrylic acid 79-41-4 | LC50 | > 3,6 mg/l | dust/mist | 4 h | rat | OECD Guideline 403 (Acute Inhalation Toxicity) |
| methacrylic acid 79-41-4 | Acute toxicity estimate (ATE) | 3,61 mg/l | dust/mist | | | Expert judgement |
| methyl methacrylate 80-62-6 | LC50 | 29,8 mg/l | vapour | 4 h | rat | not specified |
| Cumene hydroperoxide 80-15-9 | LC50 | 1,370 mg/l | vapour | 4 h | rat | not specified |

Skin corrosion/irritation:

Non corrosive to skin in accordance with the in vitro test method, B40 skin corrosion - Human skin model assay, equivalent to test method OECD 431 or based on analogy to similar products tested.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|--|----------------|------------------|---------|--|
| Tetrahydrofurfuryl methacrylate 2455-24-5 | not irritating | 24 h | rabbit | Draize Test |
| methacrylic acid 79-41-4 | corrosive | 3 min | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6 | not irritating | 4 h | rabbit | not specified |
| Butyl hydroxytoluene 128-37-0 | not irritating | 4 h | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| Cumene hydroperoxide 80-15-9 | corrosive | | rabbit | Draize Test |
| Tetrahydrofurfuryl alcohol 97-99-4 | not irritating | 4 h | rabbit | EPA OPP 81-5 (Acute Dermal Irritation) |

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|--|------------------------|------------------|---------|---|
| Tetrahydrofurfuryl methacrylate 2455-24-5 | not irritating | | rabbit | Draize Test |
| methacrylic acid 79-41-4 | corrosive | | rabbit | Draize Test |
| reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6 | not irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| Butyl hydroxytoluene 128-37-0 | slightly irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| Tetrahydrofurfuryl alcohol 97-99-4 | irritating | | rabbit | EPA OPP 81-4 (Acute Eye Irritation) |

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Species | Method |
|---|-----------------|---|--|---|
| Tetrahydrofurfuryl methacrylate 2455-24-5 | sensitising | Patch-Test | human | not specified |
| Tetrahydrofurfuryl methacrylate 2455-24-5 | sensitising | Direct peptide reactivity assay (DPRA) | cysteine and lysine, in chemico test | not specified |
| methacrylic acid 79-41-4 | not sensitising | Buehler test | guinea pig | equivalent or similar to OECD Guideline 406 (Skin Sensitisation) |
| 2-Ethylhexyl methacrylate 688-84-6 | sensitising | Guinea pig maximisation test | guinea pig | Magnusson and Kligman Method |
| 1-Methyltrimethylene dimethacrylate 1189-08-8 | sensitising | Mouse local lymphnode assay (LLNA) | mouse | OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |
| reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight \leq 700) 25068-38-6 | sensitising | Mouse local lymphnode assay (LLNA) | mouse | OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |
| Butyl hydroxytoluene 128-37-0 | not sensitising | Draize Test | guinea pig | Draize Test |
| methyl methacrylate 80-62-6 | sensitising | Mouse local lymphnode assay (LLNA) | mouse | OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |
| Tetrahydrofurfuryl alcohol 97-99-4 | not sensitising | Mouse local lymphnode assay (LLNA) | mouse | OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|--|----------|--|--------------------------------------|---------|---|
| methacrylic acid 79-41-4 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| 2-Ethylhexyl methacrylate 688-84-6 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay) |
| Butyl hydroxytoluene 128-37-0 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | not specified |
| Butyl hydroxytoluene 128-37-0 | negative | in vitro mammalian chromosome aberration test | with and without | | not specified |
| Butyl hydroxytoluene 128-37-0 | negative | mammalian cell gene mutation assay | with | | not specified |
| methyl methacrylate 80-62-6 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | not specified |
| Cumene hydroperoxide 80-15-9 | positive | bacterial reverse mutation assay (e.g Ames test) | without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Tetrahydrofurfuryl alcohol 97-99-4 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Tetrahydrofurfuryl alcohol 97-99-4 | negative | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Tetrahydrofurfuryl alcohol 97-99-4 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous components CAS-No. | Result | Route of application | Exposure time / Frequency of treatment | Species | Sex | Method |
|--|------------------|----------------------|--|---------|-------------|--|
| methacrylic acid 79-41-4 | not carcinogenic | inhalation | 2 y | mouse | male/female | OECD Guideline 451 (Carcinogenicity Studies) |
| reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6 | not carcinogenic | dermal | 2 y daily | mouse | male | OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies) |
| reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6 | not carcinogenic | oral: gavage | 2 y daily | rat | male/female | OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies) |
| Butyl hydroxytoluene 128-37-0 | | oral: feed | 2 y daily | rat | male | |

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Test type | Route of application | Species | Method |
|--|---|----------------------------|-------------------------|---------|---|
| Tetrahydrofurfuryl methacrylate 2455-24-5 | NOAEL P 300 mg/kg | screening | oral: gavage | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| methacrylic acid 79-41-4 | NOAEL P 50 mg/kg NOAEL F1 400 mg/kg NOAEL F2 400 mg/kg | Two generation study | oral: gavage | rat | OECD Guideline 416 (Two- Generation Reproduction Toxicity Study) |
| reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6 | NOAEL P >= 50 mg/kg NOAEL F1 >= 750 mg/kg NOAEL F2 >= 750 mg/kg | Two generation study | oral: gavage | rat | OECD Guideline 416 (Two- Generation Reproduction Toxicity Study) |
| Butyl hydroxytoluene 128-37-0 | NOAEL P 500 mg/kg | Two generation study | oral: feed | rat | not specified |

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Route of application | Exposure time / Frequency of treatment | Species | Method |
|--|-----------------|-------------------------|--|---------|---|
| Tetrahydrofurfuryl methacrylate 2455-24-5 | NOAEL 300 mg/kg | oral: gavage | 29 d yes, concurrent vehicle | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| methacrylic acid 79-41-4 | | inhalation | 90 d 6 h/d, 5 d/w | rat | OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day) |
| reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6 | NOAEL 50 mg/kg | oral: gavage | 14 w daily | rat | OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) |
| Butyl hydroxytoluene 128-37-0 | NOAEL 25 mg/kg | oral: feed | daily | rat | not specified |
| methyl methacrylate 80-62-6 | LOAEL 2000 ppm | inhalation | 14 weeks 6 hrs/day, 5 days/wk | mouse | Dose Range Finding Study |
| methyl methacrylate 80-62-6 | NOAEL 1000 ppm | inhalation | 14 weeks 6 hrs/day, 5 days/wk | mouse | Dose Range Finding Study |
| Cumene hydroperoxide 80-15-9 | | inhalation: aerosol | 6 h/d 5 d/w | rat | not specified |
| Tetrahydrofurfuryl alcohol 97-99-4 | NOAEL 500 ppm | oral: feed | 91-93 d daily | rat | not specified |
| Tetrahydrofurfuryl alcohol 97-99-4 | NOAEL 1000 ppm | oral: feed | 91-93 d daily | rat | not specified |

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|-----------------------------|---------------|---|--|
| Tetrahydrofurfuryl methacrylate 2455-24-5 | LC50 | 34,7 mg/l | 96 h | Pimephales promelas | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| methacrylic acid 79-41-4 | LC50 | 85 mg/l | 96 h | Salmo gairdneri (new name: Oncorhynchus mykiss) | EPA OTS 797.1400 (Fish Acute Toxicity Test) |
| 2-Ethylhexyl methacrylate 688-84-6 | LC50 | 2,78 mg/l | 96 h | Oryzias latipes | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| 1-Methyltrimethylene dimethacrylate 1189-08-8 | LC50 | 32,5 mg/l | 48 h | | DIN 38412-15 |
| reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6 | LC50 | 1,75 mg/l | 96 h | Oncorhynchus mykiss | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Butyl hydroxytoluene 128-37-0 | LC50 | Toxicity > Water solubility | 96 h | Brachydanio rerio (new name: Danio rerio) | EU Method C.1 (Acute Toxicity for Fish) |
| Butyl hydroxytoluene 128-37-0 | NOEC | 0,053 mg/l | 30 d | Oryzias latipes | OECD Guideline 210 (fish early lite stage toxicity test) |
| methyl methacrylate 80-62-6 | LC50 | 350 mg/l | 96 h | Leuciscus idus | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Cumene hydroperoxide 80-15-9 | LC50 | 3,9 mg/l | 96 h | Oncorhynchus mykiss | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Tetrahydrofurfuryl alcohol 97-99-4 | LC50 | > 101 mg/l | 96 h | Oryzias latipes | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| 1,1,2-trichloroethane 79-00-5 | LC50 | 136 mg/l | 96 h | Pimephales promelas | OECD Guideline 203 (Fish, Acute Toxicity Test) |

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|------------|---------------|---------------|--|
| methacrylic acid 79-41-4 | EC50 | > 130 mg/l | 48 h | Daphnia magna | EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids) |
| 2-Ethylhexyl methacrylate 688-84-6 | EC50 | 4,56 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6 | EC50 | 1,7 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Butyl hydroxytoluene 128-37-0 | EC50 | 0,48 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| methyl methacrylate 80-62-6 | EC50 | 69 mg/l | 48 h | Daphnia magna | EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids) |
| Cumene hydroperoxide 80-15-9 | EC50 | 18,84 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |

| | | | | | |
|----------------------------------|------|----------|------|---------------|----------------------|
| | | | | | Immobilisation Test) |
| 1,1,2-trichloroethane 79-00-5 | EC50 | 160 mg/l | 48 h | Daphnia magna | other guideline: |

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|------------|---------------|---------------|--|
| Tetrahydrofurfuryl methacrylate 2455-24-5 | NOEC | 37,2 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| 2-Ethylhexyl methacrylate 688-84-6 | NOEC | 0,105 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| 1-Methyltrimethylene dimethacrylate 1189-08-8 | NOEC | 5,09 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6 | NOEC | 0,3 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| Butyl hydroxytoluene 128-37-0 | NOEC | 0,069 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| methyl methacrylate 80-62-6 | NOEC | 37 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|--------------------------------|---------------|---|--|
| Tetrahydrofurfuryl methacrylate 2455-24-5 | EC50 | > 100 mg/l | 72 h | Desmodesmus subspicatus | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Tetrahydrofurfuryl methacrylate 2455-24-5 | NOEC | > 100 mg/l | 72 h | Desmodesmus subspicatus | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| methacrylic acid 79-41-4 | NOEC | 8,2 mg/l | 72 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| methacrylic acid 79-41-4 | EC50 | 45 mg/l | 72 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| 2-Ethylhexyl methacrylate 688-84-6 | EC50 | 7,68 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| 2-Ethylhexyl methacrylate 688-84-6 | NOEC | 0,28 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| 1-Methyltrimethylene dimethacrylate 1189-08-8 | EC50 | 9,79 mg/l | 72 h | Desmodesmus subspicatus | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| 1-Methyltrimethylene dimethacrylate 1189-08-8 | NOEC | 2,11 mg/l | 72 h | Desmodesmus subspicatus | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6 | EC50 | > 11 mg/l | 72 h | Scenedesmus capricornutum | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6 | NOEC | 4,2 mg/l | 72 h | Scenedesmus capricornutum | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Butyl hydroxytoluene 128-37-0 | EC50 | Toxicity > Water solubility | 72 h | Desmodesmus subspicatus (reported as Scenedesmus subspicatus) | EU Method C.3 (Algal Inhibition test) |
| Butyl hydroxytoluene 128-37-0 | EC10 | 0,4 mg/l | 72 h | Desmodesmus subspicatus (reported as Scenedesmus subspicatus) | EU Method C.3 (Algal Inhibition test) |
| methyl methacrylate 80-62-6 | EC50 | 170 mg/l | 96 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| methyl methacrylate 80-62-6 | NOEC | 100 mg/l | 96 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Cumene hydroperoxide 80-15-9 | EC50 | 3,1 mg/l | 72 h | Desmodesmus subspicatus (reported as Scenedesmus subspicatus) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Cumene hydroperoxide 80-15-9 | NOEC | 1 mg/l | 72 h | Desmodesmus subspicatus (reported as Scenedesmus subspicatus) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| 1,1,2-trichloroethane 79-00-5 | EC50 | 213 mg/l | 72 h | Scenedesmus subspicatus (new name: Desmodesmus subspicatus) | OECD Guideline 201 (Alga, Growth Inhibition Test) |

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|------------|---------------|------------------------------|------------------|
| methacrylic acid 79-41-4 | EC10 | 100 mg/l | 17 h | | not specified |
| 1-Methyltrimethylene dimethacrylate 1189-08-8 | NOEC | 20 mg/l | 28 d | activated sludge, domestic | not specified |
| reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular | IC50 | > 100 mg/l | 3 h | activated sludge, industrial | other guideline: |

| | | | | | |
|----------------------------------|------|--------------------------------|--------|----------------------------|---|
| weight≤700) 25068-38-6 | | | | | |
| Butyl hydroxytoluene 128-37-0 | EC50 | Toxicity > Water solubility | 3 h | activated sludge | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |
| methyl methacrylate 80-62-6 | EC20 | > 150 - 200 mg/l | 30 min | activated sludge, domestic | ISO 8192 (Test for Inhibition of Oxygen Consumption by Activated Sludge) |
| Cumene hydroperoxide 80-15-9 | EC10 | 70 mg/l | 30 min | not specified | not specified |

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Degradability | Exposure time | Method |
|---|---------------------------------|-----------|---------------|------------------|---|
| Tetrahydrofurfuryl methacrylate 2455-24-5 | not readily biodegradable. | aerobic | 75 % | 28 d | OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test) |
| methacrylic acid 79-41-4 | inherently biodegradable | aerobic | 100 % | 14 d | OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test) |
| methacrylic acid 79-41-4 | readily biodegradable | aerobic | 86 % | 28 d | OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test) |
| 2-Ethylhexyl methacrylate 688-84-6 | readily biodegradable | aerobic | 88 % | 28 d | OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I)) |
| 1-Methyltrimethylene dimethacrylate 1189-08-8 | readily biodegradable | aerobic | 84 % | 28 d | OECD Guideline 310 (Ready Biodegradability/CO ₂ in Sealed Vessels (Headspace Test) |
| reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6 | not readily biodegradable. | aerobic | 5 % | 28 d | OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test) |
| Butyl hydroxytoluene 128-37-0 | not readily biodegradable. | aerobic | 4,5 % | 28 d | OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I)) |
| Butyl hydroxytoluene 128-37-0 | not inherently biodegradable | aerobic | 5,2 - 5,6 % | 35 d | OECD Guideline 302 C (Inherent Biodegradability: Modified MITI Test (II)) |
| methyl methacrylate 80-62-6 | readily biodegradable | aerobic | 94 % | 14 d | OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I)) |
| Cumene hydroperoxide 80-15-9 | not readily biodegradable. | aerobic | 3 % | 28 d | OECD Guideline 301 B (Ready Biodegradability: CO ₂ Evolution Test) |
| Tetrahydrofurfuryl alcohol 97-99-4 | readily biodegradable | aerobic | 92 % | 28 d | OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I)) |
| 1,1,2-trichloroethane 79-00-5 | not readily biodegradable. | aerobic | 5 % | 28 d | OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I)) |

12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Bioconcentration factor (BCF) | Exposure time | Temperature | Species | Method |
|---|--------------------------------------|----------------------|--------------------|------------------------|--|
| 2-Ethylhexyl methacrylate 688-84-6 | 37 | 56 h | 24 °C | Danio rerio | OECD Guideline 305 (Bioconcentration: Flow-through Fish Test) |
| Butyl hydroxytoluene 128-37-0 | 330 - 1.800 | 56 d | | Cyprinus carpio | OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish) |
| Cumene hydroperoxide 80-15-9 | 9,1 | | | calculation | OECD Guideline 305 (Bioconcentration: Flow-through Fish Test) |
| 1,1,2-trichloroethane 79-00-5 | 2 | 14 d | | Lepomis macrochirus | other guideline: |

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | LogPow | Temperature | Method |
|---|-----------------|-------------|--|
| Tetrahydrofurfuryl methacrylate 2455-24-5 | 1,76 | | EU Method A.8 (Partition Coefficient) |
| methacrylic acid 79-41-4 | 0,93 | 22 °C | OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method) |
| 2-Ethylhexyl methacrylate 688-84-6 | 4,95 | 20 °C | OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method) |
| reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6 | 3,242 | 25 °C | EU Method A.8 (Partition Coefficient) |
| Butyl hydroxytoluene 128-37-0 | 5,1 | | OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method) |
| methyl methacrylate 80-62-6 | 1,38 | 20 °C | other guideline: |
| Cumene hydroperoxide 80-15-9 | 1,6 | 25 °C | OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method) |
| Tetrahydrofurfuryl alcohol 97-99-4 | -0,14 | 24,7 °C | OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method) |
| 1,1,2-trichloroethane 79-00-5 | > 2,05 - < 2,49 | 20 °C | QSAR (Quantitative Structure Activity Relationship) |

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | PBT / vPvB |
|---|---|
| Tetrahydrofurfuryl methacrylate 2455-24-5 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| methacrylic acid 79-41-4 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| 2-Ethylhexyl methacrylate 688-84-6 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| 1-Methyltrimethylene dimethacrylate 1189-08-8 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Butyl hydroxytoluene 128-37-0 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| methyl methacrylate 80-62-6 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Cumene hydroperoxide 80-15-9 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Tetrahydrofurfuryl alcohol 97-99-4 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Product disposal:
 Dispose of in accordance with local and national regulations.
 Do not empty into drains / surface water / ground water.

Disposal of uncleaned packages:
 After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code
 08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances
 The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number or ID number

| | |
|------|---------------------|
| ADR | Not dangerous goods |
| RID | Not dangerous goods |
| ADN | Not dangerous goods |
| IMDG | Not dangerous goods |
| IATA | Not dangerous goods |

14.2. UN proper shipping name

| | |
|------|---------------------|
| ADR | Not dangerous goods |
| RID | Not dangerous goods |
| ADN | Not dangerous goods |
| IMDG | Not dangerous goods |
| IATA | Not dangerous goods |

14.3. Transport hazard class(es)

| | |
|------|---------------------|
| ADR | Not dangerous goods |
| RID | Not dangerous goods |
| ADN | Not dangerous goods |
| IMDG | Not dangerous goods |
| IATA | Not dangerous goods |

14.4. Packing group

| | |
|------|---------------------|
| ADR | Not dangerous goods |
| RID | Not dangerous goods |
| ADN | Not dangerous goods |
| IMDG | Not dangerous goods |
| IATA | Not dangerous goods |

14.5. Environmental hazards

| | |
|------|----------------|
| ADR | not applicable |
| RID | not applicable |
| ADN | not applicable |
| IMDG | not applicable |
| IATA | not applicable |

14.6. Special precautions for user

| | |
|-----|----------------|
| ADR | not applicable |
|-----|----------------|

| | |
|------|----------------|
| RID | not applicable |
| ADN | not applicable |
| IMDG | not applicable |
| IATA | not applicable |

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

| | |
|---|----------------|
| Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): | Not applicable |
| Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): | Not applicable |
| Persistent organic pollutants (Regulation (EU) 2019/1021): | Not applicable |
| VOC content (2010/75/EC) | < 3 % |

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H225 Highly flammable liquid and vapour.
 H242 Heating may cause a fire.
 H302 Harmful if swallowed.
 H311 Toxic in contact with skin.
 H312 Harmful in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H330 Fatal if inhaled.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H351 Suspected of causing cancer.
 H360 May damage fertility or the unborn child.
 H360D May damage the unborn child.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

| | |
|-------------|---|
| ED: | Substance identified as having endocrine disrupting properties |
| EU OEL: | Substance with a Union workplace exposure limit |
| EU EXPLD 1: | Substance listed in Annex I, Reg (EC) No. 2019/1148 |
| EU EXPLD 2: | Substance listed in Annex II, Reg (EC) No. 2019/1148 |
| SVHC: | Substance of very high concern (REACH Candidate List) |
| PBT: | Substance fulfilling persistent, bioaccumulative and toxic criteria |
| PBT/vPvB: | Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria |
| vPvB: | Substance fulfilling very persistent and very bioaccumulative criteria |

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.