

Features

- Waterproof IP67 rating guarantees protection against extended immersion under higher pressures
- Voltage rating of 60V AC/DC
- Current rating of 3A
- Gold-plated brass contacts for corrosion resistance
- Threaded mating type
- Operating temperature range from -25°C to 80°C
- Nickel plated brass shell
- Conforms to standards IEC 61076-2-104

RS PRO Male M8 3 Pin A-code Connector

RS Stock No.: 0335198



RS PRO is the own brand of RS. The RS PRO Seal of Approval is your assurance of professional quality, a guarantee that every part is rigorously tested, inspected, and audited against demanding standards. Making RS PRO the Smart Choice for our customers.

Industrial Circular Connector



Product Description

The 3 pin male M8 metal front mount socket connector had been widely used for automative and sensor application, it's unshielded.

General Specifications

	_
Number of Contacts	3
Shielding	unshielded
Housing Material	Brass
Contact Material	Brass
Contact Plating	Gold
Pole Format	3 pin
Contact Gender	Male
Mating Type	Threaded
Body Orientation	Straight
Mating Cycles	500
Cable limits	/
Typical conductor size	/
Application	Sensor, automation

Electrical Specifications

Plug/Socket	Socket
Current Rating	3A
Voltage Rating	60V AC/DC
Insulation Resistance	≥100MΩ

Industrial Circular Connector



Mechanical Specifications

Connector Size	Standard
Termination Method	PCB
Mounting Type	Panel mount
Panel Cut-Out	φ8.1mm*7.2mm
Contact Diameter	φ1.0mm

Operation Environment Specifications

Operating Temperature	-25°C to 80°C

Protection Category

IP Rating	IP67

Approvals

Compliance/Certifications	CE, RoHS, REACH, IP67

Dimensions in mm

