1-1375820-3 ACTIVE

CST

TE Internal #: 1-1375820-3

Housing, Receptacle, Crimp, Wire-to-Wire, UL 94V-0, 13 Position, 2.54 mm [.1 in] Centerline, 1 Row, Rectangular Wire & Cable

Connectors & Housings

View on TE.com >



Connectors > Rectangular Connectors > Standard Rectangular Connectors > Receptacle Housing: 2.54mm, 1 Row, CST-100 II



Connector Product Type: Housing

Mating Retention Type: Latch
Connector System: Wire-to-Wire

Contact Retention Within Housing: Without

UL Flammability Rating: UL 94V-0

All Receptacle Housing: 2.54mm, 1 Row, CST-100 II (24)

Features

Product Type Features

Connector Product Type	Housing	
Connector System	Wire-to-Wire	
Sealable	No	
Connector & Contact Terminates To	Wire & Cable	
Configuration Features		
Number of Positions	13	
Number of Rows	1	
Electrical Characteristics		
Operating Voltage	250 VAC	
Contact Features		
Contact Type	Socket	
Contact Retention Within Housing	Without	



Contact Current Rating (Max) Mechanical Attachment Strain Rollief Without Mating Retention Type Latch Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Housing Material Nylon - GF Centerline (Pitch) Dimensions Connector Height 6-6 mm[.26 in] Wire Size 26 22 AWG Connector Length 33.53 mm[1.32 in] Usage Conditions Operating Temperature Range -55 = 105 °C[-67 - 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards Compatible With Agency/Standards Products Glow Wire Rating UL Flammability Rating UL P4V-0 Packaging Features Packaging Method Packaging Quantity 1		
Strain Relief Without Panel Mount Feature Without Mating Retention Type Latch Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Housing Material Nylon - GF Centerline (Pitch) 2.54 mm[.1 in] Dimensions Connector Height 6.6 mm[.26 in] Wire Size 26 - 22 AWG Connector Length 33.53 mm[1.32 in] Usage Conditions Operating Temperature Range -55 - 105 °C[-67 - 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards Compatible With Agency/Standards Products CSA, UL Glow Wire Rating Standard Part - Not Glow Wire UL Flammability Rating UL 94V-0 Packaging Features Packaging Method Package	Contact Current Rating (Max)	7 A
Panel Mount Feature Without Mating Retention Type Latch Connector Mounting Type Cable Mount (Free Hanging) Housing Features Housing Material Nylon GF Centerline (Pitch) 2.54 mm[.1 in] Dimensions Connector Height 6.6 mm[.26 in] Wire Size 26 – 22 AWG Connector Length 33.53 mm[1.32 in] Usage Conditions Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards Compatible With Agency/Standards Products CSA, UL Glow Wire Rating Standard Part - Not Glow Wire UL Flammability Rating UL 94V-0 Packaging Features Packaging Method Package	Mechanical Attachment	
Mating Retention Type Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Housing Material Nylon - GF Centerline (Pitch) 2.54 mm[.1 in] Dimensions Connector Height 6.6 mm[.26 in] Wire Size 26 - 22 AWG Connector Length 33.53 mm[1.32 in] Usage Conditions Operating Temperature Range -55 - 105 °C[-67 - 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards Compatible With Agency/Standards Products Glow Wire Rating UL Planmability Rating UL 94V-0 Packaging Features Packaging Method Package	Strain Relief	Without
Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Housing Material Nylon - GF Centerline (Pitch) 2.54 mm[.1 in] Dimensions Connector Height 6.6 mm[.26 in] Wire Size 26 – 22 AWG Connector Length 33.53 mm[1.32 in] Usage Conditions Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Operating Temperature Range Circuit Application Circuit Application Power & Signal Industry Standards Compatible With Agency/Standards Products Glow Wire Rating UL Plammability Rating UL 94V-0 Packaging Features Packaging Method Package	Panel Mount Feature	Without
Housing Features Housing Material Nylon - GF Centerline (Pitch) 2.54 mm[.1 in] Dimensions Connector Height 6.6 mm[.26 in] Wire Size 26 – 22 AWG Connector Length 33.53 mm[1.32 in] Usage Conditions Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Operating Temperature Range Power & Signal Industry Standards Circuit Application Power & Signal Industry Standards Compatible With Agency/Standards Products CSA, UL Glow Wire Rating Standard Part - Not Glow Wire UL Flammability Rating UL 94V 0 Packaging Features Packaging Method Package	Mating Retention Type	Latch
Housing Material Centerline (Pitch) 2.54 mm[.1 in] Dimensions Connector Height 6.6 mm[.26 in] Wire Size 26 – 22 AWG Connector Length 33.53 mm[1.32 in] Usage Conditions Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards Compatible With Agency/Standards Products Glow Wire Rating UL Plammability Rating Packaging Features Packaging Features Packaging Method Package	Connector Mounting Type	Cable Mount (Free-Hanging)
Centerline (Pitch) Dimensions Connector Height 6.6 mm[.26 in] Wire Size 26 – 22 AWG Connector Length 33.53 mm[1.32 in] Usage Conditions Operating Temperature Range 55 – 105 °C[67 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards Compatible With Agency/Standards Products Glow Wire Rating UL 94V-0 Packaging Features Packaging Method Package	Housing Features	
Dimensions Connector Height 6.6 mm[26 in] Wire Size 26 – 22 AWG Connector Length 33.53 mm[1.32 in] Usage Conditions Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards Compatible With Agency/Standards Products CSA, UL Glow Wire Rating Standard Part - Not Glow Wire UL Flammability Rating UL 94V-0 Packaging Features Packaging Method Package	Housing Material	Nylon - GF
Connector Height Wire Size 26 – 22 AWG Connector Length 33.53 mm[1.32 in] Usage Conditions Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards Compatible With Agency/Standards Products Glow Wire Rating UL Flammability Rating Packaging Features Packaging Method Package	Centerline (Pitch)	2.54 mm[.1 in]
Wire Size 26 – 22 AWG Connector Length 33.53 mm[1.32 in] Usage Conditions Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards Compatible With Agency/Standards Products CSA, UL Glow Wire Rating Standard Part - Not Glow Wire UL Flammability Rating UL 94V-0 Packaging Features Packaging Method Package	Dimensions	
Connector Length 33.53 mm[1.32 in] Usage Conditions Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards Compatible With Agency/Standards Products CSA, UL Glow Wire Rating Standard Part - Not Glow Wire UL Flammability Rating UL 94V-0 Packaging Features Packaging Method Package	Connector Height	6.6 mm[.26 in]
Usage Conditions Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards Compatible With Agency/Standards Products CSA, UL Glow Wire Rating Standard Part - Not Glow Wire UL Flammability Rating UL 94V-0 Packaging Features Packaging Method Package	Wire Size	26 – 22 AWG
Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards Compatible With Agency/Standards Products CSA, UL Glow Wire Rating Standard Part - Not Glow Wire UL Flammability Rating UL 94V-0 Packaging Features Packaging Method Package	Connector Length	33.53 mm[1.32 in]
Operation/Application Circuit Application Power & Signal Industry Standards Compatible With Agency/Standards Products CSA, UL Glow Wire Rating Standard Part - Not Glow Wire UL Flammability Rating UL 94V-0 Packaging Features Packaging Method Package	Usage Conditions	
Circuit Application Power & Signal Industry Standards Compatible With Agency/Standards Products CSA, UL Glow Wire Rating Standard Part - Not Glow Wire UL Flammability Rating UL 94V-0 Packaging Features Packaging Method Package	Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Industry Standards Compatible With Agency/Standards Products CSA, UL Glow Wire Rating Standard Part - Not Glow Wire UL Flammability Rating UL 94V-0 Packaging Features Packaging Method Package	Operation/Application	
Compatible With Agency/Standards Products Glow Wire Rating UL Flammability Rating Packaging Features Packaging Method CSA, UL Standard Part - Not Glow Wire UL 94V-0 Packaging Features	Circuit Application	Power & Signal
Glow Wire Rating UL Flammability Rating UL 94V-0 Packaging Features Packaging Method Package	Industry Standards	
UL Flammability Rating Packaging Features Packaging Method Package	Compatible With Agency/Standards Products	CSA, UL
Packaging Features Packaging Method Package	Glow Wire Rating	Standard Part - Not Glow Wire
Packaging Method Package	UL Flammability Rating	UL 94V-0
	Packaging Features	
Packaging Quantity 1	Packaging Method	Package
	Packaging Quantity	1

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247)



Candidate List Declared Against: JAN 2025
(247)
Does not contain REACH SVHC

Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per
	homogenous material. Also BFR/CFR/PVC
	Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts













Customers Also Bought















Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1375820-3_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-1375820-3_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1375820-3_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English

Agency Approvals

CSA Certificate

English