

SKINDICHT® BL-M ATEX

SKINDICHT® BL-M ATEX, nickel plated brass blind plugs, high degree of protection & cold impact resistance, for mobile applications in offshore



Temperature-resistant



Reliability



Robust



Corrosion-resistant

Benefits

High degree of protection
Cold impact resistance

Application range

Equipment group II / Category 2G+1D
Devices, machines and apparatus
For mobile applications in offshore and marine industries
Chemical and petrochemical industry

Product Make-up

Metric connection thread acc. to DIN EN 60423
Basis for technical information DIN IEC 62444

Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC000032

ETIM 5.0 Class-Description: Plug for cable screw gland

Last Update (10.11.2018)

©2018 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

SKINDICHT® BL-M ATEX

Classification ETIM 6:	ETIM 6.0 Class-ID: EC000032 ETIM 6.0 Class-Description: Plug for cable screw gland
Certifications:	CE 0637 Ex II 2G Ex eb IIC Ex II 1D Ex ta IIIC IECEX IBE 13.0029X
Material:	Body: nickel-plated brass O-ring: NBR
Tests:	DIN EN 60079-0 DIN EN 60079-7 DIN EN 60079-31
Protection rating:	IP 68 - 5 bar
Temperature range:	-30°C to +90°C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.

SKINDICHT® BL-M ATEX

Article number	Article designation / size	SW wrench size mm	Thread length, D (mm)	PL_DURCHMESSERAUSSE N	Outer Ø (mm)
SKINDICHT® BL-M ATEX					
52103103	M 12 x 1,5	16	5	17.8	17.8
52103113	M 16 x 1,5	20	5	22	22.0
52103123	M 20 x 1,5	24	6	26.4	26.4
52103133	M 25 x 1,5	29	7	31.9	31.9
52103143	M 32 x 1,5	36	8	39.6	39.6
52103153	M 40 x 1,5	45	8	49.5	49.5
52103163	M 50 x 1,5	54	9	59	59.0
52103173	M 63 x 1,5	67	10	73.5	73.5

Last Update (10.11.2018)

©2018 Lapp Group - Technical changes reserved

Product Management www.lappkabel.deYou can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16