

### product type designation

product description

### IE FC M12 Cable Connector PRO (PROFINET)

M12 connector with socket insert with high protection class, 8-pole, X-coded

IE FC M12 Cable Connector PRO 4x 2 M12 plug-in connectors that can be assembled in the field (X-coded); 8-pole; metal enclosure; FC quick-connect technology; Female contact insert; 1 pack=8 units.



### suitability for use

For connecting electrical cables to SCALANCE W (M12 gigabit interface) for fast assembly with the FastConnect system

### transfer rate

transfer rate / for Industrial Ethernet

10 Mbit/s, 100 Mbit/s, 1000 Mbit/s, 10000 Mbit/s

### interfaces

number of electrical connections

- for Industrial Ethernet FC TP cables
- for network components or terminal equipment

8

1

type of electrical connection

- for Industrial Ethernet FC TP cables
- for network components or terminal equipment

integrated cut-and-clamp contacts for 8-wire TP FC installation cable AWG24 M12 connector (X-coded)

type of electrical connection / FastConnect

Yes

### mechanical data

material / of the enclosure

metal

locking mechanism design

Screwed joint

tightening torque / for M12 round connector / maximum

0.6 N·m

connector coding / of the M12 circular connector

X

### design, dimensions and weights

type of cable outlet

180° cable outlet

width

16.8 mm

height

16.8 mm

depth

49 mm

net weight

40 g

connectable cable cross-section

6.5 ... 8 mm

connectable conductor cross-section

0.21 ... 0.33 mm<sup>2</sup>

### ambient conditions

ambient temperature

- during operation
- during storage
- during transport

-40 ... +85 °C

-40 ... +85 °C

-40 ... +85 °C

chemical resistance

- to water

resistant

protection class IP

IP65/67

### product features, product functions, product components / general

product feature

- PoE capability
- PoE+capability
- silicon-free

Yes

Yes

Yes

product component	
<ul style="list-style-type: none"> <li>• strain relief</li> </ul>	Yes
<b>standards, specifications, approvals</b>	
certificate of suitability	
<ul style="list-style-type: none"> <li>• RoHS conformity</li> <li>• UL approval</li> <li>• cULus approval</li> <li>• railway application in accordance with EN 50155</li> <li>• fire protection in accordance with EN 45545-2</li> </ul>	Yes Yes Yes Yes Yes
standard for structured cabling	Cat6A
<b>further information / internet links</b>	
internet link	
<ul style="list-style-type: none"> <li>• to web page: selection aid TIA Selection Tool</li> <li>• to website: Industrial communication</li> <li>• to website: Industry Mall</li> <li>• to website: Information and Download Center</li> <li>• to website: Selection guide for cables and connectors</li> <li>• to website: Image database</li> <li>• to website: CAx-Download-Manager</li> <li>• to website: Industry Online Support</li> </ul>	<a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a> <a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a> <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a> <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> <a href="https://sie.ag/2QdlxcP">https://sie.ag/2QdlxcP</a> <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a> <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>

**last modified:**

8/29/2023 