



# TECHNICAL SPECIFICATION

Technical Service Department,  
JSP Ltd., Worsham Mill, Minster  
Lovell, Oxford, OX29 0TA  
Tel.: 01993 824000  
Fax: 01993 824422

## MkVII Industrial Safety Helmet C/W Sureslide Retractablespec

### Conformity:

**Helmet** – Conforms to EN 397 & EN 50365:2002.

EC Certificate Number 0279, issued by BSi Product Certification.

**Sureslide** – Conforms to EN 166.

EC Certificate Number 52231, to be issued by BSi Product Certification.

### Sureslide Performance:

Offers protection against low energy high-speed particles at 45 m/s (101 mph). The optical qualities of the lens comply with the requirements of optical class 1 (highest).

**Markings: EN166 1.F**

### Size & Weights:

530 – 640mm (6½ - 7⅞)

Webbing Harness 0.425Kg

Wheel Ratchet Harness 0.475  
(weight is approx.)

### Limitations Of Use:

Protection will only be offered if the helmet is fitted correctly. Any Helmet subjected to severe impact should be replaced immediately. If the Eyeshield becomes scratched or damaged it should be replaced. Do not apply paint, solvents, adhesives or self-adhesive labels, except in accordance with instructions from the manufacturer. The harness, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the helmet and seek medical advice. The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer.

### Notes:

- i. *The helmet is available vented or unvented. With a vented shell, it does not meet the requirements of the electrical insulation option within the standard.*



Image Shows Vented Version

### Instructions For Use:

Fit helmet on head and fasten strap to ensure correct fit. Slide eyeshield down and fit across the bridge of the nose as required for a comfortable fit. For adequate protection this helmet must be worn with the peak facing forward and be adjusted to the size of the users head. Ensure that the eyeshield is in place over the eyes before entering the hazard area.

### Materials:

Shell: HDPE  
Webbing Harness: LDPE Strap  
LDPE Harness Clips  
Terylene Webbing Straps  
Wheel Ratchet LDPE Strap  
Harness: LDPE Harness Clips  
Terylene Webbing Straps  
Nylon Ratchet Assembly With Steel Spring  
Eyeshield: Polycarbonate Sheet C/W Polycarbonate & PVC Nose Piece

Both Harness types come with 'Nomaz' Style Leatherette Sweatband

Manufacturing For Safety