Part No.		2		3		4		5 6	
		Material Surface	Screw (quantity)	2 Washer (quantity)	Spring washer (quantity)	4 Nut (quantity)	Package	Notice	
	F-GSCH1/5-K1092	Steel	2	4 max. 10000	2	2 max. 5000	in pairs bulk packed	Packed together in a bag Individually packed in bags	
A	F-GSCH1/5-K1092S		zinc plated with tension control fluid		max. 5000				
F-GSCH1/5-K1092SN		Steel tin plated	2	4	2	2	in pairs	Packed together in a bag	
		Length of engagement							
		Length of engagement							
		Length of engagement						-	
							SW4.5	-	
			.31	8		1.5	SW4.5	RoHS compliant by exemption	
			.31	•	S INFORMATION THAT IS PROP CALE MEASUREMENTS W TOLERANCE ACC. T	PRIETARY TO MOLEX ELECTRO	<u> </u>	ROHS compliant by exemption	

1731120245 F-GSCH1/5-K1	
	092
1731120600 F-GSCH1/5-K10	92SN

SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION								
F = 0		nm	2:1	MEASUREMENTS WITHOUT TOLERANCE ACC. TO ISO 2768-m	Т		mo	lex	
$ \begin{array}{c} $				CURRENT REVISION DRWN: DRAWN BY APPR: APPR BY	ON MTeubel gkrimshandl	15-02-2019 18-02-2019	FCT-Female	Screw Lock	
= 0	2 24130		130	INITIAL REVISION		PRODUCT CUSTOMER DRAWING			
⟨c/ = 0	1	27	100	DRWN: DRAWN BY	sschref	07-11-2007	MATERIAL NUMBER		REVISION
⊠ = 0	REV.			MTeubel 18-03-2014		see table			
= 0	REPLAC	EMENT FOR:		THIRD ANGLE PROJECTION	DRAWING A4-SIZE		DOCUMENT NUMBER F-GSCH-K1092	CUSTOMER GENERAL MARKET	SHEET NUMBER 1 OF 1