


Geberit Mapress Carbon Steel pipe cross, reduced



Example image



APPLICATION PURPOSES

- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For district heating water $\leq 120\text{ }^{\circ}\text{C}$
- For compressed air (oil purity class 3)
- For technical building systems, industry and shipbuilding

CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed
- Outside zinc-plated
- Seal ring made of CIIR, black
- Pressing socket with transparent protection plug

TECHNICAL DATA

Product material	Non-alloy steel 1.0034 E195 (EN 10305)
------------------	--

Art. no.	DN	d, $\varnothing$ mm	d1, $\varnothing$ mm	arc $^{\circ}$	L cm	L1 cm	I cm	I1 cm	Z cm	Z1 cm
21121	40 / 25	42	28	90	11.4	11.6	5.7	5.8	2.7	3.5
21122	50 / 25	54	28	90	13.8	12.8	6.9	6.4	3.4	4.1
21123	50 / 32	54	35	90	13.8	13.6	6.9	6.8	3.4	4.2
21127	65 / 25	76.1	28	90	23	15.8	11.5	7.9	6.2	5.6
21128	65 / 32	76.1	35	90	23	16.2	11.5	8.1	6.2	5.5

Art. no.	DN	d, ø mm	d1, ø mm	arc °	L cm	L1 cm	I cm	I1 cm	Z cm	Z1 cm
21130	80 / 25	88.9	28	90	26	17.4	13	8.7	7	6.4
21131	80 / 32	88.9	35	90	26	18	13	9	7	6.4
21133	100 / 25	108	28	90	31	20	15.5	10	8	7.7
21134	100 / 32	108	35	90	31	20	15.5	10	8	7.4