ML10/13.SF



Products Low Voltage Products and Systems Connection Devices Terminal Blocks SNA Series

General Information

Extended Product Type: ML10/13.SF

Product ID: 1SNA199095R1300 EAN: 3472591990959

Catalog Description: ML10/13.SF Screw Clamp Terminal Blocks - For 6.3×25 and 6.3×32 fuses - Black Long Description:

Protect your circuits with 6.35x25.4 and 6.35x32 fuse terminal blocks (fuse not supplied wit

h terminal blocks).

Additional Information

CSA Cortification ISND161066A0201 Cotor: Black Connecting Capacity Main Circuit LUCSA: Screw Clamp / Rigid 1x 22 10 AW/G Connecting Capacity Main Circuit Screw Clamp / Rigid 1x 0.5 10 mm² Connecting Capacity Main Circuit: Screw Clamp / Rigid 1x 0.5 10 mm² Connection Type: Screw Clamp Control Control Control France (FR) Customs Tariff Number: 85361050 Data Sheet, Technical Information: 15NC160019C0202 Declaration of Conformity - CE 15ND225016U1000 EAC Certificate: 15ND161009A1100 EAN 3472591990959 ETIM 4: EC0000899 - Fuse terminal block ETIM 5: EC0000899 - Fuse terminal block ETIM 6: EC0000899 - Fuse terminal block ETIM 6: EC0000899 - Fuse terminal block Environmental Information: 15ND220021E1002 Rammability According to U.94: V0 Function: Level 0 - Information enabled Industrial To Criffication Lovel: 0 Instructions and Manuals: 15NC160019C0202 Maximum Operating Voltage UUCSA:	ABB Industrial IT Suite:	Control IT
Connecting Capacity Main Circuit ULCSA Screw Clamp / Rigid 1x 22 10 AW/G Connecting Capacity ULCSA: Screw Clamp / Rigid 22 10 AW/G Connecting Capacity Main Circuit: Screw Clamp / Rigid 1x 0.5 10 mm² Connecting Capacity Main Circuit: Screw Clamp / Rigid 1x 0.5 16 mm² Connection Type: Screw clamp Country of Origin: France (FR) Country of Origin: France (FR) Country of Origin: 15NC160019C0202 Data Sheet, Technical Information: 15NC160019C0202 Eccloration of Conformity - CE 15ND25016U1000 EAC 3472591990959 ETIM 4: EC000899 - Fuse terminal block ETIM 5: EC000899 - Fuse terminal block ETIM 6: EC000899 - Fuse terminal block Environmental Information: 15ND220021E1002 Flammability According to UL94: V0 Fuse As Guige Type: A6 Ill Publishing Status: Level 0 - Information enabled Induction: ML 10/13.SF Screw Clamp Terminal Blocks - For 6.3 x 25 and 6.3 x 32 fuses - Black Maximum Operating Voltage ULCSA: Main Circuit 600 V	CSA Certificate:	1SND161066A0201
Connecting Capacity McSA: Screw Clamp / Rigid 22 10 AWG Stranded 10 AWG Connecting Capacity Main Circuit: Screw Clamp / Rigid 1x 0.5 16 mm² Connection Type: Screw clamp / Rigid 1x 0.5 16 mm² Connection Type: Screw clamp Country of Origin: France (FR) Customs Tariff Number: 85361050 Data Sheet, Tochnical Information: 18NC160019C0202 Declaration of Conformity-CE 18ND161009A1100 EAC Certificate: 18ND161009A1100 EAN 3472591990959 ETIM 4: EC0000899 - Fuse terminal block ETIM 5: EC0000899 - Fuse terminal block ETIM 6: EC0000899 - Fuse terminal block Environmental Information: 18ND220021E1002 Rammability According to UL94: V0 Function: Fuse Gauge Type: A6 ITPublishing Status: Level 0 - Information enabled Instructions and Manuals: 18NC160019C0202 Invoice Description: ML10/13.SF Screw Clamp Terminal Blocks - For 6.3 x 25 and 6.3 x 32 fuses - Black Maximum Operating Voltage UL/SA: Main Circuit 600 V	Color:	Black
Connecting Capacity Main Circuit: Screw Clamp / Flexible 1x 0.5 10 mm² Screw Clamp / Rigid 1x 0.5 16 mm² Connection Type: Screw Clamp / Rigid 1x 0.5 16 mm² Connection Type: Screw clamp Country of Origin: France (FR) Customs Tariff Number: 85361050 Data Sheet, Technical Information: 1SNC160019C0202 Declaration of Conformity - CE: 1SND161009A1100 EAC Certificate: 1SND161009A1100 EAN: 3472591990959 ETIM 4: EC000899 - Fuse terminal block ETIM 5: EC000899 - Fuse terminal block ETIM 6: EC000899 - Fuse terminal block Invision 1. As	Connecting Capacity Main Circuit UL/CSA:	Screw Clamp / Rigid 1x 22 10 AWG
Connection Type: Screw Clamp / Rigid 1x 0.5 16 mm² Country of Origin: France (FR) Customs Tariff Number: 85361050 Data Sheet, Technical Information: 1 SNC160019C0202 Declaration of Conformity - CE 1 SND161009A1100 EAC Certificate: 1 SND161009A1100 EAN 3472591990959 ETIM 4: EC000899 - Fuse terminal block ETIM 5: EC000899 - Fuse terminal block ETIM 6: EC000899 - Fuse terminal block Environmental Information: 1 SND220021E1002 Ramability According to UL94: V0 Runction: Fuse Gauge Type: A6 Ill Tublishing Status: Level 0 - Information enabled Industrial IT Certification Level: 0 Instructions and Manuals: 1 SNC160019C0202 Invoice Description: ML10/13.SF Screw Clamp Terminal Blocks - For 6.3 x 25 and 6.3 x 32 fuses - Black Maximum Operating Voltage UL/CSA: Main Circuit 600 V Minimum Order Quantity: 20 piece Mumber of Connections: 1 Say X.5 mm Mounting Rail) acc. to IEC 60715	Connecting Capacity UL/CSA:	, e
Country of Origin: France (FR) Customs Tariff Number: 85361050 Data Sheet, Technical Information: 1SNC160019C0202 Declaration of Conformity - CE: 1SND161009A1100 EAC Certificate: 1SND161009A1100 EAN: 3472591990959 ETIM 4: EC000899 - Fuse terminal block ETIM 5: EC000899 - Fuse terminal block ETIM 6: EC000899 - Fuse terminal block Environmental Information: 1SND220021E1002 Rammability According to UL94: V0 Fuse Guge Type: A6 Level 0 - Information enabled Industrial IT Certification Level: 0 Instructions and Manuals: 1SNC160019C0202 Invoice Description: ML10/13.SF Screw Clamp Terminal Blocks - For 6.3 x 25 and 6.3 x 32 fuses - Black Maximum Order Quantity: 20 piece Mounting on DIN Rail: G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 Number of Connections: 2 Number of Levels: 1 Chiget Classifica	Connecting Capacity Main Circuit:	'
Customs Tariff Number: 85361050 Data Sheet, Technical Information: 1SNC160019C0202 Declaration of Conformity - CE 1SND225016U1000 EAC Certificate: 1SND161009A1100 EAN: 3472591990959 ETIM 4: EC000899 - Fuse terminal block ETIM 5: EC000899 - Fuse terminal block ETIM 6: EC000899 - Fuse terminal block Environmental Information: 1SND220021E1002 Rammability According to UL94: V0 Fuse 46 Iff Publishing Status: Level 0 - Information enabled Industrial IT Certification Level: 0 Instructions and Manuals: 1SNC160019C0202 Invoice Description: ML10/13.SF Screw Clamp Terminal Blocks - For 6.3 x 25 and 6.3 x 32 fuses - Black Maximum Operating Voltage UL/CSA: Main Circuit 600 V Minimum Order Quantity: 20 piece Mounting on DIN Rail: G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715	Connection Type:	Screw clamp
Data Sheet, Technical Information: 1SNC160019C0202 Declaration of Conformity - CE 1SND25016U1000 EAC Certificate: 1SND161009A1100 EAN: 3472591990959 ETIM 4: EC000899 - Fuse terminal block ETIM 5: EC000899 - Fuse terminal block ETIM 6: EC000899 - Fuse terminal block Environmental Information: 1SND220021E1002 Rammability According to UL94: V0 Function: Fuse Gauge Type: A6 Industrial IT Certification Level: 0 Instructions and Manuals: 1SNC160019C0202 Invoice Description: ML10/13.SF Screw Clamp Terminal Blocks - For 6.3 x 25 and 6.3 x 32 fuses - Black Maximum Operating Voltage UL/CSA: Main Circuit 600 V Minimum Order Quantity: 20 piece Mounting on DIN Rail: G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 Number of Connections: 2 Number of Levels: 1 Otject Classification Code: X Order Multiple: 20 piece Package Le	Country of Origin:	France (FR)
Declaration of Conformity - CE: 1SND225016U1000 EAC Cortificate: 1SND161009A1100 EAN: 3472591990959 ETIM 4: EC000899 - Fuse terminal block ETIM 5: EC000899 - Fuse terminal block ETIM 6: EC000899 - Fuse terminal block Environmental Information: 1SND220021E1002 Fammability According to UL94: V0 Function: Fuse Gauge Type: A6 Industrial IT Cortification Level: 0 Instructions and Manuals: 1SNC160019C0202 Invoice Description: ML10/13.SF Screw Clamp Terminal Blocks - For 6.3 x 25 and 6.3 x 32 fuses - Black Maximum Operating Voltage UL/CSA: Main Circuit 600 V Minimum Order Quantity: 20 piece Mounting on DIN Rail: G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715	Customs Tariff Number:	85361050
EAC Certificate: 1SND161009A1100 EAN: 3472591990959 ETIM 4: EC000899 - Fuse terminal block ETIM 5: EC000899 - Fuse terminal block ETIM 6: EC000899 - Fuse terminal block Environmental Information: 1SND220021E1002 Rammability According to UL94: V0 Function: Fuse Gauge Type: A6 Iff Publishing Status: Level 0 - Information enabled Industrial IT Certification Level: 0 Instructions and Manuals: 1SNC160019C0202 Invoice Description: ML10/13.SF Screw Clamp Terminal Blocks - For 6.3 x 25 and 6.3 x 32 fuses - Black Maximum Operating Voltage UL/CSA: Main Circuit 600 V Minimum Order Quantity: 20 piece Mounting on DIN Pail: G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715	Data Sheet, Technical Information:	1SNC160019C0202
EAN: 3472591990959 ETIM 4: EC000899 - Fuse terminal block ETIM 5: EC000899 - Fuse terminal block ETIM 6: EC000899 - Fuse terminal block Environmental Information: 1SND220021E1002 Rammability According to UL94: V0 Function: Fuse Gauge Type: A6 ITT Publishing Status: Level 0 - Information enabled Industrial IT Certification Level: 0 Instructions and Manuals: 1SNC160019C0202 Invoice Description: Mt. 10/13.SF Screw Clamp Terminal Blocks - For 6.3 x 25 and 6.3 x 32 fuses - Black Maximum Operating Voltage UL/CSA: Main Circuit 600 V Minimum Order Quantity: 20 piece Mounting on DIN Rail: G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715	Declaration of Conformity - CE:	1SND225016U1000
ETIM 4: EC000899 - Fuse terminal block ETIM 5: EC000899 - Fuse terminal block ETIM 6: EC000899 - Fuse terminal block Environmental Information: 1SND220021E1002 Rammability According to UL94: V0 Function: Fuse Gauge Type: A6 IIT publishing Status: Level 0 - Information enabled Industrial IT Certification Level: 0 Instructions and Manuals: 1SNC160019C0202 Invoice Description: ML 10/13.SF Screw Clamp Terminal Blocks - For 6.3 x 25 and 6.3 x 32 fuses - Black Maximum Operating Voltage UL/CSA: Main Circuit 600 V Minimum Order Quantity: 20 piece Mounting on DIN Rail: G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715	EAC Certificate:	1SND161009A1100
ETIM 5: EC000899 - Fuse terminal block ETIM 6: EC000899 - Fuse terminal block Environmental Information: 1SND220021E1002 Rammability According to UL94: V0 Function: Fuse Gauge Type: A6 IIT Publishing Status: Level 0 - Information enabled Industrial IT Certification Level: 0 Instructions and Manuals: 1SNC160019C0202 Invoice Description: ML10/13.SF Screw Clamp Terminal Blocks - For 6.3 x 25 and 6.3 x 32 fuses - Black Maximum Operating Voltage UL/CSA: Main Circuit 600 V Minimum Order Quantity: 20 piece Mounting on DIN Rail: G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715	EAN:	3472591990959
ETIM 6: EC000899 - Fuse terminal block Environmental Information: 1SND220021E1002 Flammability According to UL94: V0 Function: Fuse Gauge Type: A6 IIT Publishing Status: Level 0 - Information enabled Industrial IT Certification Level: 0 Instructions and Manuals: 1SNC160019C0202 Invoice Description: ML10/13.SF Screw Clamp Terminal Blocks - For 6.3 x 25 and 6.3 x 32 fuses - Black Maximum Operating Voltage UL/CSA: Main Circuit 600 V Minimum Order Quantity: 20 piece Mounting on DIN Rail: G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715	ETIM 4:	EC000899 - Fuse terminal block
Environmental Information: 1SND220021E1002 Flammability According to UL94: V0 Function: Fuse Gauge Type: A6 IIT Publishing Status: Level 0 - Information enabled Industrial IT Certification Level: 0 Instructions and Manuals: 1SNC160019C0202 Invoice Description: ML10/13.SF Screw Clamp Terminal Blocks - For 6.3 x 25 and 6.3 x 32 fuses - Black Maximum Operating Voltage UL/CSA: Main Circuit 600 V Minimum Order Quantity: 20 piece Mounting on DIN Rail: G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715	ETIM 5:	EC000899 - Fuse terminal block
Flammability According to UL94: V0 Function: Fuse Gauge Type: A6 IIT Publishing Status: Level 0 - Information enabled Industrial IT Certification Level: 0 Instructions and Manuals: 1SNC160019C0202 Invoice Description: ML10/13.SF Screw Clamp Terminal Blocks - For 6.3 x 25 and 6.3 x 32 fuses - Black Maximum Operating Voltage UL/CSA: Main Circuit 600 V Minimum Order Quantity: 20 piece Mounting on DIN Rail: G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715	ETIM 6:	EC000899 - Fuse terminal block
Function: Fuse Gauge Type: A6 IIT Publishing Status: Level 0 - Information enabled Industrial IT Certification Level: 0 Instructions and Manuals: ISNC160019C0202 Invoice Description: ML10/13.SF Screw Clamp Terminal Blocks - For 6.3 x 25 and 6.3 x 32 fuses - Black Maximum Operating Voltage UL/CSA: Main Circuit 600 V Minimum Order Quantity: 20 piece Mounting on DIN Rail: G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 Number of Connections: 2 Number of Connections: 2 Number of Levels: 1 Object Classification Code: X Order Multiple: 20 piece Package Level 1 Gross Weight: 1.02 kg	Environmental Information:	1SND220021E1002
Gauge Type: A6 IIT Publishing Status: Level 0 - Information enabled Industrial IT Certification Level: 0 Instructions and Manuals: 1SNC160019C0202 Invoice Description: ML10/13.SF Screw Clamp Terminal Blocks - For 6.3 x 25 and 6.3 x 32 fuses - Black Maximum Operating Voltage UL/CSA: Main Circuit 600 V Minimum Order Quantity: 20 piece Mounting on DIN Rail: G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715	Flammability According to UL94:	V0
IIT Publishing Status: Industrial IT Certification Level: Instructions and Manuals: ISNC160019C0202 Invoice Description: ML10/13.SF Screw Clamp Terminal Blocks - For 6.3 x 25 and 6.3 x 32 fuses - Black Maximum Operating Voltage UL/CSA: Main Circuit 600 V Minimum Order Quantity: 20 piece Mounting on DIN Rail: G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 Number of Connections: 2 Number of Levels: 1 Object Classification Code: X Order Multiple: 20 piece Package Level 1 EAN: 3472591990959 Package Level 1 Gross Weight: 1.02 kg	Function:	Fuse
Industrial IT Certification Level: Instructions and Manuals: ISNC160019C0202 Invoice Description: ML10/13.SF Screw Clamp Terminal Blocks - For 6.3 x 25 and 6.3 x 32 fuses - Black Maximum Operating Voltage UL/CSA: Main Circuit 600 V Minimum Order Quantity: 20 piece Mounting on DIN Rail: G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 Number of Connections: 2 Number of Levels: 1 Object Classification Code: X Order Multiple: 20 piece Package Level 1 EAN: 3472591990959 Package Level 1 Gross Weight: 1.02 kg	Gauge Type:	A6
Instructions and Manuals: ISNC160019C0202 Invoice Description: ML10/13.SF Screw Clamp Terminal Blocks - For 6.3 x 25 and 6.3 x 32 fuses - Black Maximum Operating Voltage UL/CSA: Main Circuit 600 V Minimum Order Quantity: 20 piece Mounting on DIN Rail: G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 Number of Connections: 2 Number of Levels: 1 Object Classification Code: X Order Multiple: 20 piece Package Level 1 EAN: 3472591990959 Package Level 1 Gross Weight: 1.02 kg	IIT Publishing Status:	Level 0 - Information enabled
Invoice Description: ML10/13.SF Screw Clamp Terminal Blocks - For 6.3 x 25 and 6.3 x 32 fuses - Black Maximum Operating Voltage UL/CSA: Main Circuit 600 V Minimum Order Quantity: 20 piece Mounting on DIN Rail: G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715	Industrial IT Certification Level:	0
Maximum Operating Voltage UL/CSA:Main Circuit 600 VMinimum Order Quantity:20 pieceMounting on DIN Rail:G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715Number of Connections:2Number of Levels:1Object Classification Code:XOrder Multiple:20 piecePackage Level 1 EAN:3472591990959Package Level 1 Gross Weight:1.02 kg	Instructions and Manuals:	1SNC160019C0202
Minimum Order Quantity: 20 piece Mounting on DIN Rail: G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715	Invoice Description:	ML10/13.SF Screw Clamp Terminal Blocks - For 6.3 x 25 and 6.3 x 32 fuses - Black
Mounting on DIN Rail: G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 Number of Connections: 2 Number of Levels: 1 Object Classification Code: X Order Multiple: 20 piece Package Level 1 EAN: 3472591990959 Package Level 1 Gross Weight: 1.02 kg	Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 Number of Connections: 2 Number of Levels: 1 Object Classification Code: X Order Multiple: 20 piece Package Level 1 EAN: 3472591990959 Package Level 1 Gross Weight: 1.02 kg	Minimum Order Quantity:	20 piece
Number of Levels: 1 Object Classification Code: X Order Multiple: 20 piece Package Level 1 EAN: 3472591990959 Package Level 1 Gross Weight: 1.02 kg	Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Object Classification Code: X Order Multiple: 20 piece Package Level 1 EAN: 3472591990959 Package Level 1 Gross Weight: 1.02 kg	Number of Connections:	2
Order Multiple: 20 piece Package Level 1 EAN: 3472591990959 Package Level 1 Gross Weight: 1.02 kg	Number of Levels:	1
Package Level 1 EAN: 3472591990959 Package Level 1 Gross Weight: 1.02 kg	Object Classification Code:	X
Package Level 1 Gross Weight: 1.02 kg	Order Multiple:	20 piece
	Package Level 1 EAN:	3472591990959
Package I evel 1 Height: 71 mm	Package Level 1 Gross Weight:	1.02 kg
r donage Euror i risigit. / 1 IIIIII	Package Level 1 Height:	71 mm

Package Level 1 Length:	155 mm
Package Level 1 Units:	20 piece
Package Level 1 Width:	172 mm
Package Level 2 Gross Weight:	10.700 kg
Package Level 2 Height:	300 mm
Package Level 2 Length:	500 mm
Package Level 2 Units:	200 piece
Package Level 2 Width:	300 mm
Package Level 3 Units:	4800 piece
Pollution Degree:	3
Product Main Type:	ML10/13.SF
Product Name:	Terminal block
Product Net Depth:	58 mm
Product Net Height:	85 mm
Product Net Weight:	51 g
Product Net Width:	13 mm
Product Packing Type:	Вох
RMRS Certificate:	1SND161007A1101
Rated Cross-Section:	10 mm²
Rated Current (I _n):	Main Circuit 16 A
Rated Impulse Withstand Voltage (U _{imp}):	8000 V
Rated Voltage (U _r):	800 V
Recommended Screw Driver:	5.5 mm
RoHS Date:	20050518
RoHS Information:	1SND230023F0208
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Selling Unit of Measure:	piece
Short Description:	black Screw Clamp Terminal Blocks ML10/13.SF
Spacing:	13 mm
Sub-Function:	For 6.3x25 and 6.3x32 Fuses
Sub-Function 3:	For 6.3x25 and 6.3x32 Fuses
Tightening Torque:	acc. IEC 60947-1 1.2 N·m Manufacturer 1.4 N·m
Wire Stripping Length:	12.0 mm
cUL Certificate:	1SND161000A0203

