



Canalis - tap-off unit - 16A - 3L+N +PE - without protection

KBC16DCB40

١	J	1	а	ı	r

Range	Canalis
Product or component type	Tap-off unit
Device short name	KBC
Product compatibility	KBB KBA
Device application	Lighting
Range compatibility	KBA busbar trunking KBB busbar trunking

Complementary

[Ue] rated operational voltage	230240 V
[Ui] rated insulation voltage	690 V
[le] rated operational current	16 A at 35 °C
Network frequency	50/60 Hz
Protection type	Without protection
Busbar trunking polarity	L2 + L1 + L3 + PE
Tap-off unit polarity	3L+N+PE
Tap-off unit connector type	With fixed polarity
Standards	EN/IEC 60439-2 EN/IEC 61439-6
Width	205 mm
Depth	38 mm
Height	68 mm
Colour	Cream (RAL 9001)
Net weight	90 g

Environment

IP degree of protection	IP55 conforming to EN/IEC 60529
-------------------------	---------------------------------

Packing Units

Unit Type of Package 1	PCE

Number of Units in Package 1	1
Package 1 Weight	189.0 g
Package 1 Height	8 cm
Package 1 width	8 cm
Package 1 Length	18 cm
Unit Type of Package 2	P06
Number of Units in Package 2	144
Package 2 Weight	37.588 kg
Package 2 Height	74 cm
Package 2 width	80 cm
Package 2 Length	60 cm
Unit Type of Package 3	S03
Number of Units in Package 3	18
Package 3 Weight	3.899 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration

Contractual	warranty

Halogen content performance

RoHS exemption information

China RoHS Regulation

Environmental Disclosure

Mercury free

WEEE

PVC free

Warranty	18 months
----------	-----------

Product out of China RoHS scope. Substance declaration for your information

The product must be disposed on European Union markets following specific waste collection and

Yes

Yes

Yes

China RoHS declaration

Product Environmental Profile

never end up in rubbish bins

Halogen free plastic parts product

Product data sheet

KBC16DCB40

Dimension Drawings



