



Cut protection

# KRYTECH 600

Low risk - ISO B

Cut, Grip and Skin protection for very oily environments



**GRIP & PROOF**  
TECHNOLOGY

CUT PROTECTION  
**LEVEL B**

EN388



4X42B

EN407



X1XXXX



GR

ISO 18889

CATEGORY 3

ISO 13997:

DEXTERITY



0334

6 N

EN ISO 21420:  
5/5



## SPECIFIC ADVANTAGES



### Comfort

- Unbeatable fingertip sensitivity



### Durability

- Excellent abrasion resistance due to the nitrile coating



### Productivity

- Grip and Proof coating ensures an excellent grip in oily environment. It also reduces muscle strain and boost productivity



### Skin protection

- Free of harmful substances: OEKO-TEX® STANDARD 100, DMF Free
- Oilproof, it repels oil penetration and reduce dermatitis



### Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting



### Care for the environment

- 95 gr CO<sub>2</sub> of carbon footprint reduction (1)
- Recycled material in the glove: 20 %
- Recycled material in the liner: 37 %
- Optimised individual packaging to limit plastic waste
- Recycled material in the packaging: 30 %

## INDUSTRIES

- Automotive/mechanical industry
- Mechanical industry
- Other industries

## APPLICATIONS

- Cutting and stamping metal
- Maintenance in wet environments (water, oil, greases, hydrocarbons)
- Precision assembly
- Glass working
- Machine maintenance
- Maintenance in wet environments
- Bodywork assembly
- Handling and sorting small, sharp parts
- Handling oily mechanical parts
- Machining parts using cutting oil



Cut protection

# KRYTECH 600

Low risk - ISO B

## LEGENDS

EN388

### MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

4 X 4 2 B

0-4 0-5 0-4 0-4 A-F P

Impact protection (optional)

Cut resistance according to ISO 13997

Puncture resistance

Tear resistance

Blade cut resistance

Abrasion resistance

EN407

### THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)

X 1 X X X X

0-4 0-4 0-4 0-4 0-4 0-4

Resistance to large quantities of molten metal

Small splashes of molten metal

Radiant heat resistant

Convective heat resistance

Contact heat resistance

Limited flame spread



### PROTECTION FROM PESTICIDES

GR: Re-entry tasks

ISO 18889

## PRODUCT DETAILS

Interior finish	Seamless textile support from HDPE fibres
Gauge	13
Exterior finish	Fully-coated
Material	Nitrile GRIP&PROOF coating
Cuff characteristic	Knitted Cuff
Colour.s	Black Grey
European sizes	7 8 9 10

## LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/bag 48 pairs/carton
-----------	---

## LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/01/19/0175 ext 02/01/19 updated 03-08/12/2023
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

(1) Measurement based on life cycle analysis, carried out by Glimpact, an independent third party, according to the European PEF method adopted by European Commission, based a pair of Grip&Proof cut B nitrile gloves.

Edit 04/12/2024

MAPA SAS capital de 35.000.010 €  
420, rue d'Estienne d'Orves  
92705 Colombes Cedex France  
RCS Nanterre 314 307 720

mapa-pro.com

**MAPA**  
PROFESSIONAL