

Product data sheet

Specifications



Repacked, shunt trip release with
OC contact, Acti9, MX+OF, 110VAC
to 415VAC, 110VDC to 130VDC

A9N26946W



This repacked option saves 0.466 over the
standard condition

Main

range of product	Acti9
Product or component type	Shunt trip release with OC contact
Device short name	MX + OF
Signal contacts composition	1 C/O
[In] rated current	3 A at 415 V, AC 6 A at <= 240 V, AC
[Uc] control circuit voltage	110...415 V AC 50/60 Hz 110...130 V DC
9 mm pitches	2

Complementary

Range compatibility	Acti9 iDPN Acti9 C120 Acti9 C40 Acti9 C60H-DC Acti9 C60NA-DC Acti9 C60PV-DC Acti9 DPN Vigi Acti9 DT40 Acti9 DT60 Acti9 ID C40 Acti9 IDc Acti9 ITG40 Acti9 ID Acti9 DPN
Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Comb busbar and distribution block compatibility	Top: YES
Height	82.5 mm
Width	18 mm
Depth	73.5 mm
Product weight	65 g
Colour	White
Connections - terminals	Screw clamp terminal (bottom) - 2 cable(s) 1.5 mm² - flexible Screw clamp terminal (bottom) - 2 cable(s) 1.5 mm² - flexible with ferrule Screw clamp terminal (bottom) - 1 cable(s) 0.5...2.5 mm² - rigid
Wire stripping length	9 mm for bottom connection
Tightening torque	1 N.m bottom

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Standards	EN/IEC 60947-2
Product certifications	ASTA ASEFA LCIE KEMA
Tropicalisation	2 conforming to EN/IEC 60947-2
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.200 cm
Package 1 Width	7.200 cm
Package 1 Length	8.300 cm
Package 1 Weight	62.000 g
Unit Type of Package 2	S01
Number of Units in Package 2	16
Package 2 Height	15.000 cm
Package 2 Width	15.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	1.180 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Lower carbon footprint

0.5 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

SCIP Number

9da5f8d9-d60f-424a-bb30-a856a097686c

EU RoHS Directive

[Compliant By Exemption](#)

REACH Regulation

[Reference contains Substances of Very High Concern above the threshold](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins