

Product datasheet

Specifications



Cable tie, Thorsman installation material, 200x4.8mm, black

IMT46412

Main

product range	Thorsman
Range of product	Thorsman installation material
product type	Cable tie
colour	Black
quantity per package	Set of 100

Complementary

Minimum tightening diameter	3 mm
Maximum tightening diameter	49.5 mm
Condition of use	Indoor/outdoor
resistance to tearing	Resistance to tearing: 230 N
Material	PA (polyamide) 6.6 UV-stabilised
Length	200 mm
Width	4.8 mm
Thickness	1.3 mm
Net weight	0.115 kg
Market segment	Small commercial

Environment

Environmental characteristic	Fire resistance needle flame 30 s conforming to IEC 60695-11-5
Flame retardance	Self-extinguishing conforming to UL 94 V2
Ambient air temperature for operation	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.000 cm
Package 1 Width	13.000 cm
Package 1 Length	24.000 cm
Package 1 Weight	122.000 g
Unit Type of Package 2	S35
Number of Units in Package 2	60

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Height	15.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	8.340 kg
Unit Type of Package 3	P12
Number of Units in Package 3	1440
Package 3 Height	105.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	209.000 kg

Contractual warranty

Warranty	18 mois
----------	---------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	1
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACH Regulation	REACH Declaration
Halogen content performance	Halogen free product
PVC free	Yes

Use Again

Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No