

Integra Plus EC

- Up to 70% heat recovery
- Low power consumption
- Effective condensation control
- 3 speed control
- Summer mode
- EC motors



Easy Installation

The Vent-Axia Integra Plus EC is designed for mounting in ceiling voids, lofts and above a suspended ceiling. Four 150mm spigots are provided for simple connection to insulated flexible or rigid ventilation ducting. The unit comes complete with a 22mm condensate outlet.

The Integra Plus EC incorporates two adjustable speeds and a Purge setting (full Speed).

Switching on the controller allows activation of the Summer Mode.

Controllers & Sensors

Model	Stock Ref
Ambient Response Humidistat	563550
Visionex PIR	459623


Model

Model	Stock Ref
Integra Plus EC	437666EC


SEC Class

Model	SEC Class	SEC Class (inc. LDC)
Integra Plus EC	B	A

Airflow Direction




Dimensions (mm)



A	ØB	C	D	E	F	G	H	I
580	150	100	64	125	350	125	305	85

Weight: 17kg fan box

Performance



Sound Data

		Octave band, Hz, dB SWL										SPL dB(A)
Flow, l/s	Unit setting V	Test mode	63	125	250	500	1k	2k	4k	8k	at 3m	
55	4	Supply	39.2	43.1	44.5	47.1	42.6	36.0	29.3	30.7	30.7	
		Extract	47.0	42.4	38.6	40.4	35.5	28.0	27.9	32.6	25.3	
		Breakout	43.2	42.7	38.2	37.6	33.4	28.4	27.6	31.5	21.7	
69	5	Supply	42.0	47.6	46.1	49.9	48.8	41.2	33.7	32.5	34.4	
		Extract	47.8	42.2	41.4	43.2	40.4	29.6	27.7	32.5	27.7	
		Breakout	45.2	45.7	41.9	40.7	37.3	30.5	27.5	32.4	23.8	
79	6	Supply	46.0	49.7	50.6	54.0	54.4	45.9	39.6	36.9	38.7	
		Extract	44.5	43.2	44.8	46.4	46.2	32.2	28.4	32.3	31.4	
		Breakout	46.2	47.2	44.3	43.4	43.1	32.8	28.5	32.2	26.6	
81	6.6	Supply	47.0	52.5	53.8	56.4	58.3	48.8	42.8	40.8	41.8	
		Extract	50.3	45.3	47.7	48.5	47.4	35.0	30.7	32.9	33.0	
		Breakout	45.5	47.9	45.5	45.5	45.5	34.0	29.2	31.5	28.3	
95	7	Supply	48.9	54.1	56.3	58.0	59.2	51.0	45.9	43.8	43.3	
		Extract	47.6	46.5	49.4	49.7	48.3	37.0	31.1	32.3	34.0	
		Breakout	49.0	49.5	48.2	47.5	47.3	36.7	31.1	32.3	30.1	
109	8	Supply	51.0	58.2	57.4	60.1	61.2	54.4	48.9	48.0	45.6	
		Extract	56.2	52.4	51.7	53.1	49.6	39.5	33.8	33.2	36.3	
		Breakout	51.8	53.9	51.3	50.7	48.7	40.3	34.0	32.5	32.2	
113	9	Supply	49.1	56.1	59.4	62.8	63.3	57.2	52.1	50.8	47.4	
		Extract	54.5	50.9	52.4	54.5	51.4	42.3	35.3	33.8	37.8	
		Breakout	53.6	54.3	52.8	52.3	50.8	43.4	36.2	33.5	34.1	

Tested according to BS848. Breakout quoted spherical. Supply and Extract quoted hemispherical.