




-0-0-	







	AMPHENOL AT06-4S	18.2
чуу		<u>, </u>

WIDARD MOLDED COLOR IS CREV

REVISIONS

DESCRIPTION

RELEASE NEW DWG FORMAT

REDUCED DIAMETER SEAL

REV

АЗ

ECO

STANDARD MOLDED COLOR IS GREY. ADDITIONAL COLORS SHOWN IN PART NUMBER CHART ARE AVAILABLE VIA SPECIAL ORDER.

NOTES: UNLESS OTHERWISE SPECIFIED

1 MATERIAL:

HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

- 2. MODIFICATIONS: REDUCED DIAMETER WIRE SEAL
- 3. SPECIFICATIONS:
 - 3.1 CURRENT RATING: 13 AMPS
 - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
 - 3.5 MOISTURE RESISTANCE: IP67 (MATED CONDITION)
 - 3.6 MATING CYCLE DURABILITY: 100 CYCLES
 - 3.7 RoHS COMPLIANT
- 4. MATING PART: AT04-4P* RECEPTACLE (* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

•		R SEAL WIRE	

_				
	CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL
	SIZE	O.D.	O.D.	WIRE RANGE
	16	1.35 mm (.053 in)	3.05 mm (.120 in)	14 - 20 AWG

PART NUMBER CHART					
COLOR	PART NUMBER				
GREY	AT06-4S-RD01				
BLACK	AT06-4S-RD01BLK				
BLUE	AT06-4S-RD01BLU				
BROWN	AT06-4S-RD01BRN				
GREEN	AT06-4S-RD01GRN				
RED	AT06-4S-RD01RED				
WHITE	AT06-4S-RD01WHT				
YELLOW	AT06-4S-RD01YEL				

	SEE PART N	UMBER CHART							
	PART NUMBER		DESCRIPTION		ITEM				
QUANTITY MATERIALS LIST									
UNLESS OTHERWISE SPECIFIED JAII dirensories are in matriciprim). 2) Tolerances are as follows: 1) FLOEG JO.30 2 PL.DEG JO.30 3) Note reference = MATERIAL SPECIFICATIONS: PROCESS SPECIFICATIONS:		SIGNATUR	ES	DATE	Amphopol		I		
		D.PARKS		11DEC13	Amphenol				
		CHECKED:			Sine Systems - www.amphenol-sine.com				
		ENGINEER:			44724 Morley Drive				
		APPROVAL:			Clinton Township, MI 48036				
		CUSTOMER:	PLUG, 4 SOCKET, AT SERIES,						
		SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO MORMAI		REDUCED DIAMETER WIRE SEAL			\L		
				В	C-	AT06-4S-RI	D01XXX	A3	
NEXT ASS'Y:		MANUFACTURING VARIATIONS.		SCALE: NO	SNE		sнеет 1	or 1	

PLUG, 4 SOCKET, AT SERIES, REDUCED DIA. WIRE SEAL

APPR

DRP

DATE

11DEC13