
Product datasheet

Specifications



auxiliary contact, FuPacT ISFT100-630 / ISFL250-1250, 1 changeover contact NO/NC, 2A

LV480841

EAN Code: 3606481010964

Main

Range	FuPacT
Product or component type	Auxiliary contact
Device application	Remote indication
Range compatibility	FuPacT ISFT100N fuse-switch disconnector FuPacT ISFT100 fuse-switch disconnector FuPacT ISFT250 fuse-switch disconnector FuPacT ISFT400 fuse-switch disconnector FuPacT ISFT630 fuse-switch disconnector FuPacT ISFL250 fuse-switch disconnector FuPacT ISFL400 fuse-switch disconnector FuPacT ISFL630 fuse-switch disconnector FuPacT ISFL1250 fuse-switch disconnector
Auxiliary contacts type	Standard
contact function	Changeover contact
Signal contacts composition	1 NO/NC

Complementary

output contact breaking capacity	AC-12: 6 A at 24 V AC-12: 6 A at 48 V AC-12: 6 A at 110 V AC-12: 6 A at 220/240 V AC-15: 2 A at 24 V AC-15: 2 A at 48 V AC-15: 2 A at 110 V AC-15: 2 A at 220/240 V DC-12: 3 A at 24 V DC-12: 1 A at 48 V DC-12: 0.4 A at 110 V DC-12: 0.2 A at 220/240 V
Minimum load	3 mA at 24 V
[Ui] rated insulation voltage	250 V
Kit composition	Mounting accessory Housing
Standards	IEC 60947-5-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.800 cm
Package 1 Width	2.400 cm
Package 1 Length	3.200 cm
Package 1 Weight	7.000 g

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 2	S02
Number of Units in Package 2	100
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	960.000 g
Unit Type of Package 3	P12
Number of Units in Package 3	1600
Package 3 Height	45.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	27.360 kg

Logistical informations

Country of origin	DE

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
POP Directive	**No POPs**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**